

according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Trade name :	NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil
Product code :	902461
1.2 Relevant identified uses of the s	ubstance or mixture and uses advised against
Use of the substance/mixture :	Engine, gear & lubricating oil.
1.3 Details of the supplier of the safe	ety data sheet
Company :	Ellis Enterprises B.V., an affiliate of Valvoline Global Operations Wieldrechtseweg 39 3316 BG Dordrecht Netherlands
Telephone :	+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
E-mail address of person : responsible for the SDS	SDS@valvolineglobal.com

### 1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

# **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### **Additional Labelling**

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 70 - < 80
DECENE-1 HOMOPOLYMER HYDROGENATED	68037-01-4 500-183-1 01-2119486452-34- xxxx	Asp. Tox. 1; H304	>= 10 - < 15
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 5 - < 10
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0	Revision Date: 27.07.2023	Print D	Date: 16/10/2023
C14-16-18 Alkyl phenol	Not Assigned	Skin Sens. 1B; H317	>= 1 - < 2.5
	01-2119498288-19- xxxx	STOT RE 2; H373 (Liver)	

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

4.1 Description of first aid mea	asures
General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	<ul> <li>If unconscious, place in recovery position and seek medical advice.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Flush eyes with water as a precaution.</li> <li>Remove contact lenses.</li> <li>Protect unharmed eye.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>
If swallowed	<ul> <li>Keep respiratory tract clear.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> <li>If symptoms persist, call a physician.</li> <li>Take victim immediately to hospital.</li> </ul>
4.2 Most important symptoms	and effects, both acute and delayed
Symptoms	: No symptoms known or expected.
4.3 Indication of any immediat	te medical attention and special treatment needed
Treatment	: No hazards which require special first aid measures.
	Treat symptomatically.



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

# **SECTION 5: Firefighting measures**

5.1	Extinguishing media Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
	Unsuitable extinguishing media	:	High volume water jet
5.2	Special hazards arising from Hazardous combustion products		e substance or mixture carbon dioxide and carbon monoxide Nitrogen oxides (NOx)
5.3	Advice for firefighters Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
	Further information	:	Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

# **SECTION 6: Accidental release measures**

Personal precautions

#### 6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions	
Environmental precautions :	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for conta	inment and cleaning up
Methods for cleaning up :	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

: Refer to protective measures listed in sections 7 and 8.

Use personal protective equipment.



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

# **SECTION 7: Handling and storage**

7.1 Preca	utions for safe handling	g	
Advic	e on safe handling	:	Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
	e on protection against nd explosion	:	Normal measures for preventive fire protection.
Hygie	ene measures	:	Wash hands before breaks and at the end of workday.
7.2 Condi	tions for safe storage, i	incl	uding any incompatibilities
	irements for storage and containers	:	Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
	er information on ge stability	:	No decomposition if stored and applied as directed.
7.3 Speci	fic end use(s)		
Spec	ific use(s)	:	No data available

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

# Personal protective equipment

Eye/face protection	:	Eye wash bottle with pure water
		Tightly fitting safety goggles

Hand protection



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
Material Break through time Glove thickness Directive	<ul> <li>neoprene, nitrile rubber</li> <li>&gt;= 240 min</li> <li>&gt;= 0.35 mm</li> <li>Equipment should conform to EN 374</li> </ul>	
Remarks	<ul> <li>The selected protective gloves have to s specifications of Regulation (EU) 2016/4 EN 374 derived from it. Gloves should be replaced if there is any indication of degre breakthrough. Please observe the instrupermeability and breakthrough time which the supplier of the gloves. Also take into specific local conditions under which the such as the danger of cuts, abrasion, an The data about break through time/strens standard values! The exact break through material has to be obtained from the proprotective glove.</li> <li>The suitability for a specific workplace sh with the producers of the protective glove.</li> </ul>	25 and the standard e discarded and radation or chemical ctions regarding ch are provided by consideration the product is used, d the contact time. gth of material are h time/strength of ducer of the
Skin and body protection	: Impervious clothing Choose body protection according to the concentration of the dangerous substance	
Respiratory protection	: No personal respiratory protective equip required.	ment normally

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	No data available
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	No data available



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
Boiling point/boiling range	: No data available	
Flash point	: 204 °C Method: Pensky-Martens closed cup	
Evaporation rate	: No data available	
Flammability (solid, gas)	: No data available	
Upper explosion limit / Upper flammability limit	: No data available	
Lower explosion limit / Lower flammability limit	: No data available	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: 0.841 g/cm3 (15.6 °C)	
Solubility(ies) Water solubility	: immiscible	
Solubility in other solvents	: No data available	
Partition coefficient: n- octanol/water	: No data available	
Decomposition temperature	: No data available	
Viscosity Viscosity, dynamic	: No data available	
Viscosity, kinematic	: 39.7 mm2/s (40 °C) Method: ASTM D 445	
Oxidizing properties	: No data available	
9.2 Other information		
Self-ignition	: No data available	



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

# **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

#### 10.4 Conditions to avoid

Conditions to avoid :	None known.

#### 10.5 Incompatible materials

Materials to avoid

: Strong bases Strong oxidizing agents

#### **10.6 Hazardous decomposition products**

No hazardous decomposition products are known.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

#### Components:

### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity	:	LD50 (Rat): > 15 g/kg
Acute dermal toxicity	÷	LD50 (Rabbit): > 5 g/kg

### DECENE-1 HOMOPOLYMER HYDROGENATED:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): > 5.2 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute	
8/22		



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0	Revision Date: 27.07.2023	Print Date: 16/10/2023		
Acute dermal toxicity	inhalation toxicity : LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mix toxicity	xture has no acute dermal		
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:				

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.

# Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

•		
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Remarks: No mortality observed at this dose.
Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: The toxicological data has been taken from products of similar composition.

# C14-16-18 Alkyl phenol:

Acute oral toxicity	<ul> <li>LD50 (Rat): &gt; 2,000 mg/kg</li> <li>Assessment: The substance or mixture has no acute oral toxicity</li> </ul>
Acute dermal toxicity	<ul> <li>LD50 (Rat): &gt; 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: No mortality observed at this dose.</li> </ul>

# Skin corrosion/irritation

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

#### **Components:**

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment	Slight, transient irritation
Result	Slight, transient irritation

#### DECENE-1 HOMOPOLYMER HYDROGENATED:

Species Result	:	Rabbit
Result	:	No skin irritation

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species Result	:	Rabbit No skin irritation

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

-	
Species	: Rabbit
Result	Mild skin irritation
Species Result Remarks	The toxicological data has been taken from products of similar
	composition.

#### C14-16-18 Alkyl phenol:

Method : Result :	OECD Test Guideline 431
Result :	No skin irritation

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment	:	No eye irritation
Result	:	No eye irritation

#### DECENE-1 HOMOPOLYMER HYDROGENATED:

Species Result	:	Rabbit
Result	:	Slight, transient irritation

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species Result	:	Rabbit
Result	:	No eye irritation



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species	: Rabbit
Species Result Remarks	: Slight, transient irritation
Remarks	: The toxicological data has been taken from products of similar
	composition.

### C14-16-18 Alkyl phenol:

Species Result	:	Rabbit
Result	:	Slight, transient irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Product:

Assessment

: Does not cause skin sensitisation.

#### **Components:**

#### DECENE-1 HOMOPOLYMER HYDROGENATED:

Test Type: Maximisation TestSpecies: Guinea pigAssessment: Does not cause skin sensitisation.Method: OECD Test Guideline 406	Test Type Species Assessment Method	<ul><li>Guinea pig</li><li>Does not cause skin sensitisation.</li></ul>
--	--	---

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type : Species :	Buehler Test
Species :	Guinea pig
	Does not cause skin sensitisation.

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species	: Guinea pig
Assessment	Does not cause skin sensitisation.
Method	: OECD Test Guideline 406
Remarks	: The toxicological data has been taken from products of similar composition.



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

### C14-16-18 Alkyl phenol:

Test Type Species Assessment Method	<ul> <li>Local lymph node assay</li> <li>Mouse</li> <li>The product is a skin sensitiser, sub-category 1B.</li> <li>OECD Test Guideline 429</li> </ul>
--	--

# Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

#### **DECENE-1 HOMOPOLYMER HYDROGENATED:**

Genotoxicity in vitro :	Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative
-------------------------	--

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro	:	Test Type: Ames test Test system: Salmonella typhimurium
		Metabolic activation: with and without metabolic activation Result: negative

#### C14-16-18 Alkyl phenol:

Genotoxicity in vitro	: Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative
	Result. Regative

#### Carcinogenicity

Not classified based on available information.

### **Components:**

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

# 

# Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### **Components:**

#### C14-16-18 Alkyl phenol:

Target Organs Assessment	<ul> <li>Liver</li> <li>The substance or mixture is classified as specific target organ</li> </ul>
	toxicant, repeated exposure, category 2.

### Aspiration toxicity

Not classified based on available information.

#### **Components:**

### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

### DECENE-1 HOMOPOLYMER HYDROGENATED:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

### Further information

Product:

Remarks

: No data available



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

# **SECTION 12: Ecological information**

### 12.1 Toxicity

### **Ecotoxicology Assessment**

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

#### **Components:**

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

	·, - ·	
Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC: 10 mg/l Species: Fish
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 10 mg/l Species: Aquatic invertebrates

#### **Ecotoxicology Assessment**

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

#### DECENE-1 HOMOPOLYMER HYDROGENATED:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l Exposure time: 96 h Test Type: semi-static test Test substance: WAF	
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h Test Type: static test	
	14 / 22	



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

ersion: 3.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
	Test substance: WAF Method: OECD Test Guideline 202	
Toxicity to algae/aquatic plants	: EL50 (Scenedesmus capricornutum (fro 1,000 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201	esh water algae)): >
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOELR: 125 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211	

# **Ecotoxicology Assessment**

Acute aquatic toxicity	÷	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

# LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

ersion: 3.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
Toxicity to fish (Chronic toxicity)	: NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rai	nbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211	
Ecotoxicology Assessment		
Acute aquatic toxicity	: Not classified based on available in	formation.
Chronic aquatic toxicity	: Not classified based on available in	formation.
Reaction products of Benze	eamine, N-phenyl- with nonene (brai	nched):
Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 10 Exposure time: 96 h Test Type: static test Remarks: The toxicological data ha products of similar composition.	
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea) Exposure time: 48 h Test Type: static test Test substance: WAF	): > 100 mg/l
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapir End point: Growth inhibition Exposure time: 72 h Test Type: static test	tata (algae)): 600 mg/l
Ecotoxicology Assessment		
Acute aquatic toxicity	: Not classified based on available in	formation.
Chronic aquatic toxicity	: Chronic aquatic toxicity Category 4; harmful effects to aquatic life.	May cause long lasting

# C14-16-18 Alkyl phenol:

Toxicity to fish	:	LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static test
		Test substance: WAF



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
Toxicity to daphnia and other aquatic invertebrates Toxicity to algae/aquatic plants	<ul> <li>EC50 (Daphnia magna (Water flea)): &gt; 1 Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202</li> <li>EC50 (Pseudokirchneriella subcapitata (a End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF</li> </ul>	
Ecotoxicology Assessment		
Acute aquatic toxicity	: Not classified based on available information	ation.
Chronic aquatic toxicity	: Not classified based on available informa	ation.

### 12.2 Persistence and degradability

### **Components:**

# DECENE-1 HOMOPOLYMER HYDROGENATED:

Biodegradability	: Result: Inherently biodegradable.

# LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability	Biodegra Exposur	Not readily biodegradable. adation: 2 - 4 % re time: 28 d
	Method:	OECD Test Guideline 301B

### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 0 % Exposure time: 28 d
	Method: OECD Test Guideline 301B

# C14-16-18 Alkyl phenol:

Biodegradability	:	Result: Readily biodegradable. Remarks: Expert judgement



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

#### 12.3 Bioaccumulative potential

Components:

### DECENE-1 HOMOPOLYMER HYDROGENATED:

Partition coefficient: n- : log Pow: > 6.5 octanol/water

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n- octanol/water	:	log Pow: > 7.5	
octanol/water			

#### C14-16-18 Alkyl phenol:

```
Partition coefficient: n- : log Pow: > 7.2
octanol/water
```

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### Product:

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

Product:	
Endocrine disrupting potential	: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Additional ecological information	: No data available

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0	Revision Date: 27.07.2023	Print Date: 16/10/2023	
Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways o chemical or used container. Send to a licensed waste management of		
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.		

# **SECTION 14: Transport information**

# 14.1 UN number

	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.2	2 UN proper shipping name		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)			
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.4	Packing group		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA (Cargo)	:	Not regulated as a dangerous good
	IATA_P (Passenger)	:	Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions	(Ai	nnex 17)	:	Not applicable
UK REACH Candidate list of s concern (SVHC) for Authorisa		, ,	:	Not applicable
The Persistent Organic Polluta Regulation (EU) 2019/1021 as Britain)			:	Not applicable
Regulation (EC) No 1005/200 deplete the ozone layer	9 oi	n substances that	:	Not applicable
UK REACH List of substances (Annex XIV)	S SU	bject to authorisation	:	Not applicable
Control of Major Accident Haz 2015 (COMAH)	ard	s Regulations	Not	applicable
The components of this pro	duc	ct are reported in the fo	ollo	wing inventories:
TCSI	:	On the inventory, or in	cor	npliance with the inventory
TSCA	:	All substances listed a	is ac	ctive on the TSCA inventory
AIIC	:	On the inventory, or in	cor	npliance with the inventory
DSL	:	All components of this	pro	duct are on the Canadian DSL



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0	Revision Date: 27.07.2023	Print Date: 16/10/2023
ENCS	: On the inventory, or in compliance	with the inventory
KECI	: On the inventory, or in compliance	with the inventory
PICCS	: On the inventory, or in compliance	with the inventory
IECSC	: On the inventory, or in compliance	with the inventory
NZIoC	: Not in compliance with the inventor	y

### 15.2 Chemical safety assessment

#### No data available

#### Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

### **SECTION 16: Other information**

### **Full text of H-Statements**

H304	:	May be fatal if swallowed and enters airways.
H317	:	May cause an allergic skin reaction.
H373	:	May cause damage to organs through prolonged or repeated
		exposure.
H413	:	May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Aquatic Chronic :	Long-term (chronic) aquatic hazard
Asp. Tox. :	Aspiration hazard
Skin Sens. :	Skin sensitisation
STOT RE :	Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization;



according to Regulation (EC) No. 1907/2006 NAPA® N2461000L JL 0W20 ECO LS Synthetic Motor Oil

Version: 3.0

Revision Date: 27.07.2023

Print Date: 16/10/2023

IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified: NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT -Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration. Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very **Bioaccumulative** 

### Further information

Internal information : 000000278102

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN