

according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0

Revision Date: 03.10.2023

Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	:	NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL
Product code	:	902513
		ubstance or mixture and uses advised against
Use of the substance/mixture	:	Engine, gear & lubricating oil.
1.3 Details of the supplier of the	saf	ety data sheet
Company	:	Ellis Enterprises B.V., an affiliate of Valvoline Global Operations Wieldrechtseweg 39 3316 BG Dordrecht Netherlands
Telephone	:	+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
E-mail address of person responsible for the SDS	:	SDS@valvolineglobal.com

1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0

Revision Date: 03.10.2023

Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl, DI-TERT-BUTYL POLYSULFIDE. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 25 - < 40
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 5 - < 10
DI-TERT-BUTYL POLYSULFIDE	68937-96-2 273-103-3 01-2119540515-43- xxxx	Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 2.5 - < 5



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0

Revision Date: 03.10.2023

Print Date: 16/10/2023

		specific concentration limit Skin Sens. 1B >= 46 %	
Reaction products of 4-methyl-2- pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl	Not Assigned 931-384-6 01-2119493620-38- xxxx	Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 2; H411 2 > 50 - 100 % specific concentration limit Skin Sens. 1 > 9.39 %	>= 1 - < 2.5
ARYL THIOPHOSPHATE	597-82-0 209-909-9 01-2119979545-21- xxxx	Repr. 2; H361	>= 0.1 - < 0.5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.		
If inhaled	 If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician. 		
In case of skin contact	If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.		
In case of eye contact	 Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. 		
3 / 23			



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Revis	sion Date: 03.10.2023	Print Date: 16/10/20
	It	ave irritation persiste consult	
		eye irritation persists, consult	a specialist.
If swallowed		eep respiratory tract clear.	
		o not give milk or alcoholic bev	
		ever give anything by mouth to symptoms persist, call a physi	
		ake victim immediately to hosp	
	In	iduce vomiting immediately an	d call a physician.
4.2 Most important symptoms a	nd effe	ects, both acute and delayed	
Symptoms	: N	o symptoms known or expecte	ed.
1.2 Indication of any immediate	modia	al attention and anapial treat	mont noodod
4.3 Indication of any immediate Treatment		o hazards which require specia	
rieathent		o nazarus wnich require speci	ai ilist alu illeasules.
	Т	reat symptomatically.	
SECTION 5: Firefighting mean 5.1 Extinguishing media Suitable extinguishing media	: U	se water spray, alcohol-resista	int foam, dry chemical or
	Ca	arbon dioxide.	
Unsuitable extinguishing media	: H	igh volume water jet	
5.2 Special hazards arising from	the su	ubstance or mixture	
Specific hazards during	: D	o not allow run-off from fire fig	hting to enter drains or water
firefighting	CC	ourses.	
Hazardous combustion products	: Ca	arbon dioxide and carbon mon	oxide
5.3 Advice for firefighters			
Special protective equipment	: W	/ear self-contained breathing a	pparatus for firefighting if

 for firefighters
 necessary.

 Further information
 : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

 Fire residues and contaminated fire extinguishing water must



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0

Revision Date: 03.10.2023

Print Date: 16/10/2023

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Revision Date: 03.10.2023	Print Date: 16/10/2023
7.2 Conditions for safe storage	e, including any incompatibilities	
Requirements for storage areas and containers	 Keep container tightly closed in a place. Observe label precautions working materials must comply w standards. 	. Electrical installations /
Further information on storage stability	: No decomposition if stored and a	pplied as directed.
7.3 Specific end use(s) Specific use(s)	: No data available	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
DIISOOCTYL ADIPATE	Soil	0.865 mg/kg

8.2 Exposure controls

Personal p	protective	equipment
------------	------------	-----------

Eye/face protection	:	Eye wash bottle with pure water Tightly fitting safety goggles
Hand protection Material Break through time Glove thickness Directive	:	neoprene, nitrile rubber >= 240 min >= 0.35 mm Equipment should conform to EN 374
Remarks	:	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Revision Date: 03.10.2023	Print Date: 16/10/2023
	The data about break through tim standard values! The exact break material has to be obtained from protective glove. The suitability for a specific workp with the producers of the protective	through time/strength of the producer of the blace should be discussed
Skin and body protection	: Impervious clothing Choose body protection according concentration of the dangerous s	•
Respiratory protection	: No personal respiratory protective required.	e equipment normally

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	oily
Odour Threshold	:	No data available
рН	:	Not applicable
Pour point	:	< -45 °C
Boiling point/boiling range	:	No data available
Flash point	:	164 °C Method: Cleveland open cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Revision Date: 03.10.2023	Print Date: 16/10/2023
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Relative density	: No data available	
Density	: 0.877 g/cm3 (15 °C)	
Bulk density	: Not applicable	
Solubility(ies) Water solubility	: insoluble	
Solubility in other solvents	: No data available	
Partition coefficient: n- octanol/water	: No data available	
Decomposition temperature	: No data available	
Viscosity Viscosity, dynamic	: No data available	
Viscosity, kinematic	: 104 mm2/s (40 °C)	
Oxidizing properties	: No data available	
9.2 Other information Self-ignition	: No data available	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Revision Date: 03.10.2023	Print Date: 16/10/2023
Conditions to avoid	: None known.	
10.5 Incompatible materials Materials to avoid	: Strong oxidizing agents	
10.6 Hazardous decompositic No hazardous decompositi	•	

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: > 2,000 mg/kg
		Method: Calculation method

Components:

Ш

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity	: LD50 (Rat): > 15 g/kg
Acute dermal toxicity	: LD50 (Rabbit): > 5 g/kg

DI-TERT-BUTYL POLYSULFIDE:

Acute oral toxicity	:	LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 401



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Revision Date: 03.10.2023	Print Date: 16/10/2023
Acute dermal toxicity	Assessment: The substance or r toxicity Remarks: No mortality observed : LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 4 Assessment: The substance or r toxicity Remarks: No mortality observed	nixture has no acute oral at this dose. 02 nixture has no acute dermal

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl:

Acute oral toxicity :	LD50 (Rat): ca. 2,000 mg/kg Method: OECD Test Guideline 401 Assessment: The component/mixture is moderately toxic after single ingestion.

ARYL THIOPHOSPHATE:

Acute oral toxicity	:	LD50 (Rat): > 10,000 mg/kg
Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: The toxicological data has been taken from products of similar composition.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species :	Rabbit
Species : Result :	No skin irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment Result	:	Slight, transient irritation
Result	:	Slight, transient irritation

DI-TERT-BUTYL POLYSULFIDE:



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Re	evision Date: 03.10.2023	Print Date: 16/10/2023
Result	•	Mild skin irritation	
ARYL THIOPHOSPHATE:			
Species Result	:	Rabbit Slight, transient irritation	
Serious eye damage/eye irr Not classified based on availa			
Product:		No. 2. 1. Martin	
Result	:	No eye irritation	
Remarks	:	Vapours may cause irritation to the eyes, and the skin.	respiratory system
Components:			
LUBRICATING OILS, PETRO	OLE	UM, C20-50, HYDROTREATED:	
Species	:	Rabbit	
Result	:	No eye irritation	
	/I), H	IYDROTREATED HEAVY PARAFFINIC:	
Assessment	:	No eye irritation	
Result	:	No eye irritation	
DI-TERT-BUTYL POLYSULF			
Result			
Result	•	Slight, transient irritation	
with diphosphorus pentaoxide		pentanol and diphosphorus pentasulfide, p nd salted by amines, C12-14-tert-alkyl:	ropoxylated, esterified
Result	:	Eye irritation	
ARYL THIOPHOSPHATE:			
Species	•	Rabbit	
Result		No eye irritation	



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0

Revision Date: 03.10.2023

Print Date: 16/10/2023

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Assessment

: Does not cause skin sensitisation.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type	: Buehler Test
Species	: Guinea pig
Assessment	Does not cause skin sensitisation.

DI-TERT-BUTYL POLYSULFIDE:

Test Type Species	Maximisation Test Guinea pig
	The product is a skin sensitiser, sub-category 1B. OECD Test Guideline 406

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl:

Assessment :	The product is a skin sensitiser, sub-category 1B.

ARYL THIOPHOSPHATE:

Test Type Species Assessment	: Maximisation Test
Species	: Guinea pig
Assessment	Does not cause skin sensitisation.
Method	: Directive 67/548/EEC, Annex V, B.6.
Method Remarks	The toxicological data has been taken from products of similar
	composition.

Germ cell mutagenicity

Not classified based on available information.

Components:

DI-TERT-BUTYL POLYSULFIDE:



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Revision Date: 03.10.2023	Print Date: 16/10/2023
Genotoxicity in vitro Genotoxicity in vivo	 Test Type: in vitro assay Result: Positive results were obtained in Test Type: Micronucleus test Species: Mouse Cell type: Bone marrow Method: OECD Test Guideline 474 	some in vitro tests.
ARYL THIOPHOSPHATE:	Result: negative	
Genotoxicity in vitro	: Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without m Result: negative Remarks: The toxicological data has bee products of similar composition.	
Carcinogenicity		

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Carcinogenicity - Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

Components:

ARYL THIOPHOSPHATE:

Reproductive toxicity -	:	Some evidence of adverse effects on sexual function and
Assessment		fertility, and/or on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0

Revision Date: 03.10.2023

Print Date: 16/10/2023

Aspiration toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks

: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish	 LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Re	evision Date: 03.10.2023	Print Date: 16/10/2023
		Test substance: WAF Method: OECD Test Guideline 202	
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201	(green algae)): >=
Toxicity to fish (Chronic toxicity)	:	NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow	ν trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211	
Ecotoxicology Assessment			
Acute aquatic toxicity	:	Not classified based on available information	ation.
Chronic aquatic toxicity	:	Not classified based on available information	ation.
DISTILLATES (PETROLEUN	1), H	HYDROTREATED HEAVY PARAFFINIC:	
Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 r Exposure time: 48 h	ng/l
Toxicity to algae/aquatic plants	:	EL50 (Algae, algal mat (Algae)): > 100 n Exposure time: 72 h	ng/l
Toxicity to fish (Chronic toxicity)	:	NOEC: 10 mg/l Species: Fish	

Toxicity to daphnia and other : NOEC: 10 mg/l aquatic invertebrates Species: Aquatic invertebrates (Chronic toxicity)



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

/ersion: 4.0	Revision Date: 03.10.2023	Print Date: 16/10/2023
Ecotoxicology Assessment		
Acute aquatic toxicity	: Not classified based on available in	nformation.
Chronic aquatic toxicity	: Not classified based on available in	nformation.

DI-TERT-BUTYL POLYSULFIDE:

Ecotoxicology Assessment

Acute aquatic toxicity	:	Harmful to aquatic life.
		Acute aquatic toxicity Category 3; Harmful to aquatic life.
Chronic aquatic toxicity	:	Harmful to aquatic life with long lasting effects.
		Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl:

· · · · ·		
Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): ca. 24 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): ca. 91.4 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 15 mg/l End point: Growth inhibition Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 201 NOEC (Pseudokirchneriella subcapitata (green algae)): 3.3 mg/l End point: Growth inhibition Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 201



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Revision Date: 03.10.2023 Print Date: 16/10/2		
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 0.12 mg/l End point: Reproduction Test Exposure time: 21 d Species: Daphnia magna (Water fle Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211	ea)	
Ecotoxicology Assessment			
Acute aquatic toxicity	: Toxic to aquatic life.		
Chronic aquatic toxicity	: Toxic to aquatic life with long lasting	g effects.	
ARYL THIOPHOSPHATE:			
Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 1 Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203		
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea) Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202		
Toxicity to algae/aquatic plants	: EC50 (Desmodesmus subspicatus End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201	(green algae)): > 100 mg/l	
Ecotoxicology Assessment Acute aquatic toxicity	:		
Chronic aquatic toxicity	 Not classified based on available in This product has no known ecotoxic toxicity at the limit of solubility Not classified based on available in 	cological effects., No	



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0

Ш

...

Revision Date: 03.10.2023

Print Date: 16/10/2023

12.2 Persistence and degradability

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability	:	Result: Not readily biodegradable.
		Biodegradation: 2 - 4 %
		Exposure time: 28 d
		Method: OECD Test Guideline 301B

DI-TERT-BUTYL POLYSULFIDE:

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 13 %
		Exposure time: 28 d Method: OECD Test Guideline 301B

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl:

Biodegradability	: Result: Not readily biodegradable.
	Biodegradation: 7.4 %
	Exposure time: 28 d
	Method: Modified Sturm Test

ARYL THIOPHOSPHATE:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 18 % Exposure time: 28 d
	Method: OECD Test Guideline 301B
	Biodegradation: 59.9 - 66.8 % Exposure time: 28 d Method: OECD Test Guideline 302C

12.3 Bioaccumulative potential

Components:

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl:

Partition coefficient: n- : Remarks: No data available octanol/water

ARYL THIOPHOSPHATE:



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Re	evision Date: 03.10.2023	Print Date: 16/10/2023
Bioaccumulation	:	Bioconcentration factor (BCF): 2,551	
Partition coefficient: n- octanol/water	÷	log Pow: 5.0	
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB as	sse	ssment	
Product:			
Assessment	:	This substance/mixture contains no com to be either persistent, bioaccumulative a very persistent and very bioaccumulative 0.1% or higher.	and toxic (PBT), or
12.6 Other adverse effects			
Product:			
Endocrine disrupting potential	:	The substance/mixture does not contain considered to have endocrine disrupting to REACH Article 57(f) or Commission D (EU) 2017/2100 or Commission Regulation levels of 0.1% or higher.	properties according elegated regulation
Additional ecological information	:	No data available	

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0

Revision Date: 03.10.2023

Print Date: 16/10/2023

SECTION 14: Transport information

14.1 UN number

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA_P (Passenger)	:	Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable for product as supplied.



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0

Revision Date: 03.10.2023

Print Date: 16/10/2023

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Not applicable
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	Not	applicable

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	Not in compliance with the inventory
DSL	:	This product contains the following components that are not on the Canadian DSL nor NDSL.



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0	Revision Date: 03.10.2023	Print Date: 16/10/2023
	ANGLAMOL 2000	
ENCS	: On the inventory, or in compliance w	vith the inventory
KECI	: On the inventory, or in compliance w	vith the inventory
PICCS	: On the inventory, or in compliance w	vith the inventory
IECSC	: On the inventory, or in compliance w	vith the inventory
NZIoC	: Not in compliance with the inventory	,

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H317 H319 H361 H411 H412	 May cause an allergic skin reaction. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
H302 H304	Harmful if swallowed.May be fatal if swallowed and enters airways.
H302	· Harmful if swallowed

Full text of other abbreviations

Acute toxicity
Long-term (chronic) aquatic hazard
Aspiration hazard
Eye irritation
Reproductive toxicity
Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European



according to Regulation (EC) No. 1907/2006 NAPA® N301199L 75W90 SS SYNTHETIC GEAR OIL

Version: 4.0

Revision Date: 03.10.2023

Print Date: 16/10/2023

Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization: ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information : 000000272363

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN