

according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® N3115L HD 75W80

SYNTHETIC BLEND GEAR OIL

Product code : 902379

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Gear and lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global

Operations

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

SDS@valvolineglobal.com

# 1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Long-term (chronic) aquatic hazard,

H412: Harmful to aquatic life with long lasting effects.

Category 3



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

## 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### **Additional Labelling**

EUH208 Contains Alkylamine trialkyldithiophosphate phosphate. May produce an allergic

reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8 265-158-7 649-468-00-3 01-2119487077-29- xxxx	Asp. Tox. 1; H304	>= 25 - < 40
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25-	Asp. Tox. 1; H304	>= 1 - < 2.5



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

	XXXX		
Distillates (petroleum), solvent- dewaxed light paraffinic	64742-56-9 265-159-2 649-469-00-9	Asp. Tox. 1; H304	>= 1 - < 2.5
Alkylamine trialkyldithiophosphate phosphate	Not Assigned	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 0.5 - < 1
OLEYLAMINE	112-90-3 204-015-5 612-283-00-3	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Liver, Gastrointestinal tract, Immune system) Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	>= 0.1 - < 0.25

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

carbon dioxide and carbon monoxide

## 5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.

Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

## **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety

standards.

Advice on common storage : No materials to be especially mentioned.



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

## **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

Contains no substances with occupational exposure limit values.

## 8.2 Exposure controls

## Personal protective equipment

Eye/face protection : Safety glasses

Skin and body protection : Protective suit

Respiratory protection : No personal respiratory protective equipment normally

required.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH : Not applicable

Pour point : < -42 °C

Boiling point/boiling range : No data available

Flash point : 222 °C

Method: Cleveland open cup



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.8638 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 47.5 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No decomposition if stored and applied as directed.



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

## 10.2 Chemical stability

No decomposition if stored and applied as directed.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

## 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

## **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

#### **Acute toxicity**

Not classified based on available information.

## **Components:**

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

## Distillates (petroleum), solvent-dewaxed light paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

## Alkylamine trialkyldithiophosphate phosphate:



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Acute oral toxicity : Assessment: The component/mixture is moderately toxic after

single ingestion.

**OLEYLAMINE:** 

Acute oral toxicity : LD50 (Rat): 1,950 mg/kg

Remarks: The toxicological data has been taken from

products of similar composition.

Skin corrosion/irritation

Not classified based on available information.

**Components:** 

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:** 

Assessment : Slight, transient irritation Result : Slight, transient irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

Assessment : Slight, transient irritation Result : Slight, transient irritation

Distillates (petroleum), solvent-dewaxed light paraffinic:

Species : Rabbit

Result : Slight, transient irritation

**OLEYLAMINE:** 

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:** 

Assessment : Slight, transient irritation Result : Slight, transient irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

Assessment : No eye irritation Result : No eye irritation



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Distillates (petroleum), solvent-dewaxed light paraffinic:

Species : Rabbit

Result : Slight, transient irritation

Alkylamine trialkyldithiophosphate phosphate:

Result : Corrosive

**OLEYLAMINE:** 

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

**Components:** 

Distillates (petroleum), solvent-dewaxed light paraffinic:

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Alkylamine trialkyldithiophosphate phosphate:

Assessment : The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

**Components:** 

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:** 

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

## **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

## Distillates (petroleum), solvent-dewaxed light paraffinic:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Components:

## **OLEYLAMINE:**

Target Organs : Gastro-intestinal system, Liver, Immune system

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

#### **Aspiration toxicity**

Not classified based on available information.

#### **Components:**

#### HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

## **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

May be fatal if swallowed and enters airways.

## Distillates (petroleum), solvent-dewaxed light paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **OLEYLAMINE:**

May be fatal if swallowed and enters airways.



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC **BLEND GEAR OIL** 

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

**Further information** 

**Product:** 

: No data available Remarks

## **SECTION 12: Ecological information**

## 12.1 Toxicity

## Product:

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**Components:** 

**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:** 

**Ecotoxicology Assessment** 

Not classified based on available information. Acute aquatic toxicity

Chronic aquatic toxicity Not classified based on available information.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** 

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC: 10 mg/l

Species: Fish

Toxicity to daphnia and other :

NOEC: 10 mg/l

aquatic invertebrates

Species: Aquatic invertebrates

12/20



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

(Chronic toxicity)

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), solvent-dewaxed light paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEL: 10 mg/l

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 211

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity: Not classified based on available information.

Alkylamine trialkyldithiophosphate phosphate:

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Toxic to aquatic life.



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC **BLEND GEAR OIL** 

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Acute aquatic toxicity Category 2; Toxic to aquatic life.

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

Chronic aquatic toxicity Category 2; Toxic to aquatic life with

long lasting effects.

OLEYLAMINE:

LC50 (Pimephales promelas (fathead minnow)): 0.11 mg/l Toxicity to fish

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.011 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 0.083 mg/l

Exposure time: 72 h

Remarks: The toxicological data has been taken from

products of similar composition.

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.01

mg/l

Exposure time: 96 h

M-Factor (Acute aquatic

toxicity)

10

M-Factor (Chronic aquatic

toxicity)

10

**Ecotoxicology Assessment** 

Acute aquatic toxicity Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Chronic aquatic toxicity Chronic aquatic toxicity Category 1; Very toxic to aquatic life

with long lasting effects.

## 12.2 Persistence and degradability

#### Components:

Distillates (petroleum), solvent-dewaxed light paraffinic:

Biodegradability Result: Inherently biodegradable.

> Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301B



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

**OLEYLAMINE:** 

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 44 % Exposure time: 28 d

12.3 Bioaccumulative potential

**Components:** 

**OLEYLAMINE:** 

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): > 500

Partition coefficient: n-

octanol/water

log Pow: estimated > 4

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

**Product:** 

**Endocrine disrupting** 

potential

: The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

#### **SECTION 14: Transport information**

#### 14.1 UN number

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA P : Not regulated as a dangerous good

## 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

## 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

#### 14.4 Packing group

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA\_P (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC **BLEND GEAR OIL** 

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

# 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)

Conditions of restriction for the following entries should be

considered: Number on list 3 Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great

Britain)

Not applicable

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

Control of Major Accident Hazards Regulations 34

2015 (COMAH)

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams).(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar

properties as regards flammability and environmental hazards as the products referred to in points

(a) to (d)



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

## Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

## The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

TSCA : Product contains substance(s) not listed on TSCA inventory.

AIIC : On the inventory, or in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

SBZ 5350

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : Not in compliance with the inventory

#### 15.2 Chemical safety assessment

No data available

#### **Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.
H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.
H335 : May cause respiratory irritation.



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

H373 : May cause damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Skin Corr. : Skin corrosion
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency: EC-Number - European Community number: ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent. Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration. Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations



according to Regulation (EC) No. 1907/2006 NAPA® N3115L HD 75W80 SYNTHETIC BLEND GEAR OIL

Version: 8.0 Revision Date: 26.06.2023 Print Date: 16/10/2023

Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Internal information: 000000221051

Classification of the mixture:

Classification procedure:

Aquatic Chronic 3 H412 Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB/EN