

according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® N3211L AUTOTRANS MVA

SYNTHETIC GEAR OIL

Product code : 902562

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global

Operations

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

SDS@valvolineglobal.com

## 1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

## **Additional Labelling**

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

## Components

| Chemical name  | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number                | Classification                           | Concentration<br>(% w/w) |
|--|--|--|--------------------------|
| LUBRICATING OILS, PETROLEUM,<br>C20-50, HYDROTREATED | 72623-87-1<br>276-738-4<br>649-483-00-5<br>01-2119474889-13-<br>xxxx | Asp. Tox. 1; H304                        | >= 80 - < 90             |
| METHACRYLATE COPOLYMER                               | Not Assigned   | Eye Irrit. 2; H319<br>Eye Irrit. 2; H319 | >= 2.5 - < 5             |

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

# **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

High volume water jet

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

carbon dioxide and carbon monoxide

#### 5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : For personal protection see section 8.

Refer to protective measures listed in sections 7 and 8.

Use personal protective equipment.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

## 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety

standards.



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

Advice on common storage : No materials to be especially mentioned.

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

## 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Safety glasses

Hand protection

Material : neoprene, nitrile rubber

Break through time : >= 240 minGlove thickness : >= 0.35 mm

Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the

protective glove.

Skin and body protection : Protective suit

Respiratory protection : No personal respiratory protective equipment normally

required.



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : red

Odour : No data available

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 192 °C

Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.843 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n- : No data available



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

octanol/water

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 27.6 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

No decomposition if stored and applied as directed.

## 10.2 Chemical stability

No decomposition if stored and applied as directed.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

## 10.6 Hazardous decomposition products

No hazardous decomposition products are known.



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

#### **Acute toxicity**

Not classified based on available information.

## **Components:**

#### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: No mortality observed at this dose.

## Skin corrosion/irritation

Not classified based on available information.

#### Components:

# **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Species : Rabbit

Result : No skin irritation

# **METHACRYLATE COPOLYMER:**

Result : Slight, transient irritation

# Serious eye damage/eye irritation

Not classified based on available information.

## **Components:**

# LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species : Rabbit

Result : No eye irritation

#### METHACRYLATE COPOLYMER:



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

Result : Irritating to eyes.

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

# Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### **Components:**

## **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

## Reproductive toxicity

Not classified based on available information.

## STOT - single exposure

Not classified based on available information.

## STOT - repeated exposure

Not classified based on available information.

## **Aspiration toxicity**

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

## **Components:**

## **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

May be fatal if swallowed and enters airways.

#### **Further information**

**Product:** 

Remarks : No data available

# **SECTION 12: Ecological information**

# 12.1 Toxicity

# **Components:**

# LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

: NOELR: >= 1,000 mg/l

Exposure time: 14 d

Species: Oncorhynchus mykiss (rainbow trout)



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEL: 10 mg/l Exposure time: 21 d

Species: Daphnia (water flea)

Test substance: WAF

Method: OECD Test Guideline 211

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

METHACRYLATE COPOLYMER:

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

12.2 Persistence and degradability

**Components:** 

 ${\bf LUBRICATING\ OILS,\ PETROLEUM,\ C20-50,\ HYDROTREATED:}$ 

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

#### 12.6 Other adverse effects

**Product:** 

Endocrine disrupting

potential

: The substance/mixture does not contain components considered to have endocrine disrupting properties according

to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

# **SECTION 14: Transport information**

### 14.1 UN number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA\_P (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

## 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## **SECTION 15: Regulatory information**

# **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high : Not applicable

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

: Not applicable

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

UK REACH List of substances subject to authorisation : Not applicable

(Annex XIV)

Control of Major Accident Hazards Regulations Not applicable

2015 (COMAH)

## Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

# The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

#### 15.2 Chemical safety assessment

No data available

#### **Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

#### **SECTION 16: Other information**

**Full text of H-Statements** 

H304 : May be fatal if swallowed and enters airways.

H319 : Causes serious eye irritation.

Full text of other abbreviations

Asp. Tox. : Aspiration hazard Eye Irrit. : Eye irritation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**



according to Regulation (EC) No. 1907/2006 NAPA® N3211L AUTOTRANS MVA SYNTHETIC GEAR OIL

Version: 5.0 Revision Date: 14.07.2023 Print Date: 16/10/2023

Internal information: 000000278044

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN