

according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	:	NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL
Product code	:	902567
1.2 Relevant identified uses of th	e s	ubstance or mixture and uses advised against
Use of the substance/mixture	:	Engine, gear & lubricating oil.
1.3 Details of the supplier of the	saf	ety data sheet
Company	:	Ellis Enterprises B.V., an affiliate of Valvoline Global Operations Wieldrechtseweg 39 3316 BG Dordrecht Netherlands
Telephone	:	+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
E-mail address of person responsible for the SDS	:	SDS@valvolineglobal.com

1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 80 - < 90
METHACRYLATE COPOLYMER	Not Assigned	Eye Irrit. 2; H319 Eye Irrit. 2; H319	>= 2.5 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Do not leave the victim unattended.
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0	Re	vision Date: 14.07.2023	Print Date: 16/10/2023	
In case of eye contact	:	Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specia	list.	
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unco If symptoms persist, call a physician.	onscious person.	
4.2 Most important symptoms a	nd e	ffects, both acute and delayed		
Symptoms	:	No symptoms known or expected.		
4.3 Indication of any immediate	mec	lical attention and special treatment ne	eded	
Treatment	:	No hazards which require special first air		
		Treat symptomatically.		
SECTION 5: Firefighting measures				
5.1 Extinguishing media				
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, carbon dioxide.	dry chemical or	
Unsuitable extinguishing media	:	High volume water jet		
5.2 Special hazards arising from	n the	substance or mixture		
Specific hazards during firefighting	:		enter drains or water	
Hazardous combustion products	:	carbon dioxide and carbon monoxide		
5.3 Advice for firefighters				
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus necessary.	s for firefighting if	
Further information	:	Collect contaminated fire extinguishing v must not be discharged into drains. Fire residues and contaminated fire extir		

3/16



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	For personal protection see section 8. Refer to protective measures listed in sections 7 and 8. Use personal protective equipment.		
6.2 Environmental precautions			

Environmental precautions	:	Prevent product from entering drains.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in application area.	
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	General industrial hygiene practice.	

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage	:	Containers which are opened must be carefully resealed and
areas and containers		kept upright to prevent leakage. Electrical installations /
		working materials must comply with the technological safety
		standards.



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0	Revision Date: 14.07.2023	Print Date: 16/10/2023
Advice on common storage	: No materials to be especially mentioned	
Further information on storage stability	: No decomposition if stored and applied a	as directed.
7.3 Specific end use(s) Specific use(s)	: No data available	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipm Eye/face protection		Safety glasses
Hand protection Material Break through time Glove thickness Directive	-	neoprene, nitrile rubber >= 240 min >= 0.35 mm Equipment should conform to EN 374
Remarks	:	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
Skin and body protection	:	Protective suit
Respiratory protection	:	No personal respiratory protective equipment normally required.



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	red
Odour	:	No data available
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	192 °C Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.843 g/cm3 (15.6 °C)
Solubility(ies) Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-	:	No data available
		6 / 16



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0	Revision Date: 14.07.2023	Print Date: 16/10/2023
octanol/water		
Decomposition temperature	: No data available	
Viscosity Viscosity, dynamic	: No data available	
Viscosity, kinematic	: 27.6 mm2/s (40 °C)	
Oxidizing properties	: No data available	
9.2 Other information Self-ignition	: No data available	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions. No hazards to be specially mentioned.
10.4 Conditions to avoid Conditions to avoid	:	excessive heat
10.5 Incompatible materials Materials to avoid	:	Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	 LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: No mortality observed at this dose.
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species	:	Rabbit
Result	:	No skin irritation

METHACRYLATE COPOLYMER:

Result : Slig	ght, transient irritation
---------------	---------------------------

Serious eye damage/eye irritation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species	:	Rabbit
Result	:	No eye irritation

METHACRYLATE COPOLYMER:



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

Result

: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity -	:	Classified based on DMSO extract content < 3% (Regulation
Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks

: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	:	NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout)



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0	Re	evision Date: 14.07.2023	Print Date: 16/10/2023
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211	
Ecotoxicology Assessment	:		
Acute aquatic toxicity	:	Not classified based on available information	ation.
Chronic aquatic toxicity	:	Not classified based on available information	ation.
METHACRYLATE COPOLY	MEF	R:	
Ecotoxicology Assessment	:		
Acute aquatic toxicity	:	Not classified based on available information	ation.
Chronic aquatic toxicity	:	Not classified based on available information	ation.
12.2 Persistence and degradabi	lity		
Components:			
LUBRICATING OILS, PETR	OLE	UM, C20-50, HYDROTREATED:	
Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B	
12.3 Bioaccumulative potential			
No data available			
12.4 Mobility in soil			
No data available			
12.5 Results of PBT and vPvB a	sse	ssment	
Product:			
Assessment	:	This substance/mixture contains no com to be either persistent, bioaccumulative very persistent and very bioaccumulative 0.1% or higher.	and toxic (PBT), or



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

12.6 Other adverse effects	
Product:	
Endocrine disrupting : potential	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Additional ecological : information	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

The product should not be allowed to enter drains, water courses or the soil.

SECTION 14: Transport information

14.1 UN number

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.3 Transport bazard class(os)		

:

14.3 Transport hazard class(es)



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0	Revision Date: 14.07.2023	Print Date: 16/10/2023
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
IATA_P	: Not regulated as a dangerous good	
14.4 Packing group		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
IATA (Cargo)	: Not regulated as a dangerous good	
IATA_P (Passenger)	: Not regulated as a dangerous good	
14.5 Environmental hazarda		

- - - - - -

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Not applicable
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

UK REACH List of substances subject to authorisation : Not applicable (Annex XIV)

Control of Major Accident Hazards Regulations Not applicable 2015 (COMAH)

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI	:	Not in compliance with the inventory
TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	Not in compliance with the inventory
DSL	:	All components of this product are on the Canadian DSL
ENCS	:	Not in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)



according to Regulation (EC) No. 1907/2006 NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

SECTION 16: Other information

Full text of H-Statements

H304	:	May be fatal if swallowed and enters airways.
H319	:	Causes serious eye irritation.

Full text of other abbreviations

Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very **Bioaccumulative**

Further information



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

NAPA® N3245L AUTOTRANS NGT SYNTHETIC GEAR OIL

Version: 5.0

Revision Date: 14.07.2023

Print Date: 16/10/2023

Internal information : 000000278044

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN