

NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	:	NAPA® N33660L 80W90 LS Gear Oil
Product code	:	903361
1.2 Relevant identified uses of t Use of the substance/mixture		substance or mixture and uses advised against Lubricating oils
1.3 Details of the supplier of the	saf	ety data sheet
Company	:	Ellis Enterprises B.V., an affiliate of Valvoline Global Operations Wieldrechtseweg 39 3316 BG Dordrecht Netherlands
Telephone	:	+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
E-mail address of person responsible for the SDS	:	SDS@valvolineglobal.com

1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl, Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

CAS-No.	Classification	Concentration
		(% w/w)
Index-No.		
Registration number		
72623-87-1	Asp. Tox. 1; H304	>= 5 - < 10
276-738-4		
649-483-00-5		
01-2119474889-13-		
xxxx		
64742-54-7	Asp. Tox. 1; H304	>= 1 - < 2.5
265-157-1	•	
649-467-00-8		
01-2119484627-25-		
XXXX		
Not Assigned	Aquatic Chronic 3:	>= 1 - < 2.5
	H412	
01-2119978530-33-		
	EC-No. Index-No. Registration number 72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx 64742-54-7 265-157-1 649-467-00-8 01-2119484627-25-	EC-No. Index-No. Registration number Asp. Tox. 1; H304 72623-87-1 Asp. Tox. 1; H304 276-738-4 649-483-00-5 649-483-00-5 01-2119474889-13- 01-2119474889-13- xxxx 64742-54-7 Asp. Tox. 1; H304 265-157-1 649-467-00-8 01-2119484627-25- xxxx Not Assigned Aquatic Chronic 3; H412 01-2119978530-33- Aquatic Chronic 3; H412



Version: 9.0

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Print Date: 16/10/2023

	11 Bate: 12:01:2020	1 11112	
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27- xxxx	Asp. Tox. 1; H304	>= 1 - < 2.5
Distillates (petroleum), solvent- dewaxed light paraffinic	64742-56-9 265-159-2 649-469-00-9	Asp. Tox. 1; H304	>= 1 - < 2.5
Reaction products of 4-methyl-2- pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl	Not Assigned 931-384-6 01-2119493620-38- xxxx	Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 2; H411 2 > 50 - 100 % 	>= 1 - < 2.5
Reaction product of 1,3,4- thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.	1471311-26-8 01-2119971727-23- xxxx	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 0.1 - < 0.25

Revision Date: 12.07.2023

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Do not leave the victim unattended.
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
		0/04



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0	Revision Date: 12.07.2023	Print Date: 16/10/2023			
If swallowed	: Keep respiratory tract clear. Do not give milk or alcoholic beverag Never give anything by mouth to an u If symptoms persist, call a physician.				
4.2 Most important symptoms and effects, both acute and delayed					
Symptoms	: No symptoms known or expected.				
4.3 Indication of any immediate medical attention and special treatment needed					
Treatment	: No hazards which require special firs	t aid measures.			
	Treat symptomatically.				

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	:	High volume water jet
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	carbon dioxide and carbon monoxide
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures					
Personal precautions :	Refer to protective measures listed in sections 7 and 8. Use personal protective equipment.				
6.2 Environmental precautions					
Environmental precautions :	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.				
6.3 Methods and material for containment and cleaning up					
Methods for cleaning up :	Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.				

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Advice on safe handling For personal protection see section 8. : Smoking, eating and drinking should be prohibited in the application area. Advice on protection against Normal measures for preventive fire protection. : fire and explosion General industrial hygiene practice. Hygiene measures : 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage : Containers which are opened must be carefully resealed and areas and containers kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards. No materials to be especially mentioned. Advice on common storage 2 Further information on No decomposition if stored and applied as directed. 1 storage stability



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

7.3 Specific end use(s)

Specific use(s)

: No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment	nt	
Eye/face protection	:	Safety glasses
Break through time	:	neoprene, nitrile rubber >= 240 min >= 0.35 mm Equipment should conform to EN 374
Remarks	:	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
Skin and body protection	:	Protective suit
Respiratory protection	:	No personal respiratory protective equipment normally required.



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	oily
Odour Threshold	:	No data available
рН	:	Not applicable
Pour point	:	< -24 °C
Boiling point/boiling range	:	No data available
Flash point	:	214 °C Method: Cleveland open cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	ca. 0.889 g/cm3 (15 °C)
Solubility(ies) Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0	Revision Date: 12.07.2023	Print Date: 16/10/2023
Decomposition temperature	: No data available	
Viscosity Viscosity, dynamic	: No data available	
Viscosity, kinematic	: ca. 125 mm2/s (40 °C)	
Oxidizing properties	: No data available	
9.2 Other information Self-ignition	: No data available	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions. No hazards to be specially mentioned.		
10.4 Conditions to avoid Conditions to avoid	:	None known.		
10.5 Incompatible materials Materials to avoid	:	Strong oxidizing agents		
10.6 Hazardous decomposition products				

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0	on: 9.0 Revision Date: 12.07.2023		
Product: Acute oral toxicity	: Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method		
Components:			
LUBRICATING OILS, PETR	OLEUM, C20-50, HYDROTREATED:		
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg		
Acute inhalation toxicity	: LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture l inhalation toxicity Remarks: No mortality observed at this o		
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg		

Remarks: No mortality observed at this dose.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity	:	LD50 (Rat): > 15 g/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg

Distillates (petroleum), solvent-dewaxed light paraffinic:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl:

Acute oral toxicity : LD50 (Rat): ca. 2,000 mg/kg

9/24



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0 Revision Date: 12.07.2023 Print Date: 16/10/2023 Method: OECD Test Guideline 401 Assessment: The component/mixture is moderately toxic after single ingestion. Skin corrosion/irritation Not classified based on available information. **Components:** LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED: Species Rabbit : Result No skin irritation **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:** Assessment : Slight, transient irritation Result Slight, transient irritation Reaction Products of alcohols, C14-18, C18 unsat., esterified with phosphorus pentoxide and salted with amines, C12-14,-tert-alkyl: Result No skin irritation DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC: Assessment : Slight, transient irritation Result Slight, transient irritation ٠ Distillates (petroleum), solvent-dewaxed light paraffinic: Species Rabbit Result Slight, transient irritation 1 Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.: Result : Irritating to skin. Serious eye damage/eye irritation Not classified based on available information. Product: Result No eye irritation **Components:** LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

alonal		
rsion: 9.0	Revision Date: 12.07.2023	Print Date: 16/10/2023
Species	: Rabbit	
Result	: No eye irritation	
rtoodit		
DISTILLATES (PETROLE	EUM), HYDROTREATED HEAVY PARA	FFINIC:
Assessment	: No eye irritation	
Result	: No eye irritation	
Reaction Products of alc salted with amines, C12-	cohols, C14-18, C18 unsat., esterified v -14,-tert-alkyl:	vith phosphorus pentoxide and
Result	: No eye irritation	
DISTILLATES (PETROLE	EUM), SOLVENT-DEWAXED HEAVY PA	
Assessment	Slight, transient irritation	
Result	Slight, transient irritation	
Species	solvent-dewaxed light paraffinic: : Rabbit : Slight transient irritation	
Species Result Reaction products of 4-me	Rabbit Slight, transient irritation	
Species Result Reaction products of 4-me with diphosphorus pentaox	Rabbit Slight, transient irritation Slight and diphosphorus pentas xide, and salted by amines, C12-14-tert-a	
Species Result Reaction products of 4-me	Rabbit Slight, transient irritation	
Species Result Reaction products of 4-me with diphosphorus pentaox Result	Rabbit Slight, transient irritation Slight and diphosphorus pentas xide, and salted by amines, C12-14-tert-a	alkyl:
Species Result Reaction products of 4-me with diphosphorus pentaox Result	 Rabbit Slight, transient irritation ethyl-2-pentanol and diphosphorus pentas xide, and salted by amines, C12-14-tert-a Eye irritation 	alkyl: ehyde and phenol, heptyl deriv
Species Result Reaction products of 4-me with diphosphorus pentaox Result Reaction product of 1,3,4	 Rabbit Slight, transient irritation ethyl-2-pentanol and diphosphorus pentas xide, and salted by amines, C12-14-tert-a Eye irritation 4-thiadiazolidine-2,5-dithione, formaldor is Risk of serious damage to eyes. 	alkyl: ehyde and phenol, heptyl deriv
Species Result Reaction products of 4-me with diphosphorus pentaox Result Reaction product of 1,3,4 Result	 Rabbit Slight, transient irritation ethyl-2-pentanol and diphosphorus pentas xide, and salted by amines, C12-14-tert-a Eye irritation 4-thiadiazolidine-2,5-dithione, formald Risk of serious damage to eyes. 	alkyl: ehyde and phenol, heptyl deriv
Species Result Reaction products of 4-me with diphosphorus pentaox Result Reaction product of 1,3,4 Result Respiratory or skin sens Skin sensitisation Not classified based on av	 Rabbit Slight, transient irritation ethyl-2-pentanol and diphosphorus pentas xide, and salted by amines, C12-14-tert-a Eye irritation 4-thiadiazolidine-2,5-dithione, formaldor is Risk of serious damage to eyes. sitisation vailable information. 	alkyl: ehyde and phenol, heptyl deriv
Species Result Reaction products of 4-me with diphosphorus pentaox Result Reaction product of 1,3,4 Result Respiratory or skin sens Skin sensitisation	 Rabbit Slight, transient irritation ethyl-2-pentanol and diphosphorus pentas xide, and salted by amines, C12-14-tert-a Eye irritation 4-thiadiazolidine-2,5-dithione, formalde Risk of serious damage to eyes. 	alkyl: ehyde and phenol, heptyl deriv
Species Result Reaction products of 4-me with diphosphorus pentaon Result Reaction product of 1,3,4 Result Respiratory or skin sens Skin sensitisation Not classified based on av Respiratory sensitisation	 Rabbit Slight, transient irritation ethyl-2-pentanol and diphosphorus pentas xide, and salted by amines, C12-14-tert-a Eye irritation 4-thiadiazolidine-2,5-dithione, formalde Risk of serious damage to eyes. 	alkyl: ehyde and phenol, heptyl deriv



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type	: Buehler Test
Species	: Guinea pig
Assessment	Does not cause skin sensitisation.

Distillates (petroleum), solvent-dewaxed light paraffinic:

Test Type Species	: Buehler Test
Species	: Guinea pig
Assessment	Does not cause skin sensitisation.
Ássessment Method	: OECD Test Guideline 406

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl:

Assessment : The product is a skin sensitiser, sub-category 1B.

Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.:

Assessment : The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity -	: Classified based on DMSO extract content < 3% (Regulation
Carcinogenicity - Assessment	(EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

	:	Classified based on DMSO extract content < 3% (Regulation
Assessment		(EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

Distillates (petroleum), solvent-dewaxed light paraffinic:

Carcinogenicity -
Assessment: Classified based on DMSO extract content < 3% (Regulation
(EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Distillates (petroleum), solvent-dewaxed light paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Further information

Product:

Remarks

: No data available



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

SECTION 12: Ecological information

12.1 Toxicity

12.	TOXICITY		
	Product:		
	Ecotoxicology Assessment Acute aquatic toxicity	:	
			Toxic to aquatic life.
	Chronic aquatic toxicity	:	This product has no known ecotoxicological effects.
			Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	:	NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates	:	NOEL: 10 mg/l Exposure time: 21 d



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0	Revision Date: 12.07.2023	Print Date: 16/10/2023
(Chronic toxicity)	Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211	
Ecotoxicology Assessme	nt	
Acute aquatic toxicity Chronic aquatic toxicity	Not classified based on available inNot classified based on available in	
Chronic aquatic toxicity	: Not classified based on available in	formation.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

•	·	
Toxicity to fish	:	LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	:	NOEC: 10 mg/l Species: Fish
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 10 mg/l Species: Aquatic invertebrates

Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Acute aquatic toxicity Chronic aquatic toxicity	: Not classified based on available information.

Reaction Products of alcohols, C14-18, C18 unsat., esterified with phosphorus pentoxide and salted with amines, C12-14,-tert-alkyl:

Ecotoxicology Assessment

Acute aquatic toxicity	:	Harmful to aquatic life.
		Acute aquatic toxicity Category 3; Harmful to aquatic life.
Chronic aquatic toxicity	:	Harmful to aquatic life with long lasting effects.
		Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

Distillates (petroleum), solvent-dewaxed light paraffinic:

Distillates (petrolealit), solver		
Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl:

:	LL50 (Oncorhynchus mykiss (rainbow trout)): ca. 24 mg/l
	Exposure time: 96 h



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0	Revision Date: 12.07.2023	Print Date: 16/10/2023
	Test Type: static test Test substance: WAF Method: OECD Test Guideline 203	
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): ca Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202	. 91.4 mg/l
Toxicity to algae/aquatic plants	 ErC50 (Pseudokirchneriella subcapitata mg/l End point: Growth inhibition Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 201 NOEC (Pseudokirchneriella subcapitata mg/l End point: Growth inhibition Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 201 	
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)		

Ecotoxicology Assessment

Acute aquatic toxicity	:	Toxic to aquatic life.
Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.

Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.:

Ecotoxicology Assessment

Acute aquatic toxicity

:

		Not classified based on available information.
Chronic aquatic toxicity	:	Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability	 Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B 	

Reaction Products of alcohols, C14-18, C18 unsat., esterified with phosphorus pentoxide and salted with amines, C12-14,-tert-alkyl:

Biodegradability	:	Biodegradation: 0 % Exposure time: 28 d Method: Modified Sturm Test

Distillates (petroleum), solvent-dewaxed light paraffinic:

Biod Expo	ult: Inherently biodegradable. legradation: 31 % osure time: 28 d nod: OECD Test Guideline 301B
--------------	--

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl:

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 7.4 % Exposure time: 28 d Method: Modified Sturm Test
------------------	---	---

12.3 Bioaccumulative potential

Components:

ш

Reaction Products of alcohols, C14-18, C18 unsat., esterified with phosphorus pentoxide and salted with amines, C12-14,-tert-alkyl:

Partition coefficient: n- : log Pow: 8 octanol/water



NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl:

Partition coefficient: n- : Remarks: No data available octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:			
Assessment		This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.	
12.6 Other adverse effects			
Product:			
Endocrine disrupting potential		This substance/mixture contains components considered to have endocrine disrupting properties for environment, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.	
Additional ecological information		An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.	

Components:

Reaction product of 1,3,4-thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.:

Endocrine disrupting	The substance is considered to have endocrine disrupting
potential	properties according to REACH Article 57(f) for the
	environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

: The product should not be allowed to enter drains, water courses or the soil.



NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

SECTION 14: Transport information

14.1 UN number

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA_P (Passenger)	:	Not regulated as a dangerous good
14.5 Environmental hazards		

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable for product as supplied.



NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Not applicable
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Reaction product of 1,3,4- thiadiazolidine-2,5-dithione, formaldehyde and phenol, heptyl derivs.
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	Not	applicable

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI	:	Not in compliance with the inventory
TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	Not in compliance with the inventory



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0	Revision Date: 12.07.2023	Print Date: 16/10/2023
DSL	: All components of this product are on	the Canadian DSL
ENCS	: Not in compliance with the inventory	
KECI	: On the inventory, or in compliance wi	th the inventory
PICCS	: On the inventory, or in compliance wi	th the inventory
IECSC	: On the inventory, or in compliance wi	th the inventory
NZIoC	: On the inventory, or in compliance wi	th the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H226 H302 H304 H315 H317 H318 H319 H411 H412 Full text of other abbreviation	: : : : : : : : : : : : : : : : : : :	Flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
Acute Tox. Aquatic Chronic Asp. Tox. Eye Dam. Eye Irrit. Flam. Liq. Skin Irrit. Skin Sens.		Acute toxicity Long-term (chronic) aquatic hazard Aspiration hazard Serious eye damage Eye irritation Flammable liquids Skin irritation Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road;



Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response: ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very **Bioaccumulative**

Further information

Internal information : R0517046

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 NAPA® N33660L 80W90 LS Gear Oil

Version: 9.0

Revision Date: 12.07.2023

Print Date: 16/10/2023