



TECHNICAL DATA SHEET

HD 85W-140

| | |
|--------------|--------------------------|
| Product Type | 85W-140 MINERAL GEAR OIL |
| Product Code | NT308 |

Description

Suitable for manual gearboxes, including synchromesh, fitted to automotive vehicles, industrial and commercial vehicles.

Benefits

- Excellent oxidation stability
- Outstanding low and high temperature performance
- Suitable for synchromesh gearboxes
- Long service life
- Good protection against rust and corrosion
- High level of wear protection

Specifications

Always check the owner's manual for the correct oil specification to use.

- API GL-5
- MIL-L-2105D



TECHNICAL DATA SHEET

HD 85W-140

Product Type 85W-140 MINERAL GEAR OIL
Product Code NT308

Typical Properties

| SAE Viscosity Grade | SAE J306 | - | 85W-140 |
|---------------------|-------------|--------------------|---------|
| Viscosity @ 100°C | ASTM D-445 | mm ² /s | 26,6 |
| Viscosity @ 40°C | ASTM D-445 | mm ² /s | 352,0 |
| Viscosity Index | ASTM D-2270 | - | 100 |
| Viscosity @ -12°C | ASTM D-5293 | mPa.s | <150000 |
| Pour Point | ASTM D-5950 | °C | -24 |
| Specific gravity | ASTM D-4052 | - | 0,900 |
| Flash point | ASTM D-92 | °C | >220 |

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Esplanade Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu