

according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

<b>1.1 Product identifier</b> Trade name	:	NAPA® N22360L C3 5W30 LS Synthetic Motor Oil
Product code	:	903378
1.2 Relevant identified uses of the	e s	ubstance or mixture and uses advised against
Use of the substance/mixture	:	Engine, gear & lubricating oil.
1.3 Details of the supplier of the s	safe	ety data sheet
Company	:	Ellis Enterprises B.V., an affiliate of Valvoline Global Operations Wieldrechtseweg 39 3316 BG Dordrecht Netherlands
Telephone	:	+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
E-mail address of person responsible for the SDS	:	SDS@valvolineglobal.com

#### 1.4 Emergency telephone number

 $00\mathchar`800\mathchar`825\mathchar`8654\/\ 001\mathchar`859\mathchar`202\mathchar`3865, or contact your local emergency telephone number at 112$ 

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### **Additional Labelling**

EUH210 Safety data sheet available on request.

EUH208 Contains Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt, Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
AMINES, POLYETHYLENEPOLY-, REACTION PRODUCTS WITH 1,3- DIOXOLAN-2-ONE AND SUCCINIC ANHYDRIDE MONOPOLYISOBUTENYL DERIVS.	147880-09-9	Aquatic Chronic 4; H413	>= 5 - < 10
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 1 - < 2.5
Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs.,	722503-69-7	Skin Sens. 1; H317 Aquatic Chronic 4;	>= 0.5 - < 1



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Aquatic Chronic 4;

H413

 
 Version: 7.1
 Revision Date: 21.06.2023
 Print Date: 16/10/2023

 calcium salt
 H413

 Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs.,
 722503-68-6
 Skin Sens. 1B; H317
 >= 0.5 - < 1</td>

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

calcium salts

4.1 Description of first aid measures		
General advice	: Do not leave the victim unattended.	
If inhaled	<ul> <li>If unconscious, place in recovery position and seek medical advice.</li> <li>If symptoms persist, call a physician.</li> </ul>	
In case of eye contact	<ul> <li>Remove contact lenses.</li> <li>Protect unharmed eye.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>	
If swallowed	<ul> <li>Keep respiratory tract clear.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> <li>If symptoms persist, call a physician.</li> </ul>	
4.2 Most important symptoms a	and effects, both acute and delayed	
Symptoms	: No symptoms known or expected.	
4.3 Indication of any immediate medical attention and special treatment needed		
Treatment	: No hazards which require special first aid measures.	
	Treat symptomatically.	

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1	Revision Date: 21.06.2023	Print Date: 16/10/2023
Unsuitable extinguishing media	: High volume water jet	
5.2 Special hazards arising fror	n the substance or mixture	
Hazardous combustion products	: carbon dioxide and carbon monoxide Nitrogen oxides (NOx)	
5.3 Advice for firefighters		
Special protective equipmen for firefighters	t : Wear self-contained breathing apparat necessary.	us for firefighting if
Further information	: Standard procedure for chemical fires. Use extinguishing measures that are a circumstances and the surrounding en-	

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures			
Personal precautions	:	Refer to protective measures listed in sections 7 and 8. Use personal protective equipment.	
6.2 Environmental precautions			
Environmental precautions	:	If the product contaminates rivers and lakes or drains inform respective authorities.	
6.3 Methods and material for con	taiı	nment and cleaning up	
Methods for cleaning up	:	Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.	
6.4 Reference to other sections			
See sections: 7, 8, 11, 12 and 13.			

### **SECTION 7: Handling and storage**

:

### 7.1 Precautions for safe handling

- Advice on safe handling
- For personal protection see section 8. Smoking, eating and drinking should be prohibited in the



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Revision Date: 21.06.2023	Print Date: 16/10/2023
application area.	
: Normal measures for preventive fire protection	ction.
: General industrial hygiene practice.	
including any incompatibilities	
: Electrical installations / working materials the technological safety standards.	must comply with
: No materials to be especially mentioned.	
: No decomposition if stored and applied as	directed.
: No data available	
	<ul> <li>application area.</li> <li>Normal measures for preventive fire protection</li> <li>General industrial hygiene practice.</li> <li>including any incompatibilities</li> <li>Electrical installations / working materials in the technological safety standards.</li> <li>No materials to be especially mentioned.</li> <li>No decomposition if stored and applied as</li> </ul>

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection	:	Safety glasses
Hand protection Material Break through time Glove thickness Directive	:	neoprene, nitrile rubber >= 240 min >= 0.35 mm Equipment should conform to EN 374
Remarks	:	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used,



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1	Revision Date: 21.06.2023	Print Date: 16/10/2023
	such as the danger of cuts, abrasion, ar The data about break through time/stren standard values! The exact break throug material has to be obtained from the pro protective glove.	ngth of material are gh time/strength of
Skin and body protection	: Protective suit	
Respiratory protection	: No personal respiratory protective equip required.	ment normally

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	oily
Odour Threshold	:	No data available
рН	:	Not applicable
Pour point	:	< -39 °C
Boiling point/boiling range	:	No data available
Flash point	:	205 °C Method: Cleveland open cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
		6/10



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1	Revision Date: 21.06.2023	Print Date: 16/10/2023	
Relative density	: No data available		
Density	: ca. 0.854 g/cm3 (15.6 °C)		
Bulk density	: Not applicable		
Solubility(ies) Water solubility	: insoluble		
Solubility in other solvents	: No data available		
Partition coefficient: n- octanol/water	: No data available		
Decomposition temperature	: No data available		
Viscosity Viscosity, dynamic	: No data available		
Viscosity, kinematic	: ca. 72 mm2/s (40 °C)		
Oxidizing properties	: No data available		
9.2 Other information			
Self-ignition	: No data available		

### **SECTION 10: Stability and reactivity**

#### **10.1 Reactivity**

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions	Stable under recommended storage conditions. No hazards to be specially mentioned.
10.4 Conditions to avoid	

- Conditions to avoid : None known.
- 10.5 Incompatible materials



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1	Revision Date: 21.06.2023	Print Date: 16/10/2023		
Materials to avoid	: Strong oxidizing agents			
10.6 Hazardous decomposition products				

No hazardous decomposition products are known.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.

Product:	
Acute oral toxicity	: Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method
Components:	
Reaction products of Ber	nzeneamine, N-phenyl- with nonene (branched)
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: No mortality observed at this do

### Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: The toxicological data has been taken from products of similar composition.

### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	<ul> <li>LC50 (Rat): &gt; 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute</li> </ul>



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Revision Date: 21.06.2023	Print Date: 16/10/2023
inhalation toxicity Remarks: No mortality observe	d at this dose.
: LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observe	d at this dose.
ailable information.	
zeneamine, N-phenyl- with nonene	(branched):
<ul> <li>Rabbit</li> <li>Mild skin irritation</li> <li>The toxicological data has been composition.</li> </ul>	n taken from products of similar
ROLEUM, C20-50, HYDROTREATED	:
: Rabbit : No skin irritation	
irritation	
nzeneamine, N-phenyl- with nonene	(branched):
<ul> <li>Rabbit</li> <li>Slight, transient irritation</li> <li>The toxicological data has been composition.</li> </ul>	n taken from products of similar
ROLEUM, C20-50, HYDROTREATED	:
: Rabbit	
	Remarks: No mortality observe ailable information. <b>nzeneamine, N-phenyl- with nonene</b> : Rabbit : Mild skin irritation : The toxicological data has been composition. <b>TROLEUM, C20-50, HYDROTREATED</b> : Rabbit : No skin irritation <b>irritation</b> ailable information. <b>nzeneamine, N-phenyl- with nonene</b> : Rabbit : Slight, transient irritation : The toxicological data has been composition.

### Skin sensitisation

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1 Revision Date: 21.06.2023 Print Date: 16/10/2023 **Respiratory sensitisation** Not classified based on available information. **Product:** Assessment : Does not cause skin sensitisation. Components: Reaction products of Benzeneamine, N-phenyl- with nonene (branched): **Species** : Guinea pig Assessment Does not cause skin sensitisation. Method **OECD** Test Guideline 406 : Remarks The toxicological data has been taken from products of similar composition. LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED: Test Type : **Buehler Test** Species Guinea pig Assessment Does not cause skin sensitisation. Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt: Assessment May cause sensitisation by skin contact. Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts: Assessment : The product is a skin sensitiser, sub-category 1B.

#### Germ cell mutagenicity

Not classified based on available information.

**Components:** 

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro	: Test Type: Ames test
	Test system: Salmonella typhimurium
	Metabolic activation: with and without metabolic activation
	Result: negative

#### Carcinogenicity

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

#### **Components:**

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity -Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

#### Reproductive toxicity

Not classified based on available information.

**STOT - single exposure** Not classified based on available information.

**STOT - repeated exposure** Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

**Components:** 

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

#### Further information

Product: Remarks

: No data available

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product:		
Ecotoxicology Assessmen	nt	
Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

#### **Components:**

# AMINES, POLYETHYLENEPOLY-, REACTION PRODUCTS WITH 1,3-DIOXOLAN-2-ONE AND SUCCINIC ANHYDRIDE MONOPOLYISOBUTENYL DERIVS.:

Ecotoxicology Assessment Acute aquatic toxicity	:		
		Not classified based on available information.	
Chronic aquatic toxicity	:	May cause long lasting harmful effects to aquatic life.	
		Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.	
Reaction products of Benze	nea	amine, N-phenyl- with nonene (branched):	
Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h	
		Test Type: static test Remarks: The toxicological data has been taken from	
		products of similar composition.	
Toxicity to daphnia and other	:		
aquatic invertebrates		Exposure time: 48 h Test Type: static test	
		Test substance: WAF	
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition	
plante		Exposure time: 72 h Test Type: static test	
		rest rype. static test	
Ecotoxicology Assessment			
Acute aquatic toxicity	:	Not classified based on available information.	
Chronic aquatic toxicity	:	Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.	
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:			
Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF	
		Method: OECD Test Guideline 203	



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1	Re	evision Date: 21.06.2023	Print Date: 16/10/2023
		Remarks: No toxicity at the limit of solubi	lity
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 10 Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202	0,000 mg/l
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata ( 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201	green algae)): >=
Toxicity to fish (Chronic toxicity)	:	NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow	trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211	
Ecotoxicology Assessment			
Acute aquatic toxicity	:	Not classified based on available information	tion.
Chronic aquatic toxicity	:	Not classified based on available information	tion.
Benzenesulfonic acid methy	/I-,	mono C20-26 branched alkyl derivs., ca	alcium salt:
Ecotoxicology Assessment Acute aquatic toxicity	:		
		Not classified based on available informa	tion.
Chronic aquatic toxicity	:	May cause long lasting harmful effects to	aquatic life.
		Chronic aquatic toxicity Category 4; May harmful effects to aquatic life.	cause long lasting



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

#### Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Ecotoxicology Assessment Acute aquatic toxicity	:
	Not classified based on available information.
Chronic aquatic toxicity	: May cause long lasting harmful effects to aquatic life.
	Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.
12.2 Persistence and degradabili	ty
Components:	
Reaction products of Benzer	neamine, N-phenyl- with nonene (branched):
Biodegradability	: Result: Not readily biodegradable.
	Biodegradation: 0 % Exposure time: 28 d
	Method: OECD Test Guideline 301B
LUBRICATING OILS. PETRO	LEUM, C20-50, HYDROTREATED:
Biodegradability	: Result: Not readily biodegradable.
	Biodegradation: 2 - 4 %
	Exposure time: 28 d Method: OECD Test Guideline 301B
12.3 Bioaccumulative potential	
<u>Components:</u>	
•	neamine, N-phenyl- with nonene (branched):
Partition coefficient: n- octanol/water	: log Pow: > 7.5
12.4 Mobility in soil	
No data available	
12.5 Results of PBT and vPvB as	sessment
Product:	
Assessment	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of
	14 / 19



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

0.1% or higher.

#### 12.6 Other adverse effects

Product:		
Endocrine disrupting potential	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Additional ecological information	:	No data available

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal.
Waste Code	:	The Waste code should be assigned in discussion between the user and the waste disposal company. The following Waste Codes are only suggestions: 13 02 05, mineral-based non-chlorinated engine, gear and lubricating oils

### **SECTION 14: Transport information**

#### 14.1 UN number

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1	Revision Date: 21.06.2023	Print Date: 16/10/2023
IMDG	: Not regulated as a dangerous good	
IATA_P	: Not regulated as a dangerous good	
14.3 Transport hazard class(es)	)	
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
IATA_P	: Not regulated as a dangerous good	
14.4 Packing group		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
IATA (Cargo)	: Not regulated as a dangerous good	
IATA_P (Passenger)	: Not regulated as a dangerous good	
14.5 Environmental hazards		
Not regulated as a dangerou	is good	

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1	Revision Date: 21.06.2023	Print Date: 16/10/2023		
Regulation (EC) No 1005/200 deplete the ozone layer	9 on substances that : Not applicable			
UK REACH List of substance (Annex XIV)	s subject to authorisation : Not applicable			
Control of Major Accident Hazards Regulations Not applicable 2015 (COMAH)				
The components of this product are reported in the following inventories:				
TCSI	: Not in compliance with the inventory			
TSCA	: All substances listed as active on the TSC	A inventory		
AIIC	: Not in compliance with the inventory			
DSL	: All components of this product are on the	Canadian DSL		
ENCS	Not in compliance with the investory			
ENCS	: Not in compliance with the inventory			
KECI	: On the inventory, or in compliance with the	e inventory		
PICCS	: On the inventory, or in compliance with the	e inventory		
NZIoC	: On the inventory, or in compliance with the	e inventory		
IECSC	: Not in compliance with the inventory			

#### 15.2 Chemical safety assessment

#### No data available

#### Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

### **SECTION 16: Other information**

Full text of H-Statements	
H304	: May be fatal if swallowed and enters airways.
H317	: May cause an allergic skin reaction.
H413	: May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Aquatic Chronic Asp. Tox. Skin Sens. Long-term (chronic) aquatic hazardAspiration hazardSkin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States): UN - United Nations: UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very **Bioaccumulative** 

#### **Further information**

Internal information : R0517092

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not



according to Regulation (EC) No. 1907/2006 NAPA® N22360L C3 5W30 LS Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN