

according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	-	NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil
Product code	:	903405
1.2 Relevant identified uses of the	e su	bstance or mixture and uses advised against
Use of the substance/mixture	:	Engine, gear & lubricating oil.
1.3 Details of the supplier of the s	safe	ty data sheet
Company		Ellis Enterprises B.V., an affiliate of Valvoline Global Operations Wieldrechtseweg 39 3316 BG Dordrecht Netherlands
Telephone		+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
E-mail address of person responsible for the SDS	:	SDS@valvolineglobal.com

1.4 Emergency telephone number

 $00\mathchar`800\mathchar`825\mathchar`8654\/\ 001\mathchar`859\mathchar`202\mathchar`3865, or contact your local emergency telephone number at 112$

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol, Molybdenum polysulphide long chain alkyl dithiocarbamate complex. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 70 - < 80
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
C14-16-18 Alkyl phenol	Not Assigned 01-2119498288-19- xxxx	Skin Sens. 1B; H317 STOT RE 2; H373 (Liver)	>= 1 - < 2.5
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	Not Assigned 01-0000019337-66- xxxx	Skin Irrit. 2; H315 Skin Sens. 1B; H317 Aquatic Chronic 3;	>= 0.1 - < 0.25



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
	H412	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Description of mist and measure		-
General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	:	If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of eye contact	:	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Keep respiratory tract clear. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	No symptoms known or expected.
----------	---	--------------------------------

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or
		carbon dioxide.



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023	
Unsuitable extinguishing media	: High volume water jet		
5.2 Special hazards arising from the substance or mixture			
Hazardous combustion products	: carbon dioxide and carbon monoxide Nitrogen oxides (NOx)		
5.3 Advice for firefighters			
Special protective equipmen for firefighters	t : Wear self-contained breathing apparatu necessary.	s for firefighting if	
Further information	: Standard procedure for chemical fires. Use extinguishing measures that are ap circumstances and the surrounding envi		

SECTION 6: Accidental release measures

6.1 Personal precautions, protecti	ve equipment and emergency procedures
Personal precautions	 Refer to protective measures listed in sections 7 and 8. Use personal protective equipment.
6.2 Environmental precautions	
Environmental precautions	 Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for conta	ainment and cleaning up
Methods for cleaning up	 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
6.4 Reference to other sections	
See sections: 7, 8, 11, 12 and 13.	



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

SECTION 7: Handling and storage

7.1 Precautions for safe handling

:	Do not breathe vapours/dust. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.
:	Normal measures for preventive fire protection.
:	Wash hands before breaks and at the end of workday.
incl	luding any incompatibilities
	Keep container tightly closed in a dry and well-ventilated
·	place. Electrical installations / working materials must comply with the technological safety standards.
:	place. Electrical installations / working materials must comply
:	place. Electrical installations / working materials must comply with the technological safety standards.
	: : incl

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Molybdenum polysulphide long chain alkyl dithiocarbamate complex	Not Assigned	TWA	10 mg/m3	SUPLR EXP

8.2 Exposure controls

Personal protective equipment



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
Eye/face protection	: Eye wash bottle with pure water Tightly fitting safety goggles	
Hand protection Material Break through time Glove thickness Directive	 neoprene, nitrile rubber >= 240 min >= 0.35 mm Equipment should conform to EN 374 	L
Remarks	 The selected protective gloves have the specifications of Regulation (EU) 201 EN 374 derived from it. Gloves should replaced if there is any indication of debreakthrough. Please observe the inseptimeability and breakthrough time with the supplier of the gloves. Also take in specific local conditions under which such as the danger of cuts, abrasion, The data about break through time/st standard values! The exact break through the protective glove. The suitability for a specific workplace with the producers of the protective glove. 	6/425 and the standard d be discarded and egradation or chemical tructions regarding which are provided by not consideration the the product is used, and the contact time. rength of material are bugh time/strength of producer of the e should be discussed
Skin and body protection	: Impervious clothing Choose body protection according to concentration of the dangerous subst	
Respiratory protection	: No personal respiratory protective eq required.	uipment normally

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	No data available
Odour Threshold	:	No data available



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0	Rev	vision Date: 27.06.2023	Print Date: 16/10/2023
рН	:	Not applicable	
Pour point	:	< -39 °C	
Boiling point/boiling range	:	No data available	
Flash point	:	202 °C Method: Pensky-Martens closed cup	
Evaporation rate	:	No data available	
Flammability (solid, gas)	:	No data available	
Upper explosion limit / Upper flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Vapour pressure	:	No data available	
Relative vapour density	:	No data available	
Relative density	:	No data available	
Density	:	ca. 0.853 g/cm3 (15.6 °C)	
Solubility(ies) Water solubility	:	insoluble	
Solubility in other solvents	:	No data available	
Partition coefficient: n- octanol/water	:	No data available	
Decomposition temperature	:	No data available	
Viscosity Viscosity, dynamic	:	No data available	
Viscosity, kinematic	:	ca. 45.1 mm2/s (40 °C)	
Oxidizing properties	:	No data available	

9.2 Other information



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Giubai		
Version: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
Self-ignition	: No data available	
SECTION 10: Stability an	d reactivity	
10.1 Reactivity		
No decomposition if store	ed and applied as directed.	
10.2 Chemical stability		
No decomposition if store	ed and applied as directed.	
10.3 Possibility of hazardou	s reactions	
Hazardous reactions	: No decomposition if stored and	applied as directed.
10.4 Conditions to avoid		
Conditions to avoid	: None known.	
10.5 Incompatible materials		
Materials to avoid	: Strong bases Strong oxidizing agents	
10.6 Hazardous decomposit	ion products	
No hazardous decompos	ition products are known.	

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

	00 mg/kg	:	Acute oral toxicity
Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity	h dust/mist substance or mixture has no acute	 - /	Acute inhalation toxicity



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
Acute dermal toxicity	Remarks: No mortality observed at thi : LD50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at thi	
Reaction products of Bei	nzeneamine, N-phenyl- with nonene (branc	hed):
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: No mortality observed at thi	is dose.
Acute dermal toxicity	 LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixtur toxicity Remarks: The toxicological data has b products of similar composition. 	

C14-16-18 Alkyl phenol:

Acute oral toxicity	:	LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute oral toxicity
Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: No mortality observed at this dose.

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Acute oral toxicity	:	LD50 (Rat): > 2,000 mg/kg
Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

:

Species	:	Rabbit
Result	:	No skin irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched): Rabbit

Species

9/21



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

ersion: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
Result Remarks	 Mild skin irritation The toxicological data has been tak composition. 	en from products of similar
C14-16-18 Alkyl phenol:		
Method Result	: OECD Test Guideline 431 : No skin irritation	
Molybdenum polysulphide	long chain alkyl dithiocarbamate com	olex:
Species Result	: Rabbit : Irritating to skin.	
Not classified based on avail <u>Product:</u> Result Remarks	 able information. Slight, transient irritation Expected based on components. 	
<u>Components:</u> LUBRICATING OILS, PETR	OLEUM, C20-50, HYDROTREATED:	
Species Result	: Rabbit : No eye irritation	
Reaction products of Benz	eneamine, N-phenyl- with nonene (bra	nched):
Species Result Remarks	 Rabbit Slight, transient irritation The toxicological data has been tak composition. 	en from products of similar
C14-16-18 Alkyl phenol:		
Species Result	: Rabbit : Slight, transient irritation	
Molybdenum polysulphide	long chain alkyl dithiocarbamate com	olex:
Species Result	Rabbit Slight, transient irritation	



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Assessment

: Does not cause skin sensitisation.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type	:	Buehler Test
Species	:	Guinea pig
Test Type Species Assessment	:	Does not cause skin sensitisation.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species Assessment Method Remarks	 Guinea pig Does not cause skin sensitisation. OECD Test Guideline 406
Remarks	: The toxicological data has been taken from products of similar composition.

C14-16-18 Alkyl phenol:

Species : Assessment :	Local lymph node assay Mouse The product is a skin sensitiser, sub-category 1B. OECD Test Guideline 429
Method .	OECD Test Guideline 429

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Test Type Species Assessment	:	Maximisation Test
Species	:	Guinea pig
Assessment	:	The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

11/21



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
Genotoxicity in vitro	: Test Type: Ames test Test system: Salmonella typhimuri Metabolic activation: with and with Result: negative	
C14-16-18 Alkyl phenol:		
Genotoxicity in vitro	: Test Type: Ames test Test system: Salmonella typhimuri Metabolic activation: with and with Result: negative	
"		

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Genotoxicity in vitro	: Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Result: negative
-----------------------	--

Carcinogenicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity -:Classified based on DMSO extract content < 3% (Regulation
(EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol:

Target Organs	: Liver
Assessment	The substance or mixture is classified as specific target organ
	toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks

: No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment		
Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
	Test Type: static test Test substance: WAF Method: OECD Test Guideline 201	
Toxicity to fish (Chronic toxicity)	: NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow	/ trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211	

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Acute aquatic toxicity Chronic aquatic toxicity	:	Not classified based on available information.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

•		
Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

C14-16-18 Alkyl phenol:



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
Toxicity to fish	: LC50 (Cyprinus carpio (Carp)): > 100 mg Exposure time: 96 h Test Type: static test Test substance: WAF	g/l
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 1 Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202	00 mg/l
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF	algae)): > 100 mg/l

Ecotoxicology Assessment

Acute aquatic toxicity	:	Not classified based on available information.
Chronic aquatic toxicity	:	Not classified based on available information.

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

	g onan any annou banato complex.
Toxicity to fish :	LC50 (Oncorhynchus mykiss (rainbow trout)): 94.8 mg/l Exposure time: 96 h Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other : aquatic invertebrates	EL50 (Daphnia magna (Water flea)): 50 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic : plants	NOELR (Pseudokirchneriella subcapitata (green algae)): 4.05 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 Remarks: The toxicological data has been taken from products of similar composition.
Toxicity to daphnia and other :	NOELR: 100 mg/l



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

/ersion: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023	
aquatic invertebrates (Chronic toxicity)	Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211		
Ecotoxicology Assessment			
Acute aquatic toxicity	Acute aquatic toxicity Category 3; Harn	nful to aquatic life.	
Chronic aquatic toxicity	: Chronic aquatic toxicity Category 3; Ha with long lasting effects.	Irmful to aquatic life	

12.2 Persistence and degradability

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 0 % Exposure time: 28 d Method: OECD Test Guideline 301B
		Method. OEOD Test Oddeline 30TD

C14-16-18 Alkyl phenol:

Biodegradability	:	Result: Readily biodegradable. Remarks: Expert judgement

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Biodegradability	:	Result: Not readily biodegradable.
		Biodegradation: 23 %
		Exposure time: 28 d
		Method: OECD Test Guideline 301B
		Remarks: The toxicological data has been taken from
		products of similar composition.



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0

н

Revision Date: 27.06.2023

Print Date: 16/10/2023

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n-	:	log Pow: > 7.5
octanol/water		

C14-16-18 Alkyl phenol:

Partition coefficient: n-	:	log Pow: > 7.2
octanol/water		

Molybdenum polysulphide long chain alkyl dithiocarbamate complex:

Partition coefficient: n-	:	log Pow: > 5.1
octanol/water		Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:		
Endocrine disrupting potential	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Additional ecological information	:	No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023	
Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways o chemical or used container. Send to a licensed waste management of		
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.		

SECTION 14: Transport information

14.1 UN number

	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.2	2 UN proper shipping name		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.3	B Transport hazard class(es)		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA_P	:	Not regulated as a dangerous good
14.4	Packing group		
	ADR	:	Not regulated as a dangerous good
	RID	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA (Cargo)	:	Not regulated as a dangerous good
	IATA_P (Passenger)	:	Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	: Not applicable			
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	: Not applicable			
The Persistent Organic Pollutants Regulations (retained : Not applicable Regulation (EU) 2019/1021 as amended for Great Britain)				
Regulation (EC) No 1005/2009 on substances that : Not applicable deplete the ozone layer				
UK REACH List of substances subject to authorisation : Not applicable (Annex XIV)				
Control of Major Accident Hazards Regulations Not applicable 2015 (COMAH)				
The components of this product are reported in the following inventories:				
	n compliance with the inventory			
TSCA : All substances listed a	as active on the TSCA inventory			
AIIC : Not in compliance with	h the inventory			
DSL : All components of this	s product are on the Canadian DSL			



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0	Revision Date: 27.06.2023	Print Date: 16/10/2023
ENCS	: On the inventory, or in compliance w	ith the inventory
KECI	: On the inventory, or in compliance w	ith the inventory
PICCS	: On the inventory, or in compliance w	ith the inventory
IECSC	: On the inventory, or in compliance w	ith the inventory
NZIoC	: Not in compliance with the inventory	

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements				
H304	:	May be fatal if swallowed and enters airways.		
H315	:	Causes skin irritation.		
H317	:	May cause an allergic skin reaction.		
H373	:	May cause damage to organs through prolonged or repeated exposure.		
H412	:	Harmful to aquatic life with long lasting effects.		
H413	:	May cause long lasting harmful effects to aquatic life.		
Full text of other abbreviations				
Aquatic Chronic	:	Long-term (chronic) aquatic hazard		
Asp. Tox.	:	Aspiration hazard		
Skin Irrit.	:	Skin irritation		
Skin Sens.	:	Skin sensitisation		
STOT RE	:	Specific target organ toxicity - repeated exposure		
SUPLR EXP	:	Supplier-recommended exposure guidelines		
SUPLR EXP / TWA	:	Time weighted average		

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule;



according to Regulation (EC) No. 1907/2006 NAPA® N23660L FD 5W20 ECOB Synthetic Motor Oil

Version: 8.0

Revision Date: 27.06.2023

Print Date: 16/10/2023

ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very **Bioaccumulative**

Further information

Internal information : 000000242474

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN