



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Product code : 903376

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global
Operations
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local
CSR contact person

E-mail address of person : SDS@valvolineglobal.com
responsible for the SDS

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number
at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI
2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt, Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
AMINES, POLYETHYLENEPOLY-, REACTION PRODUCTS WITH 1,3- DIOXOLAN-2-ONE AND SUCCINIC ANHYDRIDE MONOPOLYISOBUTENYL DERIVS.	147880-09-9	Aquatic Chronic 4; H413	>= 5 - < 10
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 1 - < 2.5
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13- xxxx	Asp. Tox. 1; H304	>= 1 - < 2.5
Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs.,	722503-69-7	Skin Sens. 1; H317 Aquatic Chronic 4;	>= 0.5 - < 1



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

calcium salt		H413	
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	722503-68-6	Skin Sens. 1B; H317 Aquatic Chronic 4; H413	$\geq 0.5 - < 1$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : carbon dioxide and carbon monoxide
Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

application area.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Electrical installations / working materials must comply with the technological safety standards.

Advice on common storage : No materials to be especially mentioned.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses

Hand protection

Material : neoprene, nitrile rubber

Break through time : ≥ 240 min

Glove thickness : ≥ 0.35 mm

Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used,



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.

Skin and body protection : Protective suit

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: amber
Odour	: oily
Odour Threshold	: No data available
pH	: Not applicable
Pour point	: < -39 °C
Boiling point/boiling range	: No data available
Flash point	: 205 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Relative density	:	No data available
Density	:	ca. 0.854 g/cm ³ (15.6 °C)
Bulk density	:	Not applicable
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 72 mm ² /s (40 °C)
Oxidizing properties	:	No data available

9.2 Other information

Self-ignition	:	No data available
---------------	---	-------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions. No hazards to be specially mentioned.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	None known.
---------------------	---	-------------

10.5 Incompatible materials



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: The toxicological data has been taken from products of similar composition.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

inhalation toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity

: LD50 (Rabbit): > 5,000 mg/kg

Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species

: Rabbit

Result

: Mild skin irritation

Remarks

: The toxicological data has been taken from products of similar composition.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species

: Rabbit

Result

: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species

: Rabbit

Result

: Slight, transient irritation

Remarks

: The toxicological data has been taken from products of similar composition.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species

: Rabbit

Result

: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Respiratory sensitisation

Not classified based on available information.

Product:

Assessment : Does not cause skin sensitisation.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Remarks : The toxicological data has been taken from products of similar composition.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Assessment : May cause sensitisation by skin contact.

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Assessment : The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Components:

AMINES, POLYETHYLENEPOLY-, REACTION PRODUCTS WITH 1,3-DIOXOLAN-2-ONE AND SUCCINIC ANHYDRIDE MONOPOLYISOBUTENYL DERIVS.:

Ecotoxicology Assessment

Acute aquatic toxicity :

Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Remarks: The toxicological data has been taken from products of similar composition.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: >= 1,000 mg/l
Exposure time: 14 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL: 10 mg/l
Exposure time: 21 d
Species: Daphnia (water flea)
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Ecotoxicology Assessment

Acute aquatic toxicity :

Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Ecotoxicology Assessment

Acute aquatic toxicity :

Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

12.2 Persistence and degradability

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n- : log Pow: > 7.5
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

Waste Code : The Waste code should be assigned in discussion between the user and the waste disposal company.
The following Waste Codes are only suggestions:
13 02 05, mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Regulation (EC) No 1005/2009 on substances that
deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation
(Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations
2015 (COMAH) : Not applicable

The components of this product are reported in the following inventories:

TCSI	: Not in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory
IECSC	: Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H304	: May be fatal if swallowed and enters airways.
H317	: May cause an allergic skin reaction.
H413	: May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Skin Sens.	:	Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information : R0517092

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® N243BK500L C2 C3 5W30 GM LS
Synthetic Motor Oil

Version: 7.1

Revision Date: 21.06.2023

Print Date: 16/10/2023

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN