

according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® N24460L HP 10W60 FS

Synthetic Motor Oil

Product code : 903409

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global

Operations

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

SDS@valvolineglobal.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Long-term (chronic) aquatic hazard,

H412: Harmful to aquatic life with long lasting

Category 3

effects.



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 5 - < 10
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 2.5 - < 5
PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3- DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8 283-392-8 01-2119493626-26- xxxx	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411 ——— specific concentration limit Skin Irrit. 2; H315	>= 1 - < 2.5



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

		>= 6.25 % Eye Dam. 1; H318 >= 12.5 % Eye Irrit. 2; H319 >= 10.0 %	
BUTYLATED HYDROXY TOLUENE	128-37-0 204-881-4 01-2119565113-46- xxxx	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 ——— M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0.1 - < 0.25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses

Hazardous combustion

products

carbon dioxide and carbon monoxide

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the

technological safety standards.

Further information on storage stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
BUTYLATED HYDROXY TOLUENE	128-37-0	TWA	10 mg/m3	GB EH40

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : neoprene, nitrile rubber

Break through time : >= 240 minGlove thickness : >= 0.35 mm

Directive : Equipment should conform to EN 374

Remarks : Nitrile rubber butyl-rubber

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of

material has to be obtained from the producer of the

protective glove.

The suitability for a specific workplace should be discussed



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

with the producers of the protective gloves.

Skin and body protection Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection No personal respiratory protective equipment normally

required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance liquid

Colour amber

Odour oily

Odour Threshold No data available

рΗ Not applicable

Pour point < -33 °C

Boiling point/boiling range > 225 °C

236 °C Flash point

Method: Cleveland open cup

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure 0.00004 hPa

Calculated Vapor Pressure

Relative vapour density No data available



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

Relative density : ca. 0.866 (15.6 °C)

Density : ca. 0.867 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 149 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Acid chlorides

Acids



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

alkalis

Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: The toxicological data has been taken from

products of similar composition.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

BUTYLATED HYDROXY TOLUENE:



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

Acute oral toxicity : LD50 (Rat): > 6,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit

Result : Mild skin irritation

Remarks : The toxicological data has been taken from products of similar

composition.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species : Rabbit

Result : Irritating to skin.

BUTYLATED HYDROXY TOLUENE:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : Slight, transient irritation



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

Remarks : Expected based on components.

Remarks : May cause irreversible eye damage.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : No eye irritation Result : No eye irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit

Result : Slight, transient irritation

Remarks : The toxicological data has been taken from products of similar

composition.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species : Rabbit
Result : Corrosive

BUTYLATED HYDROXY TOLUENE:

Species : Rabbit

Method : OECD Test Guideline 405
Result : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Remarks : The toxicological data has been taken from products of similar

composition.



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

BUTYLATED HYDROXY TOLUENE:

Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

BUTYLATED HYDROXY TOLUENE:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

: LL50 (Fish): > 100 mg/l Toxicity to fish

Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

aquatic invertebrates

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

NOEC 10 mg/l

Species: Fish

Toxicity to daphnia and other : NOEC: 10 mg/l

aquatic invertebrates

(Chronic toxicity)

Species: Aquatic invertebrates

Ecotoxicology Assessment

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish LC50 (Danio rerio (zebra fish)): > 100 mg/l

> Exposure time: 96 h Test Type: static test

Remarks: The toxicological data has been taken from

products of similar composition.

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Toxicity to algae/aquatic

plants

: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

Ecotoxicology Assessment

Not classified based on available information. Acute aquatic toxicity

Chronic aquatic toxicity Chronic aquatic toxicity Category 4; May cause long lasting

harmful effects to aquatic life.



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, **ZINC SALTS:**

Toxicity to daphnia and other : NOEC: 0.4 mg/l

aquatic invertebrates

(Chronic toxicity)

End point: Reproduction Test

Exposure time: 28 d

Species: Daphnia magna (Water flea)

Test substance: WAF

Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

BUTYLATED HYDROXY TOLUENE:

Toxicity to fish : LC50 (Fish): estimated 0.199 mg/l

Exposure time: 96 h Remarks: **QSAR**

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.48 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

M-Factor (Acute aquatic

toxicity)

1

Toxicity to fish (Chronic

toxicity)

NOEC 0.053 mg/l

Exposure time: 42 d

Species: Oryzias latipes (Orange-red killifish)

Test Type: flow-through test

M-Factor (Chronic aquatic

toxicity)

Ecotoxicology Assessment

Acute aquatic toxicity Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Chronic aquatic toxicity Chronic aquatic toxicity Category 1; Very toxic to aquatic life

with long lasting effects.



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

12.2 Persistence and degradability

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301B

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 1.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

BUTYLATED HYDROXY TOLUENE:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 4.5 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Physico-chemical : Remarks: The product can be degraded by abiotic (e.g.

removability chemical or photolytic) processes.

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n- : log Pow: > 7.5

octanol/water

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Partition coefficient: n- : log Pow: 0.56

octanol/water

BUTYLATED HYDROXY TOLUENE:

Partition coefficient: n- : log Pow: 4.17 (21 °C)

octanol/water



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting : The substance/mixture does not contain components

potential

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixtureRelevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the

following entries should be

considered: Number on list 3 Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Not applicable

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

Control of Major Accident Hazards Regulations

2015 (COMAH)

Not applicable

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : Contact your sales representative for additional information.



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage

Skin Irrit. : Skin irritation

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x%



according to Regulation (EC) No. 1907/2006 NAPA® N24460L HP 10W60 FS Synthetic Motor Oil

Classification procedure:

Version: 7.0 Revision Date: 07.07.2023 Print Date: 16/10/2023

growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population: LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information: R0517747

Classification of the mixture:

Aquatic Chronic 3 H412 Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN