



TECHNICAL DATA SHEET

75W-90 SS

Product Type 75W-90 SEMI SYNTHETIC GEAR OIL
Product Code N301

Description

A high performance semi synthetic gear oil suitable for modern gearboxes and differentials.

Benefits

- Excellent oxidation stability
- Outstanding low and high temperature performance
- May be used where an SAE 80W-90, 85W-90 or 90 API GL-4 or GL-5 oil is specified.
- Good protection against rust and corrosion
- Very high level of wear protection
- Suitable for use in most synchromesh gearboxes and hypoid axle units

Specifications

Always check the owner's manual for the correct oil specification to use.

- API GL-5, GL-4



TECHNICAL DATA SHEET

75W-90 SS

Product Type 75W-90 SEMI SYNTHETIC GEAR OIL
Product Code N301

Typical Properties

SAE Viscosity Grade	SAE J306	-	75W-90
Viscosity @ 100°C	ASTM D-445	mm ² /s	15,4
Viscosity @ 100°C; After shearing	ASTM D-6278	mm ² /s	Stay-in-grade
Viscosity @ 40°C	ASTM D-445	mm ² /s	104,0
Viscosity Index	ASTM D-2270	-	156
Viscosity @ -40°C	ASTM D-5294	mPa.s	<150 000
Pour Point	ASTM D-5950	°C	-48
Specific Gravity	ASTM D-4052	-	0,877
Flash Point	ASTM D-92	°C	164

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Eskan Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu