



TECHNICAL DATA SHEET

HD 75W-80

Product Type	75W-80 MINERAL GEAR OIL
Product Code	N311

Description

Mineral gear oil recommended for use in a wide range of passenger cars and vans.

Benefits

- Improved synchromesh performance
- Shear stability
- Improved shift quality
- Corrosion protection

Specifications

Always check the owner's manual for the correct oil specification to use.

- API GL-4, GL-4+ (Tranself TRZ, NFJ, NFP, TRJ)
- BMW MTF LT-2
- Special Honda MTF 94, MTF, MTF-II



TECHNICAL DATA SHEET

HD 75W-80

Product Type 75W-80 MINERAL GEAR OIL

Product Code N311

Typical Properties

Test	Method	Unit	Value
SAE Viscosity Grade	SAE J300	-	75W-80
Viscosity @ 100°C	ASTM D-445	mm ² /s	8,5
Viscosity @ 100°C; After shearing	ASTM D-6277	mm ² /s	Stay-in-grade
Viscosity @ 40°C	ASTM D-445	mm ² /s	47
Viscosity Index	ASTM D-2270	-	157
Viscosity @ -40°C	ASTM D-5294	mPa.s	<150000
Pour Point	ASTM D-5950	°C	-42
Specific Gravity	ASTM D-4052	-	0,870
Flash Point	ASTM D-92	°C	216

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

DEVELOPED BY VALVOLINE™



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Esplanade Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu