



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : NAPA® N329199L HD 75W85  
SYNTHETIC BLEND GEAR OIL

Product code : 904755

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

#### 1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline  
Wieldrechtseweg 39  
3316 BG Dordrecht  
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local  
CSR contact person

E-mail address of person : SDS@valvoline.com  
responsible for the SDS

#### 1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number  
at 112

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Long-term (chronic) aquatic hazard,  
Category 3

H412: Harmful to aquatic life with long lasting  
effects.



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)**

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P273 Avoid release to the environment.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

#### Additional Labelling

EUH208 Contains DI-TERT-BUTYL POLYSULFIDE, Amines, C10-14-tert-alkyl. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13-xxxx	Asp. Tox. 1; H304	>= 70 - < 80
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25-xxxx	Asp. Tox. 1; H304	>= 5 - < 10
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9 265-159-2 649-469-00-9	Asp. Tox. 1; H304	>= 2.5 - < 5
DI-TERT-BUTYL POLYSULFIDE	68937-96-2	Skin Sens. 1B;	>= 1 - < 2.5



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

	273-103-3 01-2119540515-43- xxxx	H317 Aquatic Chronic 3; H412	
Amines, C10-14-tert-alkyl	Not Assigned  01-2119456798-18	Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 0.025 - < 0.1$
(Z)-octadec-9-enylamine, C16-18- (even numbered, saturated and unsaturated)-alkylamines	1213789-63-9 627-034-4 01-2119473797-19- xxxx	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Liver, Immune system, Gastro- intestinal system) Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	$\geq 0.025 - < 0.1$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

advice.  
If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.  
  
Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.  
Use personal protective equipment.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Advice on common storage : No materials to be especially mentioned.



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : No data available

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Safety glasses

#### Hand protection

Material : neoprene, nitrile rubber  
Break through time :  $\geq 240$  min  
Glove thickness :  $\geq 0.35$  mm  
Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.

Skin and body protection : Protective suit

Respiratory protection : No personal respiratory protective equipment normally required.

B



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: amber
Odour	: oily
Odour Threshold	: No data available
pH	: Not applicable
Pour point	: $\leq -42$ °C
Boiling point/boiling range	: No data available
Flash point	: 170 °C Method: ASTM D 92, Pensky-Martens closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 0.861 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: immiscible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 66.9 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

### 9.2 Other information

Self-ignition : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.  
No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : excessive heat

### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Not classified based on available information.





## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

### Components:

#### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No mortality observed at this dose.
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

- Acute oral toxicity : LD50 (Rat): > 15 g/kg
- Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

#### **Distillates (petroleum), solvent-dewaxed light paraffinic:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### **DI-TERT-BUTYL POLYSULFIDE:**

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: No mortality observed at this dose.
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: No mortality observed at this dose.

#### **Amines, C10-14-tert-alkyl:**



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

- Acute oral toxicity : LD50 Oral (Rat, male and female): 612 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes  
Assessment: The component/mixture is moderately toxic after single ingestion.
- Acute inhalation toxicity : LC50 (Rat, male and female): Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The component/mixture is highly toxic after short term inhalation.
- Acute dermal toxicity : LD50 (Rat, male and female): 251 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes  
Assessment: The component/mixture is toxic after single contact with skin.

### **(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:**

- Acute oral toxicity : LD50 (Rat): 1,689 mg/kg  
Method: OECD Test Guideline 401  
Remarks: The toxicological data has been taken from products of similar composition.
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: No mortality observed at this dose.  
The toxicological data has been taken from products of similar composition.

### **Skin corrosion/irritation**

Not classified based on available information.

### **Components:**

#### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

- Species : Rabbit  
Result : No skin irritation

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

- Assessment : Slight, transient irritation  
Result : Slight, transient irritation

#### **Distillates (petroleum), solvent-dewaxed light paraffinic:**



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

Species : Rabbit  
Result : Slight, transient irritation

### DI-TERT-BUTYL POLYSULFIDE:

Result : Mild skin irritation

### Amines, C10-14-tert-alkyl:

Species : Rabbit  
Result : Corrosive after 3 minutes to 1 hour of exposure  
GLP : yes

### (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:

Species : Rabbit  
Result : Corrosive after 3 minutes to 1 hour of exposure  
Remarks : The toxicological data has been taken from products of similar composition.

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

#### LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species : Rabbit  
Result : No eye irritation

#### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : No eye irritation  
Result : No eye irritation

#### Distillates (petroleum), solvent-dewaxed light paraffinic:

Species : Rabbit  
Result : Slight, transient irritation

### DI-TERT-BUTYL POLYSULFIDE:

Result : Slight, transient irritation

### Amines, C10-14-tert-alkyl:

Species : Rabbit  
Method : No information available.  
Result : Corrosive  
GLP : yes



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

### **(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:**

Species	:	Rabbit
Result	:	Corrosive
Remarks	:	The toxicological data has been taken from products of similar composition.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Product:**

Assessment	:	Does not cause skin sensitisation.
Remarks	:	Based on data from similar materials

### **Components:**

#### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.

#### **Distillates (petroleum), solvent-dewaxed light paraffinic:**

Test Type	:	Buehler Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406

#### **DI-TERT-BUTYL POLYSULFIDE:**

Test Type	:	Maximisation Test
Species	:	Guinea pig
Assessment	:	The product is a skin sensitiser, sub-category 1B.
Method	:	OECD Test Guideline 406

#### **Amines, C10-14-tert-alkyl:**

Test Type	:	Buehler Test
Exposure routes	:	Dermal
Species	:	Guinea pig
Assessment	:	The product is a skin sensitiser, sub-category 1A.
Method	:	Buehler Test



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

GLP : yes

### **(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:**

Assessment : Does not cause skin sensitisation.  
Remarks : The toxicological data has been taken from products of similar composition.

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **DI-TERT-BUTYL POLYSULFIDE:**

Genotoxicity in vitro : Test Type: in vitro assay  
Result: Positive results were obtained in some in vitro tests.

Genotoxicity in vivo : Test Type: Micronucleus test  
Species: Mouse  
Cell type: Bone marrow  
Method: OECD Test Guideline 474  
Result: negative

### **(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative  
Remarks: The toxicological data has been taken from products of similar composition.

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

### **Distillates (petroleum), solvent-dewaxed light paraffinic:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

Not classified based on available information.

### **Components:**

#### **(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:**

Exposure routes : Inhalation  
Target Organs : Respiratory Tract  
Assessment : The substance or mixture is classified as specific target organ  
toxicant, single exposure, category 3 with respiratory tract  
irritation.

### **STOT - repeated exposure**

Not classified based on available information.

### **Components:**

#### **(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:**

Exposure routes : Ingestion  
Target Organs : Liver, Immune system, Gastro-intestinal system  
Assessment : The substance or mixture is classified as specific target organ  
toxicant, repeated exposure, category 2.

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

May be fatal if swallowed and enters airways.

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

May be fatal if swallowed and enters airways.

### **Distillates (petroleum), solvent-dewaxed light paraffinic:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

### **(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Further information**

##### **Product:**

Remarks : No data available

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

##### **Product:**

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

##### **Components:**

#### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

Toxicity to fish (Chronic toxicity) : NOELR:  $\geq 1,000$  mg/l  
Exposure time: 14 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL: 10 mg/l  
Exposure time: 21 d  
Species: Daphnia (water flea)  
Test substance: WAF  
Method: OECD Test Guideline 211

### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

### DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish):  $> 100$  mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates):  $> 10,000$  mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Algae, algal mat (Algae)):  $> 100$  mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l  
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l  
Species: Aquatic invertebrates

### Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

### Distillates (petroleum), solvent-dewaxed light paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)):  $> 100$  mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)):  $> 10,000$  mg/l





## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

aquatic invertebrates	Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Test substance: WAF Method: OECD Test Guideline 211

### Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.

### DI-TERT-BUTYL POLYSULFIDE:

#### Ecotoxicology Assessment

Acute aquatic toxicity	: Harmful to aquatic life.  Acute aquatic toxicity Category 3; Harmful to aquatic life.
Chronic aquatic toxicity	: Harmful to aquatic life with long lasting effects.  Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

### Amines, C10-14-tert-alkyl:

#### Ecotoxicology Assessment

Acute aquatic toxicity	: Very toxic to aquatic life.  Acute aquatic toxicity Category 1; Very toxic to aquatic life.
Chronic aquatic toxicity	: Very toxic to aquatic life with long lasting effects.



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

Chronic aquatic toxicity Category 1; Very toxic to aquatic life with long lasting effects.

### **(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:**

- Toxicity to fish : LC50 (Fish): estimated 0.06 mg/l  
Exposure time: 96 h  
Remarks: The toxicological data has been taken from products of similar composition.
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.98 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
Remarks: The toxicological data has been taken from products of similar composition.
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 0.083 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
Remarks: The toxicological data has been taken from products of similar composition.
- M-Factor (Acute aquatic toxicity) : 10
- M-Factor (Chronic aquatic toxicity) : 10

### **Ecotoxicology Assessment**

- Acute aquatic toxicity : Acute aquatic toxicity Category 1; Very toxic to aquatic life.
- Chronic aquatic toxicity : Chronic aquatic toxicity Category 1; Very toxic to aquatic life with long lasting effects.

## **12.2 Persistence and degradability**

### **Components:**

### **LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:**

- Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

### **Distillates (petroleum), solvent-dewaxed light paraffinic:**

Biodegradability : Result: Inherently biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

### **DI-TERT-BUTYL POLYSULFIDE:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 13 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

### **(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 66 %  
Exposure time: 28 d  
Method: Regulation (EC) No. 440/2008, Annex, C.4-C  
Remarks: The toxicological data has been taken from products of similar composition.

## **12.3 Bioaccumulative potential**

### **Components:**

#### **Amines, C10-14-tert-alkyl:**

Partition coefficient: n-octanol/water : log Pow: 2.9 (20 °C)

#### **(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines:**

Partition coefficient: n-octanol/water : log Pow: estimated 6 - 8

## **12.4 Mobility in soil**

No data available

## **12.5 Results of PBT and vPvB assessment**

### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

### 12.6 Other adverse effects

**Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.

---

### SECTION 14: Transport information

#### 14.1 UN number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

IATA\_P : Not regulated as a dangerous good

### 14.4 Packing group

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA\_P (Passenger) : Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:  
Number on list 3

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable

The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Control of Major Accident Hazards Regulations : Not applicable



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

2015 (COMAH)

**The components of this product are reported in the following inventories:**

TCSI	: Not in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory

### 15.2 Chemical safety assessment

No data available

**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

## SECTION 16: Other information

**Full text of H-Statements**

H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H335	: May cause respiratory irritation.
H373	: May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Internal information : 000000281188



## SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006  
NAPA® N329199L HD 75W85 SYNTHETIC  
BLEND GEAR OIL

Version: 1.0

Revision Date: 20.04.2023

Print Date: 16/10/2023

---

### Classification of the mixture:

Aquatic Chronic 3

H412

### Classification procedure:

Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN