



TECHNICAL DATA SHEET

75W FS

Product Type 75W SYNTHETIC GEAR OIL
Product Code N334

Description

A synthetic low-viscosity manual transmission fluid that can be used in a wide variety of modern vehicles.

Benefits

- Multi-vehicle fluid specified by many manufacturers
- Long-lasting formulation, designed for maximum product life
- Outstanding performance across a wide temperature range

Specifications

Always check the owner's manual for the correct oil specification to use.

- API GL-4
- BMW MTF LT-3
- FORD M2C200D-2, M2C200D-3



TECHNICAL DATA SHEET

75W FS

Product Type 75W SYNTHETIC GEAR OIL
Product Code N334

Typical Properties

| | | | |
|-----------------------------------|-------------|--------------------|---------------|
| SAE Viscosity Grade | SAE J306 | - | 75W |
| Viscosity @ 100°C | ASTM D-445 | mm ² /s | 6,1 |
| Viscosity @ 100°C; After shearing | ASTM D-6278 | mm ² /s | Stay-in-grade |
| Viscosity @ 40°C | ASTM D-445 | mm ² /s | 33,0 |
| Viscosity Index | ASTM D-2270 | - | 134 |
| Viscosity @ -40°C | ASTM D-5294 | mPa.s | <150000 |
| Pour Point | ASTM D-5950 | °C | -42 |
| Specific Gravity | ASTM D-4052 | - | 0,851 |
| Flash Point | ASTM D-92 | °C | 194 |

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Eskan Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu