

according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® NT10220L SHPD E9 15W40

Motor Oil

Product code : 905481

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global

Operations

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

SDS@valvolineglobal.com

#### 1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.

# Valvoline, Global

# **SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### **Additional Labelling**

EUH208 Contains Reaction products of benzenesulfonic acid, mono- C20-24 (even)-sec-

alkyl derivs. para-, calcium salts, BENZENE, POLYPROPENE DERIVATIVES,

SULFONATED, CALCIUM SALTS. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

## 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 5 - < 10
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28- xxxx	Aquatic Chronic 4; H413	>= 2.5 - < 5
PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3- DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8 283-392-8 01-2119493626-26- xxxx	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411 ——— specific concentration limit	>= 1 - < 2.5



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

		Skin Irrit. 2; H315 >= 6.25 % Eye Dam. 1; H318 >= 12.5 % Eye Irrit. 2; H319 >= 10.0 %	
Reaction products of benzenesulfonic acid, mono- C20-24 (even)-sec-alkyl derivs. para-, calcium salts	Not Assigned 947-519-7 01-2120765489-36- xxxx	Skin Sens. 1B; H317  specific concentration limit Skin Sens. 1B >= 10 %	>= 0.5 - < 1
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS	Not Assigned	Skin Sens. 1B; H317	>= 0.1 - < 0.5

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

# 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion : carbon dioxide and carbon monoxide

products Nitrogen oxides (NOx)

#### 5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Hand protection

Material : neoprene, nitrile rubber

Break through time : >= 240 min Glove thickness : >= 0.35 mm

Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the

protective glove.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally

required.



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH : Not applicable

Pour point : < -36 °C

Boiling point/boiling range : No data available

Flash point : 238 °C

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0.876 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : < 6,800 mPa.s (-20 °C)

Viscosity, kinematic : 107 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

# **SECTION 10: Stability and reactivity**

# 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

# 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

#### **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

#### **Acute toxicity**

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

## **Components:**

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity LD50 (Rabbit): > 5 g/kg

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

: LD50 (Rat): > 5,000 mg/kg Acute oral toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: The toxicological data has been taken from

products of similar composition.

# PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Acute inhalation toxicity LC50 (Rat): > 2.3 mg/l

> Exposure time: 4 h Test atmosphere: vapour

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

#### Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Remarks : Not classified

#### **Components:**

# **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment Slight, transient irritation Result Slight, transient irritation

# Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species Rabbit



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

Result : Mild skin irritation

Remarks : The toxicological data has been taken from products of similar

composition.

# PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species : Rabbit

Result : Irritating to skin.

#### Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Remarks : Not classified

#### **Components:**

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : No eye irritation
Result : No eye irritation

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit

Result : Slight, transient irritation

Remarks : The toxicological data has been taken from products of similar

composition.

# PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species : Rabbit
Result : Corrosive

#### Respiratory or skin sensitisation

## Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

# **Components:**

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Remarks : The toxicological data has been taken from products of similar

composition.

# PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Test Type : Buehler Test
Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Reaction products of benzenesulfonic acid, mono- C20-24 (even)-sec-alkyl derivs. para-, calcium salts:

Assessment : The product is a skin sensitiser, sub-category 1B.

#### BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Assessment : The product is a skin sensitiser, sub-category 1B.

#### Germ cell mutagenicity

Not classified based on available information.

#### Components:

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

# PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

# Carcinogenicity

Not classified based on available information.

#### Components:

# **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

# STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### Components:

# **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

May be fatal if swallowed and enters airways.

#### **Further information**

**Product:** 

Remarks : No data available

#### **SECTION 12: Ecological information**

# 12.1 Toxicity

#### **Product:**

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity: Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

## **Components:**

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

NOEC: 10 mg/l

Species: Fish

Toxicity to daphnia and other : NOEC: 10 mg/l

aquatic invertebrates

(Chronic toxicity)

**Species: Aquatic invertebrates** 

# **Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

#### Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

> Exposure time: 96 h Test Type: static test

Remarks: The toxicological data has been taken from

products of similar composition.

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Toxicity to algae/aquatic

plants

: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

#### **Ecotoxicology Assessment**

Acute aquatic toxicity Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

Chronic aquatic toxicity Chronic aquatic toxicity Category 4; May cause long lasting

harmful effects to aquatic life.

PHOSPHORODITHIOIC ACID, MIXED 0,0-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, **ZINC SALTS:** 

Toxicity to daphnia and other : NOEC: 0.4 mg/l

aquatic invertebrates (Chronic toxicity)

**End point: Reproduction Test** 

Exposure time: 28 d

Species: Daphnia magna (Water flea)

Test substance: WAF

Method: OECD Test Guideline 211

**Ecotoxicology Assessment** 

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

Reaction products of benzenesulfonic acid, mono- C20-24 (even)-sec-alkyl derivs. para-, calcium salts:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EC50 (Selenastrum capricornutum (green algae)): > 1,000

Exposure time: 96 h

**Ecotoxicology Assessment** 

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity Not classified based on available information.



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

# 12.2 Persistence and degradability

#### **Components:**

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability Result: Not readily biodegradable.

> Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301B

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Biodegradability : Result: Not readily biodegradable.

> Biodegradation: 1.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Reaction products of benzenesulfonic acid, mono- C20-24 (even)-sec-alkyl derivs. para-, calcium salts:

Biodegradability : Biodegradation: 8 %

Exposure time: 28 d

Method: OECD Test Guideline 301D

#### 12.3 Bioaccumulative potential

#### Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n-

octanol/water

:  $\log Pow: > 7.5$ 

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Partition coefficient: n-: log Pow: 0.56

octanol/water

# 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

**Product:** 

This substance/mixture contains no components considered Assessment

to be either persistent, bioaccumulative and toxic (PBT), or



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### 12.6 Other adverse effects

**Product:** 

**Endocrine disrupting** 

potential

: The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

No data available

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

# **SECTION 14: Transport information**

#### 14.1 UN number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

16/20



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

**IMDG** : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA\_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# **SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high

concern (SVHC) for Authorisation

Not applicable

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Not applicable



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

Britain)

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable

UK REACH List of substances subject to authorisation

(Annex XIV)

Not applicable

Control of Major Accident Hazards Regulations

2015 (COMAH)

Not applicable

#### Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

#### The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

#### 15.2 Chemical safety assessment

#### No data available

#### **Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

# **SECTION 16: Other information**

#### **Full text of H-Statements**

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H411 : Toxic to aquatic life with long lasting effects.

H413 : May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk: IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic



according to Regulation (EC) No. 1907/2006 NAPA® NT10220L SHPD E9 15W40 Motor Oil

Version: 7.0 Revision Date: 05.09.2023 Print Date: 16/10/2023

Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Internal information: 000000274352

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN