



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Product code : 903468

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global
Operations
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local
CSR contact person

E-mail address of person : SDS@valvolineglobal.com
responsible for the SDS

1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt, 2,5-Furandione, polymer with 1-hexadecene, methyloxirane polymer with oxirane bis (2-aminopropyl) ether and 2-methyl-1-propene, 4-(phenylamino)phenyl imide, Coconut oil, reaction products with boric acid (H3BO3), diethanolamine and glycerol, Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13-xxxx	Asp. Tox. 1; H304	>= 25 - < 40
Benzenepropanoic acid,3,5-bis(1,1-dimethyl-ethyl)-4,4hydroxy-C7-C9 alkyl esters	125643-61-0 406-040-9406-040-9 607-530-00-7	Aquatic Chronic 4; H413	>= 2.5 - < 5
Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated	134758-95-5	Aquatic Chronic 4; H413	>= 2.5 - < 5
AMINES, POLYETHYLENEPOLY-, REACTION PRODUCTS WITH 1,3-	147880-09-9	Aquatic Chronic 4; H413	>= 1 - < 2.5



Valvoline
Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

DIOXOLAN-2-ONE AND SUCCINIC ANHYDRIDE MONOPOLYISOBUTENYL DERIVS.			
2,5-Furandione, polymer with 1-hexadecene, methyloxirane polymer with oxirane bis (2-aminopropyl) ether and 2-methyl-1-propene, 4-(phenylamino)phenyl imide	873694-48-5	Skin Sens. 1B; H317 Aquatic Chronic 4; H413	$\geq 1 - < 2.5$
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic 4; H413	$\geq 1 - < 2.5$
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	68784-31-6 272-238-5 01-2119657973-23-xxxx	Eye Dam. 1; H318 Aquatic Chronic 2; H411	$\geq 1 - < 2.5$
Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt	722503-69-7	Aquatic Chronic 4; H413	$\geq 1 - < 2.5$
Coconut oil, reaction products with boric acid (H3BO3), diethanolamine and glycerol	1428353-74-5 01-2120067755-46-xxxx	Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 2; H411	$\geq 1 - < 2.5$
Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt	722503-69-7	Skin Sens. 1; H317 Aquatic Chronic 4; H413	$\geq 0.1 - < 0.25$
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	722503-68-6	Skin Sens. 1B; H317 Aquatic Chronic 4; H413	$\geq 0.1 - < 0.25$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

- | | | |
|------------------------|---|---|
| In case of eye contact | : | Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist. |
| If swallowed | : | Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|----------|---|--------------------------------|
| Symptoms | : | No symptoms known or expected. |
|----------|---|--------------------------------|

4.3 Indication of any immediate medical attention and special treatment needed

- | | | |
|-----------|---|--|
| Treatment | : | No hazards which require special first aid measures.

Treat symptomatically. |
|-----------|---|--|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | | |
|--------------------------------|---|--|
| Suitable extinguishing media | : | Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. |
| Unsuitable extinguishing media | : | High volume water jet |

5.2 Special hazards arising from the substance or mixture

- | | | |
|-------------------------------|---|---|
| Hazardous combustion products | : | carbon dioxide and carbon monoxide
Nitrogen oxides (NOx) |
|-------------------------------|---|---|

5.3 Advice for firefighters

- | | | |
|---|---|---|
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |
| Further information | : | Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the
application area.

Advice on protection against : Normal measures for preventive fire protection.
fire and explosion

Hygiene measures : General industrial hygiene practice.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Electrical installations / working materials must comply with
areas and containers the technological safety standards.

Advice on common storage : No materials to be especially mentioned.

Further information on : No decomposition if stored and applied as directed.
storage stability

7.3 Specific end use(s)

Specific use(s) : No data available



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Workers	Inhalation	Long-term systemic effects	2.93 mg/m3
	Remarks:RD TOX - Repeated dose toxicity			
	Workers	Dermal	Long-term systemic effects	10.42 mg/kg
	Remarks:RD TOX - Repeated dose toxicity			
	Consumer use	Inhalation	Long-term systemic effects	11.75 mg/m3
	Remarks:RD TOX - Repeated dose toxicity			
	Consumer use	Dermal	Long-term systemic effects	2.1 mg/kg
	Remarks:RD TOX - Repeated dose toxicity			
	Consumer use	Oral	Long-term systemic effects	0.21 mg/kg
	Remarks:RD TOX - Repeated dose toxicity			

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Sewage treatment plant	3.8 mg/l
	Fresh water sediment	0.0701 mg/kg
	Marine sediment	0.00701 mg/kg
	Soil	0.0548 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses

Hand protection
Material : neoprene, nitrile rubber



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Break through time	: >= 240 min
Glove thickness	: >= 0.35 mm
Directive	: Equipment should conform to EN 374
Remarks	: The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove.
Skin and body protection	: Protective suit
Respiratory protection	: No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: amber
Odour	: No data available
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: ca. 202 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data available



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	ca. 0.857 g/cm ³ (15.6 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 71 mm ² /s (40 °C)
Oxidizing properties	:	No data available

9.2 Other information

Self-ignition	:	No data available
---------------	---	-------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids
Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Remarks: No mortality observed at this dose.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: The toxicological data has been taken from products of similar composition.

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat, female): 2,900 mg/kg
Method: OECD Test Guideline 401

LD50 (Rat, male): 3,400 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

Coconut oil, reaction products with boric acid (H3BO3), diethanolamine and glycerol:

Acute oral toxicity : (Rat, female): > 200 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species : Rabbit
Result : No skin irritation

Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated:

Result : No skin irritation
Remarks : Expected

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Result	:	Mild skin irritation
Remarks	:	The toxicological data has been taken from products of similar composition.

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Species	:	Rabbit
Result	:	Mild skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result	:	No eye irritation
--------	---	-------------------

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species	:	Rabbit
Result	:	No eye irritation

Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated:

Result	:	No eye irritation
Remarks	:	Expected

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species	:	Rabbit
Result	:	Slight, transient irritation
Remarks	:	The toxicological data has been taken from products of similar composition.

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Species	:	Rabbit
Result	:	Irreversible effects on the eye

Species	:	Rabbit
Exposure time	:	24 - 72 hrs
Assessment	:	Category 1
Method	:	in vitro assay
GLP	:	yes
Remarks	:	OECD GHS



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Coconut oil, reaction products with boric acid (H₃BO₃), diethanolamine and glycerol:

Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Assessment : Does not cause skin sensitisation.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

2,5-Furandione, polymer with 1-hexadecene, methyloxirane polymer with oxirane bis (2-aminopropyl) ether and 2-methyl-1-propene, 4-(phenylamino)phenyl imide:

Assessment : The product is a skin sensitiser, sub-category 1B.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Remarks : The toxicological data has been taken from products of similar composition.

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Coconut oil, reaction products with boric acid (H₃BO₃), diethanolamine and glycerol:

Assessment : The product is a skin sensitiser, sub-category 1B.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Assessment : May cause sensitisation by skin contact.

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Assessment : The product is a skin sensitizer, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Repeated dose toxicity

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Species	: Rat, male and female
NOAEL	: 125 mg/kg
Application Route	: Oral
Exposure time	: 28 d
Method	: oral (gavage)
GLP	: yes

Aspiration toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: >= 1,000 mg/l
Exposure time: 14 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL: 10 mg/l
Exposure time: 21 d
Species: Daphnia (water flea)
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Benzenepropanoic acid,3,5-bis(1,1-dimethyl-ethyl)-4,4hydroxy-C7-C9 alkyl esters:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated:

Ecotoxicology Assessment

Acute aquatic toxicity :

Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

AMINES, POLYETHYLENEPOLY-, REACTION PRODUCTS WITH 1,3-DIOXOLAN-2-ONE AND SUCCINIC ANHYDRIDE MONOPOLYISOBUTENYL DERIVS.:

Ecotoxicology Assessment

Acute aquatic toxicity :

Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

2,5-Furandione, polymer with 1-hexadecene, methyloxirane polymer with oxirane bis (2-aminopropyl) ether and 2-methyl-1-propene, 4-(phenylamino)phenyl imide:

Ecotoxicology Assessment

Acute aquatic toxicity :

Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Test Type: static test

Remarks: The toxicological data has been taken from products of similar composition.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.4 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 75 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): 410 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Ecotoxicology Assessment

Acute aquatic toxicity :

Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

Coconut oil, reaction products with boric acid (H3BO3), diethanolamine and glycerol:

Ecotoxicology Assessment

Acute aquatic toxicity :

Not classified based on available information.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Chronic aquatic toxicity Category 2; Toxic to aquatic life with long lasting effects.

Benzenesulfonic acid methyl-, mono C20-26 branched alkyl derivs., calcium salt:

Ecotoxicology Assessment

Acute aquatic toxicity :

Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Ecotoxicology Assessment

Acute aquatic toxicity :

Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.

12.2 Persistence and degradability

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: < 5 %
Exposure time: 27 d
Method: OECD Test Guideline 301D

Coconut oil, reaction products with boric acid (H₃BO₃), diethanolamine and glycerol:

Biodegradability : Result: Readily biodegradable.

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n- : log Pow: > 7.5
octanol/water

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Partition coefficient: n- : log Pow: 4
octanol/water

Coconut oil, reaction products with boric acid (H₃BO₃), diethanolamine and glycerol:

Partition coefficient: n- : Pow: 3.57 (25 °C)



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable
UK REACH Candidate list of substances of very high : Not applicable



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

concern (SVHC) for Authorisation

The Persistent Organic Pollutants Regulations (retained : Not applicable
Regulation (EU) 2019/1021 as amended for Great
Britain)

Regulation (EC) No 1005/2009 on substances that : Not applicable
deplete the ozone layer

UK REACH List of substances subject to authorisation : Not applicable
(Annex XIV)

Control of Major Accident Hazards Regulations : Not applicable
2015 (COMAH)

The components of this product are reported in the following inventories:

TCSI	: Not in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: Not in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: Not in compliance with the inventory
KECI	: Not in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: Not in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

SECTION 16: Other information

Full text of H-Statements

H304	:	May be fatal if swallowed and enters airways.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H411	:	Toxic to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Skin Sens.	:	Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
NAPA® NT103BK500L ECO UHPD 5W30 FS
Synthetic Motor Oil

Version: 4.0

Revision Date: 25.07.2023

Print Date: 16/10/2023

Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information : 000000277509

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN