

according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® NT105BK1000L XHPD 10W40 SS

Synthetic Motor Oil

Product code : 902606

Unique Formula Identifier

(UFI)

YXS5-3PYF-730S-N7QJ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person

responsible for the SDS

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Valvoline_{IM}

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms

<u>(!</u>)

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.

P272 Contaminated work clothing should not be allowed out

of the workplace.

P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

-			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		,



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

	Registration number		
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	68784-31-6 272-238-5 01-2119657973-23- xxxx	Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 1 - < 2.5
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated	Not Assigned	Skin Sens. 1B; H317 Repr. 2; H361d ——— specific concentration limit Repr. 2 17.15 %	>= 1 - < 2.5
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	722503-68-6	Skin Sens. 1B; H317 Aquatic Chronic 4; H413	>= 0.5 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Valvoline, TM

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion

products

: carbon dioxide and carbon monoxide

5.3 Advice for firefighters

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
Phosphorodithioic acid, mixed O,O- bis(sec-Bu and 1,3- dimethylbutyl) esters, zinc salts	Workers	Inhalation	Long-term systemic effects	2.93 mg/m3
	Remarks: RD TOX - Repeated dose toxicity			
	Workers	Dermal	Long-term systemic effects	10.42 mg/kg
	Remarks:RD TOX - Repeated dose toxicity			
	Consumer use	Inhalation	Long-term systemic effects	11.75 mg/m3
	Remarks:RD TOX - Repeated dose toxicity			
	Consumer use	Dermal	Long-term systemic effects	2.1 mg/kg
	Remarks:RD TOX - Repeated dose toxicity			
	Consumer use	Oral	Long-term systemic effects	0.21 mg/kg
	Remarks:RD TOX - Repeated dose toxicity			

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
Phosphorodithioic acid, mixed	Sewage treatment plant	3.8 mg/l
O,O-bis(sec-Bu and 1,3-		
dimethylbutyl) esters, zinc salts		
	Fresh water sediment	0.0701 mg/kg
	Marine sediment	0.00701 mg/kg
	Soil	0.0548 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Hand protection

Material : neoprene, nitrile rubber

Break through time : >= 240 min



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

Glove thickness : >= 0.35 mm

Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the

protective glove.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally

required.

В

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : No data available

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 208 °C



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

Method: Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.869 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 95.3 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Heat

10.5 Incompatible materials

Materials to avoid : Strong acids

Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat, female): 2,900 mg/kg

Method: OECD Test Guideline 401

LD50 (Rat, male): 3,400 mg/kg Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Species : Rabbit

Result : Mild skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Species : Rabbit

Result : Irreversible effects on the eye

Species : Rabbit
Exposure time : 24 - 72 hrs
Assessment : Category 1
Method : in vitro assay

GLP : yes

Remarks : OECD GHS

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Test Type : Buehler Test
Species : Guinea pig

Assessment : Does not cause skin sensitisation.



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated:

Assessment : The product is a skin sensitiser, sub-category 1B.

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Assessment : The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated:

Reproductive toxicity - : Some evidence of adverse effects on development, based on

Assessment animal experiments.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Species : Rat, male and female

NOAEL : 125 mg/kg
Application Route : Oral
Exposure time : 28 d

Method : oral (gavage)

GLP : ves



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

: Not classified based on available information. Acute aquatic toxicity

Chronic aquatic toxicity : Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.4 mg/l

> Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): 75 mg/l aquatic invertebrates

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

: EL50 (Desmodesmus subspicatus (green algae)): 410 mg/l

Toxicity to algae/aquatic

plants End point: Growth inhibition

> Exposure time: 72 h Test Type: static test

Test substance: WAF

Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity Toxic to aquatic life.

Valvoline...

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts:

Ecotoxicology AssessmentAcute aquatic toxicity

Not classified based on available information.

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

Chronic aquatic toxicity Category 4; May cause long lasting

harmful effects to aquatic life.

12.2 Persistence and degradability

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: < 5 % Exposure time: 27 d

Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts:

Partition coefficient: n-

octanol/water

: log Pow: **4**

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting

potential

: The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Waste Code : The Waste code should be assigned in discussion between

the user and the waste disposal company.

The following Waste Codes are only suggestions:

13 02 05, mineral-based non-chlorinated engine, gear and

lubricating oils

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good

: Not regulated as a dangerous good

MDG : Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

IATA_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixtureRelevant EU provisions transposed through retained EU law

UK REACH Candidate list of substances of very high : Not applicable concern (SVHC) for Authorisation



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Regulation (EC) No 1005/2009 on substances that : Not applicable

deplete the ozone layer

UK REACH List of substances subject to authorisation : N

(Annex XIV)

: Not applicable

Not applicable

Control of Major Accident Hazards Regulations

2015 (COMAH)

Not applicable

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : Not in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

SECTION 16: Other information

Full text of H-Statements

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.

H361d : Suspected of damaging the unborn child.
H411 : Toxic to aquatic life with long lasting effects.

H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam.Serious eye damageRepr.Reproductive toxicitySkin Sens.Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative



according to Regulation (EC) No. 1907/2006 NAPA® NT105BK1000L XHPD 10W40 SS Synthetic Motor Oil

Version: 2.0 Revision Date: 06.04.2023 Print Date: 16/10/2023

Further information

Internal information: 000000278139

Classification of the mixture: Classification procedure:

Skin Sens. 1 H317 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN