



# TECHNICAL DATA SHEET

## XHPD 10W-40 SS

Product Type            10W-40 SEMI-SYNTHETIC MOTOR OIL  
Product Code            NT105

### Description

A high performance heavy-duty semi-synthetic engine oil formulated to provide long drain oil refreshment and to meet the severe lubrication requirements demanded by many commercial vehicle manufacturers.

### Benefits

- For use over extended drain intervals
- High fuel efficiency and savings
- Reduced oil consumption and emissions
- Lower maintenance costs
- Outstanding engine cleanliness and reduced engine deposits
- Excellent high and low temperature stability

### Specifications

Always check the owner's manual for the correct oil specification to use.

- ACEA E4,E7
- MAN M3277
- MACK EO-N
- MERCEDES-BENZ MB-228.5
- MTU TYPE 3
- RENAULT RVI RLD-2
- VOLVO VDS-3





# TECHNICAL DATA SHEET

## XHPD 10W-40 SS

Product Type 10W-40 SEMI-SYNTHETIC MOTOR OIL  
Product Code NT105

### Typical Properties

SAE Viscosity Grade	SAE J300	-	10W-40
Viscosity @ 100°C	ASTM D-445	mm <sup>2</sup> /s	14,6
Viscosity @ 40°C	ASTM D-445	mm <sup>2</sup> /s	100
Viscosity Index	ASTM D-2270	-	151,0
Viscosity @-20°C	ASTM D-5293	mPa.s	<7000
Total Base Number	ASTM D-2896	mg/KOH/g	13
Pour Point	ASTM D-5949	°C	-39
Specific Gravity @15.6°C	ASTM D-4052	-	1
Flash Point (COC)	ASTM D-92	°C	241

### Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

### Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



**NAPA EU**  
20 Avenue André Malrause  
92300 Lavallois-Perret  
FRANCE

**NAPA UK**  
2 Eskan Court, Campbell Park  
Milton Keynes. MK9 4AN  
UNITED KINGDOM

**NAPA DE**  
Albersloher Weg 275  
48155 Münster  
DEUTSCHLAND

[napaautoparts.eu](http://napaautoparts.eu)

**NAPA Oil Technical Support:** [oilsupport@napaautoparts.eu](mailto:oilsupport@napaautoparts.eu)