



TECHNICAL DATA SHEET

SHPD E7 15W-40

Product Type	15W-40 MINERAL MOTOR OIL
Product Code	NT106

Description

Heavy-Duty engine oil formulated to provide long drain oil refreshment and to meet the severe lubrication requirements demanded by many commercial vehicle manufacturers.

Benefits

- Volvo OEM Compliant
- Mack OEM Compliant
- Renault OEM Compliant
- Cummins OEM Compliant
- Offers improved wear protection and soot handling properties
- Meets a very broad range of OEM specifications
- Ideal choice for mixed fleet long haul vehicles
- Long oil drain properties

Specifications

Always check the owner's manual for the correct oil specification to use.

- ACEA E7
- API CI-4
- ALLISON C4
- CATERPILLAR ECF-2, ECF-1A
- CUMMINS CES 20076, CES 20077, CES 20078
- DETROIT DIESEL DDC 93K215
- DEUTZ DQC III-18
- GLOBAL DHD-1
- MACK EO-N, EO-M PLUS
- MAN M3275
- MERCEDES-BENZ MB-228.3
- MTU TYPE 2
- RENAULT RVI RLD-2
- VOLVO VDS-3





TECHNICAL DATA SHEET

SHPD E7 15W-40

Product Type 15W-40 MINERAL MOTOR OIL
Product Code NT106

Typical Properties

SAE Viscosity Grade	SAE J300	-	15W-40
Viscosity @ 100°C	ASTM D-445	mm ² /s	14, 7
Viscosity @ 40°C	ASTM D-445	mm ² /s	109
Viscosity Index	ASTM D-2270	-	140,0
Viscosity @ -20°C	ASTM D-5293	mPa.s	5437,0
Total Base Number	ASTM D-2896	mg/KOH/g	10
Pour Point	ASTM D-5949	°C	≤ -33
Specific Gravity @ 15.6°C	ASTM D-4052	-	1
Flash Point (COC)	ASTM D-92	°C	239

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Esplanade Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaaautoparts.eu