

according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : NAPA® NT117199L HDP LONG DRAIN 10W40 FS

Motor Oil

Product code 902346

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline

> Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

Telephone +31 (0)78 654 3500 (in the Netherlands), or contact your local

CSR contact person

E-mail address of person responsible for the SDS

SDS@valvoline.com

#### 1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.

# Valvoline,

# **SAFETY DATA SHEET**

according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

#### **Additional Labelling**

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol.

May produce an allergic reaction.

# 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

# Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Index-No.		(/0 !!/!)
	Registration number		
DISTILLATES (PETROLEUM),	64742-65-0	Asp. Tox. 1; H304	>= 1 - < 2.5
SOLVENT-DEWAXED HEAVY	265-169-7		
PARAFFINIC	649-474-00-6		
	01-2119471299-27-		
	XXXX		
Distillates (petroleum), solvent-	64742-56-9	Asp. Tox. 1; H304	>= 1 - < 2.5
dewaxed light paraffinic	265-159-2		
	649-469-00-9		
CATALYTIC DE WAXED HEAVY	64742-70-7	Asp. Tox. 1; H304	>= 1 - < 2.5
PARAFFINIC OIL (PETROLEUM)	265-174-4		
	649-477-00-2		
Distillates (Petroleum), Hydrotreated	64742-54-7	Asp. Tox. 1; H304	>= 1 - < 2.5
Heavy Paraffinic	265-157-1		
	649-467-00-8		
	01-2119484627-25-		
	XXXX		
ZINC BIS[O-(6-	93819-94-4	Skin Irrit. 2; H315	>= 1 - < 2.5
METHYLHELPTYL)]BIS[O-SEC-	298-577-9	Eye Dam. 1; H318	



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

BUTYL)]BIS(DITHIOPHOSPATE)		Aquatic Chronic 2;	
C14-16-18 Alkyl phenol	Not Assigned	Skin Sens. 1B;	>= 0.5 - < 1
C14-10-10 Aikyi pilelioi	Not Assigned	H317	/= 0.5 - < 1
	01-2119498288-19-	STOT RE 2; H373	
	xxxx	(Liver)	

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

# 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

# 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Revision Date: 31.01.2023 Print Date: 16/10/2023 Version: 5.0

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion

products

: carbon dioxide and carbon monoxide

5.3 Advice for firefighters

for firefighters

Special protective equipment : Wear self-contained breathing apparatus for firefighting if

necessary.

Further information Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

#### **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

# **Valvoline**...

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Advice on safe handling Avoid contact with skin and eves.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

When using do not eat or drink. When using do not smoke. Hygiene measures

Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply

with the technological safety standards.

Further information on

storage stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) No data available

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

# **Derived No Effect Level (DNEL):**

Substance name	End Use	Exposure routes	Potential health effects	Value
ZINC BIS[O-(6- METHYLHELPTYL)]B IS[O-SEC- BUTYL)]BIS(DITHIOP HOSPATE)	Workers	Inhalation	Long-term systemic effects	8.31 mg/m3
	Remarks:RD TOX - Repeated dose toxicity			
	Workers	Dermal	Long-term systemic effects	0.58 mg/kg
	Remarks:RD TOX - Repeated dose toxicity			
	Consumer use	Inhalation	Long-term systemic effects	2.11 mg/m3



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Remarks:RD TOX - Repeated dose toxicity			
Consumer use	Dermal	Long-term systemic effects	0.29 mg/kg
Remarks:RD TOX - Repeated dose toxicity			
Consumer use	Oral	Long-term systemic effects	0.24 mg/kg
Remarks:RD TOX - Repeated dose toxicity			

#### 8.2 Exposure controls

# Personal protective equipment

Eye/face protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Hand protection

Material : neoprene, nitrile rubber

Break through time : >= 240 minGlove thickness : >= 0.35 mm

Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the

protective glove.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally

required.



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Revision Date: 31.01.2023 Print Date: 16/10/2023 Version: 5.0

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

liquid **Appearance** 

Colour dark brown

Odour oily

Odour Threshold No data available

pН Not applicable

Melting point/freezing point < -33.00 °C

Boiling point/boiling range > 225.00 °C

218 °C Flash point

Method: Pensky-Martens closed cup

Not applicable Evaporation rate

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower : No data available

flammability limit

Vapour pressure 0.1333333 hPa (20 °C)

Calculated Vapor Pressure

Relative vapour density No data available

Relative density No data available

Density 0.866 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

Not applicable



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 90 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

No data available

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

# 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

# 10.6 Hazardous decomposition products

No hazardous decomposition products are known.



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

# **Acute toxicity**

Not classified based on available information.

#### **Components:**

#### **DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

#### Distillates (petroleum), solvent-dewaxed light paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

# **CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute oral

toxicity

Remarks: The toxicological data has been taken from

products of similar composition.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: The toxicological data has been taken from

products of similar composition.

# Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

# ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

# Valvoline...

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Acute oral toxicity : LD50 (Rat): 2,600 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

C14-16-18 Alkyl phenol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute oral

toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Remarks : May cause skin irritation and/or dermatitis.

Components:

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:** 

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Distillates (petroleum), solvent-dewaxed light paraffinic:

Species : Rabbit

Result : Slight, transient irritation

**CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):** 

Result : Slight, transient irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Species : Guinea pig



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Method : OECD Test Guideline 404

Result : Irritating to skin.

Remarks : The toxicological data has been taken from products of similar

composition.

C14-16-18 Alkyl phenol:

Method : OECD Test Guideline 431

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Assessment : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Components:

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:** 

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Distillates (petroleum), solvent-dewaxed light paraffinic:

Species : Rabbit

Result : Slight, transient irritation

**CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):** 

Result : Slight, transient irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Assessment : No eye irritation
Result : No eye irritation

ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Species : Rabbit
Result : Corrosive

Remarks : The toxicological data has been taken from products of similar

composition.

C14-16-18 Alkyl phenol:

# Valvoline...

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Species : Rabbit

Result : Slight, transient irritation

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

**Product:** 

Assessment : Does not cause skin sensitisation.

Remarks : Based on similar product.

# **Components:**

# Distillates (petroleum), solvent-dewaxed light paraffinic:

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

# C14-16-18 Alkyl phenol:

Test Type : Local lymph node assay

Species : Mouse

Assessment : The product is a skin sensitiser, sub-category 1B.

Method : OECD Test Guideline 429

#### Germ cell mutagenicity

Not classified based on available information.

#### Components:

# ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Remarks: The toxicological data has been taken from

products of similar composition.

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse

Method: OECD Test Guideline 474



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Result: negative

Remarks: The toxicological data has been taken from

products of similar composition.

C14-16-18 Alkyl phenol:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

**Components:** 

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:** 

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (petroleum), solvent-dewaxed light paraffinic:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):** 

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Components:** 

C14-16-18 Alkyl phenol:

Target Organs : Liver



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

#### **Aspiration toxicity**

Not classified based on available information.

#### **Components:**

# **DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

May be fatal if swallowed and enters airways.

# Distillates (petroleum), solvent-dewaxed light paraffinic:

May be fatal if swallowed and enters airways.

# **CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):**

May be fatal if swallowed and enters airways.

# Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

### **Further information**

**Product:** 

Remarks : No data available

# **SECTION 12: Ecological information**

# 12.1 Toxicity

# **Product:**

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity: Not classified based on available information.

# **Components:**

# **DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

# **Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

# Valvoline,

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Chronic aquatic toxicity : Not classified based on available information.

Distillates (petroleum), solvent-dewaxed light paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l aquatic invertebrates Exposure time: 48 h

Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae/aquatic : NOEL (Pseudokirchneriella subcapitata (green algae)): >=

plants 100 mg/l

End point: Growth inhibition

Exposure time: 72 h
Test Type: static test
Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to daphnia and other : NOEL: 10 mg/l

aquatic invertebrates

(Chronic toxicity)

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 211

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

# Valvoline...

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Revision Date: 31.01.2023 Print Date: 16/10/2023 Version: 5.0

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

NOEC: 10 mg/l Species: Fish

Toxicity to daphnia and other : NOEC: 10 mg/l

aquatic invertebrates (Chronic toxicity)

Species: Aquatic invertebrates

# **Ecotoxicology Assessment**

Acute aquatic toxicity Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

# ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l

> Exposure time: 96 h Test Type: semi-static test

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 5.4 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

: EC50 (Selenastrum capricornutum (green algae)): 2.1 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

# **Ecotoxicology Assessment**

: Acute aquatic toxicity Category 2; Toxic to aquatic life. Acute aquatic toxicity

Chronic aquatic toxicity Chronic aquatic toxicity Category 2; Toxic to aquatic life with

long lasting effects.

#### C14-16-18 Alkyl phenol:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l

> Exposure time: 96 h Test Type: static test Test substance: WAF



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h
Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l

End point: Growth inhibition

Exposure time: 72 h
Test Type: static test
Test substance: WAF

# **Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

# 12.2 Persistence and degradability

#### Components:

#### ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 1.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

# C14-16-18 Alkyl phenol:

Biodegradability : Result: Readily biodegradable.

Remarks: Expert judgement

#### 12.3 Bioaccumulative potential

#### **Components:**

# ZINC BIS[O-(6-METHYLHELPTYL)]BIS[O-SEC-BUTYL)]BIS(DITHIOPHOSPATE):

Partition coefficient: n-

octanol/water

: log Pow: 0.59 - 1.2 (23 °C)

#### C14-16-18 Alkyl phenol:

Partition coefficient: n-

octanol/water

:  $\log Pow: > 7.2$ 

# 12.4 Mobility in soil

No data available

17 / 22



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

#### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Other adverse effects

**Product:** 

Endocrine disrupting

potential

: The substance/mixture does not contain components considered to have endocrine disrupting properties according

to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

No data available

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

# **SECTION 14: Transport information**

# 14.1 UN number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

# 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA\_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA\_P (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

# 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

# **SECTION 15: Regulatory information**

# **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Not applicable

UK REACH Candidate list of substances of very high : Not applicable

concern (SVHC) for Authorisation



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Not applicable

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

The Persistent Organic Pollutants Regulations (retained

Regulation (EU) 2019/1021 as amended for Great

Britain)

Regulation (EC) No 1005/2009 on substances that : Not applicable

deplete the ozone layer

UK REACH List of substances subject to authorisation : Not applicable

(Annex XIV)

Control of Major Accident Hazards Regulations Not applicable

2015 (COMAH)

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

**INFINEUM D3314** 

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

# 15.2 Chemical safety assessment

No data available

#### **Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

# Valvoline<sub>TM</sub>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

# **SECTION 16: Other information**

#### **Full text of H-Statements**

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eve damage.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H411 : Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC -International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Cooperation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT -Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan



according to Regulation (EC) No. 1907/2006 NAPA® NT117199L HDP LONG DRAIN 10W40 FS Motor Oil

Version: 5.0 Revision Date: 31.01.2023 Print Date: 16/10/2023

Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Internal information: R0517074

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN