



TECHNICAL DATA SHEET

HDP LONG DRAIN 10W-40 FS

Product Type 10W-40 SYNTHETIC MOTOR OIL
Product Code NT117

Description

A high performance heavy-duty synthetic engine oil formulated to provide long drain oil refreshment and to meet the severe lubrication requirements demanded by many commercial vehicle manufacturers.

Benefits

- Scania OEM Compliant
- Volvo OEM Compliant
- Renault OEM Compliant
- Mack OEM Compliant
- Extended drain intervals

Specifications

Always check the owner's manual for the correct oil specification to use.

- ACEA E4, E7
- API CF
- DAF EXTENDED DRAIN
- MACK EO-N
- MAN M3277
- MERCEDES-BENZ MB-228.5
- RENAULT RLD-2
- SCANIA LDF-3, LDF-2
- VOLVO VDS-3





TECHNICAL DATA SHEET

HDP LONG DRAIN 10W-40 FS

Product Type 10W-40 SYNTHETIC MOTOR OIL
Product Code NT117

Typical Properties

SAE Viscosity Grade	SAE J300	-	10W-40
Viscosity @ 100°C	ASTM D-445	mm ² /s	13,5
Viscosity @ 40°C	ASTM D-445	mm ² /s	89
Viscosity Index	ASTM D-2270	-	152,0
Viscosity @-25°C	ASTM D-5293	mPa.s	<7000
Total Base Number	ASTM D-2896	mg/KOH/g	16
Pour Point	ASTM D-5949	°C	-39
Specific Gravity @15.6°C	ASTM D-4052	-	1
Flash Point (COC)	ASTM D-92	°C	220

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Esplanade Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu