



# TECHNICAL DATA SHEET

## EURO FE 5W-30 LS

Product Type            5W-30 SYNTHETIC LOW SAPS MOTOR OIL  
Product Code            NT130

### Description

A high performance heavy-duty synthetic low SAPS engine oil engineered to offer exceptional fuel saving benefits.

### Benefits

- Exceptional fuel saving benefits
- Compatible with after-treatment devices
- Low oil consumption
- Outstanding anti-wear protection
- Wide range of applications
- Excellent cold starting properties

### Specifications

Always check the owner's manual for the correct oil specification to use.

- ACEA E6, E9, E7
- API CK-4, CJ-4
- CATERPILLAR ECF-3
- CUMMINS CES 20086
- DEUTZ DQC IV-18 LA
- JASO DH-2
- MACK EO-O PP, EO-N PP, EO-M PLUS
- MAN M3677, M3477
- MERCEDES-BENZ MB-228.51, MB-228.31
- MTU TYPE 3.1
- RENAULT TRUCKS RLD-3, RLD-2
- VOLVO VDS-4, VDS-3





# TECHNICAL DATA SHEET

## EURO FE 5W-30 LS

Product Type 5W-30 SYNTHETIC LOW SAPS MOTOR OIL  
Product Code NT130

### Typical Properties

SAE Viscosity Grade	SAE J300	-	5W-30
Viscosity @ 100°C	ASTM D-445	mm <sup>2</sup> /s	11,7
Viscosity @ 40°C	ASTM D-445	mm <sup>2</sup> /s	71
Viscosity Index	ASTM D-2270	-	161,0
Viscosity @-30°C	ASTM D-5293	mPa.s	<6600
Total Base Number	ASTM D-2896	mg/KOH/g	10
Pour Point	ASTM D-5949	°C	-42
Specific Gravity @15.6°C	ASTM D-4052	-	1
Flash Point (COC)	ASTM D-92	°C	234

### Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

### Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



**NAPA EU**  
20 Avenue André Malrause  
92300 Lavallois-Perret  
FRANCE

**NAPA UK**  
2 Eskan Court, Campbell Park  
Milton Keynes. MK9 4AN  
UNITED KINGDOM

**NAPA DE**  
Albersloher Weg 275  
48155 Münster  
DEUTSCHLAND

[napaautoparts.eu](http://napaautoparts.eu)

**NAPA Oil Technical Support:** [oilsupport@napaautoparts.eu](mailto:oilsupport@napaautoparts.eu)