



TECHNICAL DATA SHEET

75W-80 EPZ FS

Product Type	75W-80 SYNTHETIC GEAR OIL
Product Code	NT309

Description

Premium gear oil for heavy-duty vehicles formulated to provide maximum protection and lubrication of the gearboxes and transaxles over a wide temperature range, where the manufacturer specifies GL-4 oil.

Benefits

- Long service life
- Excellent oxidative and thermal stability
- Outstanding low and high temperature performance
- Fuel saving benefits
- Excellent gear and bearing pitting resistance
- High level of wear protection
- Compatible with a variety of synchroniser materials

Specifications

Always check the owner's manual for the correct oil specification to use.

- API GL-4
- DAF
- MAN 341 Type Z-4
- MAN 341 Type E-3
- Volvo 97305, 97307
- ZF TE-ML 01L, 02L, 08, 13, 16K
- Military MIL-L-2105
- Eaton Europe 300,000 km or 3 years



TECHNICAL DATA SHEET

75W-80 EPZ FS

Product Type 75W-80 SYNTHETIC GEAR OIL
Product Code NT309

Typical Properties

SAE Viscosity Grade	SAE J306	-	75W-80
Viscosity @ 100°C	ASTM D-445	mm ² /s	9,7
Viscosity @ 100°C; After shearing	ASTM D-6278	mm ² /s	8,9
Viscosity, @ 40°C	ASTM D-445	mm ² /s	56,4
Viscosity Index	ASTM D-2270	-	157
Viscosity @ -40°C	ASTM D-5294	mPa.s	115031
Pour Point	ASTM D-5950	°C	-39
Specific Gravity	ASTM D-4052	-	0,859
Flash Point	ASTM D-92	°C	222

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.



NAPA EU
20 Avenue André Malrause
92300 Lavallois-Perret
FRANCE

NAPA UK
2 Esplanade Court, Campbell Park
Milton Keynes. MK9 4AN
UNITED KINGDOM

NAPA DE
Albersloher Weg 275
48155 Münster
DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu