

TECHNICAL DATA SHEET

AUTO-TRANS D III

Product TypeSEMI-SYNTHETIC ATFProduct CodeN306

Description

Auto-Trans D III is a semi synthetic multi-purpose automatic transmission fluid for commercial and automotive vehicles.

Benefits

- Primarily designed for GM DEXRON III application
- Long oil life
- Improves clutch durability
- Can be used as a power steering fluid
- Excellent protection against wear
- Low foaming tendencies
- Compatible with all elastomers and other sealing materials
- High thermal stability
- Backwards compatible to DEXRON IID applications

Specifications

Always check the owner's manual for the correct oil specification to use.

- GM Dexron IIIH, IIIG, IID, TASA
- Allison C4
- Allison TES-389
- Mercedes-Benz MB-236.10, 9, 8, 7, 6, 5, MB-236.1
- Caterpillar TO-2
- MAN 339F, 339 V2 &Z1
- Voith 55.6335.xx
- Volvo 97341, 97340
- ZF TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A, 16N, 17C



TECHNICAL DATA SHEET

AUTO-TRANS D III

Product TypeSEMI-SYNTHETIC ATFProduct CodeN306

Typical Properties

Test	Method	Unit	Value
Color	Visual	-	Red
Viscosity @ 100ºC	ASTM D-445	mm²/s	5,8
Viscosity @ 40°C	ASTM D-445	mm²/s	27,6
Viscosity Index	ASTM D-2270	-	160
Viscosity @ -40°C	ASTM D-5294	mPa.s	9773,0
Pour Point	ASTM D-5950	⁰ C	-54
Specific gravity	ASTM D-4052	-	0,843
Flash Point	ASTM D-92	⁰ C	212

Health and Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

A safety data sheet is available on request.

Disposal

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

DEVELOPED BY VALVOLINE™



NAPA EU 155-159 Avenue Anatole 92300 Lavallois-Perret FRANCE NAPA UK 2 Eskan Court, Campbell Park Milton Keynes. MK9 4AN UNITED KINGDOM NAPA DE Albersloher Weg 275 48155 Münster DEUTSCHLAND

napaautoparts.eu

NAPA Oil Technical Support: oilsupport@napaautoparts.eu