




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve IUU

Charger voltage at 68°F (20°C) 14.4V to 14.8V

Self-discharge per month at 68°F (20°C) 1.25%

Self-discharge per month at 104°F (40°C) 5%

80% depth of discharge cycles 400

PDF Generated at https://eu.odysseybattery.com 12/19/2022 12:53:28

Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet ODS-AGM14

Battery Type

- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

| Voltage | 12V |
|--|---------------|
| Pulse (5 second) Hot Cranking Amps (PHCA) | 565A |
| Cold Cranking Amps (CCA) | 220A |
| HCA | 320A |
| MCA | 300A |
| 20Hr Nominal Capacity (Ah) | 14Ah |
| Reserve Capacity Minutes | 18 mins |
| Terminal | M6 Receptacle |
| Torque Spec in-lbs (Nm max) | 50 (5.6) |
| | |

Dimensions and Weight

| Length | 5.9 in / 150 mm |
|-----------------------------|-----------------|
| Width | 3.4 in / 86 mm |
| Height (terminals included) | 5.7 in / 145 mm |
| Height (container) | 5.7 in / 145 mm |
| Weight | 10 lbs / 4.5 kg |

Temperature

Operating temperature range $-40^{\circ}\text{F}/-40^{\circ}\text{C}$ to $113^{\circ}\text{F}/+45^{\circ}\text{C}$ Optimum storage temperature $68^{\circ}\text{F}/+20^{\circ}\text{C}$

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800 Want more info? Scan code to access the ODYSSEY® Battery Literature Library

