

ODS-AGM16CL (PC625)

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage			12V
Capacity (20-hour rate)			18Ah
Capacity (10-hour rate)			17Ah
Cold Cranking Amps (CCA,	SAE J537)		220A
PHCA - 5-second pulse curr	ent		540A
HCA			400A
MCA			330A
Reserve capacity			26 mins
Short circuit current (using I	EC method)		1800A
Internal resistance at 20°C	(using IEC method)	$7~\text{m}\Omega$

Dimensions & Weight

Length	170 mm
Width	99 mm
Height (to top of terminals)	178 mm
Height Container	175 mm
Weight	6 kg

Temperature

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.


Charging & self-discharge

Type of charging curve	100
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%


Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

Terminal Position Terminal Type M6 FEMALE THREAD



ODS-AGM16CL RIGHT POSITIVE FRONT FEMALE CONNECTION



PDF Generated at https://eu.odysseybattery.com 22/12/2021 10:07:57 Information correct at time of exporting PDF. Please check website for updates.

