

# ODS-AGM28LMJA (PC925LMJT)

Technical Data Sheet

#### **Battery Type**

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

#### **Power & Performance**

Voltage	12V
Capacity (20-hour rate)	28Ah
Capacity (10-hour rate)	27Ah
Cold Cranking Amps (CCA, SAE J537)	330A
PHCA - 5-second pulse current	900A
HCA	610A
MCA	480A
Reserve capacity	48 mins
Short circuit current (using IEC method)	2400A
Internal resistance at 20°C (using IEC method)	5 mΩ

#### **Dimensions & Weight**

Length	168 mm
Width	180 mm
Height (to top of terminals)	147 mm
Height Container	127 mm
Weight	11.5 kg

## Temperature

Operating Temperature Range	-40°C to +80°C
Optimum Storage Temperature	+20°C

## Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

# Charging & self-discharge

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

## Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).


PDF Generated at https://eu.odysseybattery.com 22/12/2021 10:11:21 Information correct at time of exporting PDF. Please check website for updates.




Solutions

EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-610-208-1991 / +1-800-538-3627


EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug, Switzerland EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780



#### **Terminal Position**



# **Terminal Type**





©2021 EnerSys. All rights reserved. Trademarks and logos are the property of EnerSys and its affiliates. Subject to revisions without prior notice. E.&O.E.