

MANUAL MOTORIZED WHEEL BALANCER LED SCREEN

Reference : EQ 0600BL



Item name	MANUAL MOTORIZED WHEEL BALANCER LED SCREEN
EAN code	3701555310039
Intro	Wheel balancer designed for dynamic or static balancing of VL-VUL-4X4 wheels. The advantage of this machine is its modern, ergonomic design. The intuitive calibration system makes work easier and improves balancing accuracy. The machine is equipped with an LED display. Manual parameter entry.
Text	Features : - automatic cycle - multifunction keys - static and dynamic program (2 planes) in a single run - 6 Alu programs (+ Optimization, Static, Motorcycle, Hidden weight) - self-calibration - self-diagnosis: fault code - simultaneous display of weights and mass positions - measurement accuracy: $\pm 1g$ - display accuracy: 5g
Specifications	Specifications: - power supply: 230V-50Hz - motor power: 180W - dimensions open housing: 880x980x1420mm - LED display - maximum wheel weight: 65kg

- minimum rim diameter: 10 inches
- max rim diameter: 24 inches
- rim width: from 1 to 20 inches
- manual measurement of 3 parameters: offset-diameter-width
- safety housing
- rotation speed: 200 rpm
- compartmentalized tray for cones and weights
- 4 storage racks
- noise level <70dB
- weight: 87kg

Contents	Livrée avec : - EQ6521BL : 4 cônes de 42 à 137mm Ø40mm - Clé hexagonale 12mm - SA8305 : compas largeur de jante - masse étalon 100g pour calibration - OC8034 : pince à masses multifonction - EQ6404BL : écrou rapide Ø40x4mm avec bol/joint/bague de compression
Advice	Installation et mise en service, nous consulter. Toutes nos équilibreuse sont livrées déjà étalonnées en usine.
Warranty period	2 years
Power	80W
Tension	230V
More	Products with electrical plug
Product weight	87.00 kg
Tariff code	Tariff Equipment (TE)
Product range	B-Line
Warranty Procedure	INTERVENTION



CLAS EQUIPEMENTS
 83, chemin de la CROUZA
 73800 CHIGNIN
 France

Tel : +33 (0) 4 79 72 62 22
 Fax :

Monday to Friday - From 8 to
 12h30 and from 14h to 17h30
 (16h30 on Friday)