

## 2 COLUMNS POST LIFT 400V 4T HIGH PASSAGE 5070mm 2.6kw

Reference : PE 2009T



|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Item name</b>         | 2 COLUMNS POST LIFT 400V 4T HIGH PASSAGE 5070mm 2.6kw                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>EAN code</b>          | 3701555306995                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Text</b>              | <p>Electro-hydraulic post lift.</p> <p>Hoses and cables pass through the top for optimum working comfort, allowing free access under the vehicle for equipment (cylinders, oil recovery system, etc.), making it easier to clean the workshop.</p> <p>Multiple lifting capacities thanks to the telescopic arms in asymmetrical version (front short 3 stages from 640 to 1200mm, rear long 2 stages from 775 to 1550mm ) allowing a precise lifting of low or utility vehicles.</p>                                                                                                              |
| <b>Product highlight</b> | Height adjustable to the millimeter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Specifications</b>    | <p>Specifications:</p> <ul style="list-style-type: none"><li>- lifting height: 65-1980mm</li><li>- lifting time: +/- 40s</li><li>- lowering time: +/- 40s</li><li>- drive power: 2.6 kw</li><li>- electrical voltage of the drive: (3~) 400/50 V/Hz</li><li>- strength/quality of concrete: 200mm-C20/25</li><li>- adjustable pads on 55mm stroke screw (+ 70mm and 160mm extension)</li><li>- electromagnetic unlocking of the safety notches</li><li>- overload safety and hose rupture</li><li>- bevelled columns for large door openings</li><li>- hydraulic synchronization system</li></ul> |

- made in Europe
- Epoxy painting

## Options

Options :  
- PE0007: Mercedes/Iveco 105-135mm extension sets

## Advice

Installation et mise en service, nous consulter.  
Dans le cadre de la garantie, l'installation et la mise en service doivent être effectuées par un professionnel.  
Frais de transport non inclus.

## Warranty period

2 years

## Power

2600W

## Tension

400V

## Product weight

720.00 kg

## Max. height

4,470.00 mm

## Maximum load (T)

4.00 T

## Tariff code

Tariff Equipment (TE)

## Composition of nomenclature

1 x PE 2009T-1 - 2 COLUMNS POST LIFT 400V 4T HIGH PASSAGE 5070mm 2.6kw  
PACK. 1/1



CLAS EQUIPEMENTS  
83, chemin de la CROUZA  
73800 CHIGNIN  
France

Tel : +33 (0) 4 79 72 62 22  
Fax :

Monday to Friday - From 8 to  
12h30 and from 14h to 17h30  
(16h30 on Friday)