

DESCRIPTION



Supersint FE 0W40

High-Performance engine oil



1. APPLICATION

Supersint FE 0W40 is a fuel-economy high-performance motor oil for petrol and diesel car engines with/without extended service intervals.
This oil is characterized by excellent cold start properties and the minimization of friction and wear.

2. YOUR BENEFIT

- Significant fuel savings.
- Excellent cold start properties.
- Excellent protection against corrosion.
- Excellent engine cleanliness because of the modified combination of additives.
- Suitable for extended oil change intervals according to the manufacturer's specifications.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA A3/B4
- API SN, API CF
- BMW Longlife-01 | Fiat 9.55535-M2/Z2
- Ford WSS-M2C937-A | PSA B71 2296
- Mercedes Benz 229.5/226.5/229.3 | Porsche A40
- Renault RN0700/0710
- VW 502 00/505 00



DESCRIPTION



Quality engineered in Germany

Supersint FE 0W40

High-Performance engine oil



4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	846	Kg/cm ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	83,7	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	14,0	mm ² /s	ASTM D7279
Viscosity Index	173		ASTM D2270
Flashpoint	224	°C	DIN ISO 2592
Pourpoint	-45	°C	ASTM D7346
Total Base Number (TBN)	10,8	mg KOH/g	ASTM D2896

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0120000	20 Liter	0120030
205 Liter	0120010	4 x 5 Liter	0120050
60 Liter	0120020	12 x 1 Liter	0120075

