

DESCRIPTION



Supersint FS SAE 5W40

High-Performance engine oil



1. APPLICATION

Supersint FS 5W40 is a high performance, fuel efficient passenger car diesel and petrol engine oil with/without turbocharger. It is also suitable for extended drain intervals as required by car manufacturers. With its modern additive package, Supersint FS 5W40 is characterized by lasting engine cleanliness.

2. YOUR BENEFIT

- Extended oil change intervals possible according to the manufacturer's specifications.
- Significant fuel savings possible.
- Excellent engine cleanliness because of to the modified combination of additives.
- Exzellente Scherstabilität und sehr stabiles Viskositätsverhalten.
- Excellent protection against corrosion.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA A3/B4
- API SN, API CF
- BMW Longlife-01
- Fiat 9.55535-H2/M2/N2
- Mercedes Benz 229.3/226.5
- Opel GM-LL-B-025 | PSA B71 2296
- Porsche A40 | Renault RN0700/RN0710
- VW 502 00/505 00



DESCRIPTION



Quality engineered in Germany



Supersint FS SAE 5W40

High-Performance engine oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	853	Kg/m ³	DIN EN ISO 12185:1997-11
Kin. Viscosity at 40°C	92,1	mm ² /s	DIN 51659-2:2017-02
Kin. Viscosity at 100°C	15,2	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	175		DIN ISO 2909:2004-08
Pourpoint	-39	°C	ASTM D 7346:2015
Flashpoint	230	°C	DIN EN ISO 2592:2018-01
Total Base Number (TBN)	10,3	Mg KOH/g	ASTM D 2896:2015

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0121000	20 Liter	0121030
205 Liter	0121010	4 x 5 Liter	0121050
60 Liter	0121020	12 x 1 Liter	0121060

