

DESCRIPTION



Supersint FE 5W40

Fuel-efficient low-friction engine oil



1. APPLICATION

Supersint FE 5W40 is a fuel-economy engine oil for car petrol and diesel engines with/without turbo-charger and direct injection. It offers optimal protection against wear, even when the stop-start function is used frequently in city traffic and on long journeys under full or partial load. Extended oil changes are possible according to the manufacturer's instructions.

2. YOUR BENEFIT

- Excellent protection against wear, corrosion and foaming.
- Excellent shear stability prevents viscosity drop and oil film cracking.
- Due to the low flow pressure, quick oiling is guaranteed during a cold start.
- Suitable for extended oil change intervals according to the manufacturer's specifications.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA A3/B4
- API SN, API CF
- BMW Longlife-01 | Chrysler MS-10725/12991
- Fiat 9.55535-H2/M2/N2/Z2 | Mercedes Benz 229.5/229.3/229.6
- Opel GM-LL-B-025 | Porsche A 40
- PSA B71 2296 | Renault RN 0700/0710
- VW 502 00/505 00



DESCRIPTION



Quality engineered in Germany



Supersint FE 5W40

Fuel-efficient low-friction engine oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	850	Kg/cm ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	84,1	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	13,9	mm ² /s	ASTM D7279
Viscosity Index	171		ASTM D2270
Flashpoint	238	°C	DIN ISO 2592
Pourpoint	-42	°C	ASTM D7346
Total Base Number (TBN)	9,9	mg KOH/g	ASTM D2896

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0125000	20 Liter	0125030
205 Liter	0125010	4 x 5 Liter	0125050
60 Liter	0125020	12 x 1 Liter	0125075

