

# DESCRIPTION



## Superpower C-1 5W30

Premium HC-Synthetic Engine oil



### 1. APPLICATION

This High-Performance, low-friction engine oil is suitable for modern passenger cars/vans with and without extended maintenance intervals. Among other things, it was specially developed for Mazda vehicles with exhaust aftertreatment and turbocharging. Base oils of HC synthesis technology, additives with low sulphate ash, low phosphorus and sulfur content (low SAPS) and friction-reducing properties result in maximum fuel savings and a reduction in pollutant emissions. Superpower C-1 5W30 is recommended for petrol and diesel engines when ACEA C1 engine oils are specified. The low proportion of ash-forming Active ingredients reduce deposits in diesel particulate filters and increase the effectiveness and service life of three-way catalytic converters for petrol engines and other exhaust aftertreatment systems

### 2. YOUR BENEFIT

- Extended maintenance intervals possible.
- Viscosity stable and very resistant to aging.
- Fuel savings and reduction of pollutant emissions.
- Very good cold start properties, reduces possible deposits.

### 3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA C1, C2
- JASO DL-1; Mitsubishi
- Ford WWS-M2C934-B; Mazda
- Jaguar Land Rover STJR.03.5005



# DESCRIPTION



Quality engineered in Germany

## Superpower C-1 5W30

Premium HC-Synthetic Engine oil



### 4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	845	Kg/cm <sup>3</sup>	DIN EN ISO 12185
Kin. Viscosity at 40°C	55,00	mm <sup>2</sup> /s	ASTM D7279
Kin. Viscosity at 100°C	10,00	mm <sup>2</sup> /s	ASTM D7279
Viscosity Index	165		ASTM D2270
Flashpoint	>220	°C	DIN ISO 2592
Pourpoint	-39	°C	ASTM D7346
Total Base Number (TBN)	8,0	mg KOH/g	ASTM D2896

### 5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0128000	20 Liter	0128030
205 Liter	0128010	4 x 5 Liter	0128050
60 Liter	0128020	12 x 1 Liter	0128075

