

DESCRIPTION



Supersint LSP SAE 5W30

Premium HC-Synthetic Engine oil



1. APPLICATION

Fuel-saving motor oil, excellently suited for modern diesel and petrol engines in Cars, Vans, SUVs and transporters with/without turbochargers, even with extended oil change intervals. Carefully selected additives give this high-performance engine oil its excellent properties. Also suitable for pump-jet engines.

2. YOUR BENEFIT

- Very good cold start properties.
- Fuel savings in partial and full load operation.
- Extends the life of the exhaust aftertreatment systems.
- Prevents deposits in the engine and in the exhaust gas turbocharger.
- Outstanding shear stability, very good protection against wear and corrosion.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA C2, C3
- API SN Plus, API SN, API CF
- BMW Longlife-04
- Chrysler MS-11106 | GM dexos2™
- Fiat 9.55535-S3 | Ford M2C 917-A
- Mercedes Benz 229.52/229.51/229.31
- Opel OV0401547-D30/-G30; Renault RN0700/RN0710
- VW 502 00/505 00/505 01



DESCRIPTION



Quality engineered in Germany



Supersint LSP SAE 5W30

Premium HC-Synthetic Engine oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	851	Kg/cm ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	73,7	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	12,2	mm ² /s	ASTM D7279
Viscosity Index	163		ASTM D2270
Flashpoint	224	°C	DIN ISO 2592
Pourpoint	-36	°C	ASTM D7346
Total Base Number (TBN)	8,0	mg KOH/g	ASTM D2896

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0129500	20 Liter	0129530
205 Liter	0129510	4 x 5 Liter	0129550
60 Liter	0129520	12 x 1 Liter	0129570

