

DESCRIPTION

emka[®]

Quality engineered in Germany

Multi-Light 10W40

HC-Synthetic low running engine oil



1. APPLICATION

Multi-Light 10W40 is a modern, high-performance, low-friction engine oil for OTTO and diesel engines with/without turbocharging. It is characterized by excellent cold start properties and minimization of friction and wear. With Multi-Light, extended oil change intervals are also possible according to the manufacturer's instructions and it ensures safe operation under all operating conditions.

2. YOUR BENEFIT

- Excellent cold start properties.
- Very stable and excellent viscosity behavior and high shear stability.
- The low evaporation loss minimizes oil consumption.
- Very good detergent and dispersing properties.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA A3/B4
- API SN, API CF
- BMW Longlife-01
- Mercedes Benz 229.1/228.1
- Renault 0700/0710
- VW 501 01/505 00



DESCRIPTION



Quality engineered in Germany



Multi-Light 10W40

HC-Synthetic low running engine oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	860	Kg/m ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	101	mm ² /s	ASTM 7279
Kin. Viscosity at 100°C	15,1	mm ² /s	ASTM 7279
Viscosity Index	149		ASTM 2270
Flashpoint	>220	°C	DIN ISO 2592
Pourpoint	-33	°C	ASTM 7346

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0260000	20 Liter	0260030
205 Liter	0260010	4 x 5 Liter	0260050
60 Liter	0260020	12 x 1 Liter	0260075

