

DESCRIPTION

emka[®]

Quality engineered in Germany

Multigrade T 15W40

High Performance Engine oil



1. APPLICATION

Multigrade T 15W40 is a high-performance motor oil for use in mixed fleets in petrol and diesel engines with and without turbocharging. It is characterized by excellent cold start properties and minimizes wear and fuel consumption. Multigrade T 15W40 is ideal for year-round use and enables extended periods Oil change intervals according to manufacturer's instructions.

2. YOUR BENEFIT

- Outstanding cold start properties.
- Excellent resistance to aging.
- Reduction in fuel consumption.
- Very good protection against wear and corrosion.
- Reduced maintenance costs due to possible extended oil change intervals.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA A3/B4;
- API CF-4, API SN;
- MAN 3275-1/271;
- Mercedes Benz 228.1/229.1;
- MACK EO-L; Volvo VDS;
- VW 500 00/505 00/501 01;
- Allison C-4; MTU Type 2;



DESCRIPTION



Quality engineered in Germany



Multigrade T 15W40

High Performance Engine oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	865	Kg/m ³	DIN EN ISO 12185
Viscosity at 40°C	103,00	mm ² /s	DIN 51562
Viscosity at 100°C	14,50	mm ² /s	DIN 51562
Viscosity index	135		DIN ISO 2909
Flashpoint	>220	°C	DIN ISO 2592
Pourpoint	-33	°C	DIN ISO 3016
TBN (Total Base Number)	7,90	mgKOH/g	DIN ISO 3771

5. PACKAGING

INHALT	ART.NR.	INHALT	ART.NR.
Tankware	0340000	20 Liter	0340030
205 Liter	0340010	4 x 5 Liter	0340050
60 Liter	0340020	12 x 1 Liter	0340075

