

DESCRIPTION



Superpower C-2 5W30

High Performance low running Engine oil



1. APPLICATION

This high-performance, low-viscosity engine oil is suitable for diesel and petrol engines in modern passenger cars/vans and light commercial vehicles with and without extended service intervals. HC-Synthetic base oil and modern additive technology with low sulphate ash, low phosphorus and sulfur content (LowSAPS) and friction-reducing properties result in maximum fuel savings and a reduction in pollutant emissions. The exhaust gas turbocharger is kept clean over the long term, which means that the boost pressure remains at an optimal level over the long term. Superpower C-2 5W30 is recommended for diesel and petrol engines where Motor oils according to ACEA C2 are required. It increases the effectiveness and service life of the installed exhaust gas aftertreatment systems and the high level of economy remains due to optimization of fuel consumption even if the extended oil change intervals are used.

2. YOUR BENEFIT

- Reduction in fuel consumption.
- Excellent protection against wear, even under constant stress.
- Prevents deposits in the engine and exhaust gas turbocharger.
- Preserves and protects the exhaust aftertreatment systems.
- Excellent cold start behavior, safe and shear-stable lubricating film.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA C2, A5/B5
- API SN, API CF
- Fiat 9.55535-S1
- Iveco 18-1811 Class SC1
- Renault RN 0700 | PSA B71 2290
- Subaru | Suzuki | Toyota



DESCRIPTION



Quality engineered in Germany



Superpower C-2 5W30

High Performance low running Engine oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	851	Kg/cm ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	63,8	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	11,0	mm ² /s	ASTM D7279
Viscosity Index	165		ASTM D2270
Flashpoint	236	°C	DIN ISO 2592
Pourpoint	-39	°C	ASTM D7346
Total Base Number (TBN)	8,0	mg KOH/g	ASTM D2896

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0800000	20 Liter	0800030
205 Liter	0800010	4 x 5 Liter	0800050
60 Liter	0800020	12 x 1 Liter	0800075

