# DESCRIPTION





### Multi Superpower C-3 5W30

Premium HC-Synthetic smooth-running Engine oil

#### **1. APLLICATION**

Multi Superpower C-3 5W30 is a premium HC-Synthetic smooth-running engine oil for passenger cars, vans and SUVs from various premium manufacturers such as BMW, Mercedes Benz, Opel and the VW Group that are equipped with exhaust Aftertreatment Systems (exceptions are the in-line 5-cylinder and V10 TDI-VW engines built up to 2007, which are to be filled with an oil according to VW standard 506 01). The service life of the exhaust Aftertreatment Systems is extended due to the reduced formation of ash. Extended oil change intervals according to the manufacturer's instructions are possible.

#### **2. YOUR BENEFIT**

- Extremely stable and excellent viscosity behavior.
- Excellent cold start behavior, very shear stable lubricating film.
- Reduction of fuel consumption under all operating conditions.
- Reduces deposits in the engine and exhaust gas turbocharger to a minimum.
- Excellent protection against wear and corrosion, even under continuous stress.

#### **3. TECHNICAL SPECIFICATIONS**

#### Can be used with:

- ACEA C3
- API SP
- BMW Longlife-04
- GM dexos2<sup>™</sup>
- Mercedes Benz 229.52/229.51/229.31
- Opel/Vauxhall OV0401547-G30/-D30
- Porsche C30
- VW 504 00/507 00



EMKA Schmiertechnik GmbH Schmalbachstrasse 19 74626 Bretzfeld, Germany 
 Telefon
 +49 7946 94 470-0

 Telefax
 +49 7946 94 470-70

 E-Mail
 info@emka-oil.de

www.emka-oil.de

## DESCRIPTION





## Multi Superpower C-3 5W30

Premium HC-Synthetic smooth-running Engine oil

### 4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test	
Density at 15°C	848	Kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11	
Kin. Viscosity at 40°C	69,0	mm²/s	DIN 51659-2:2017-02	
Kin. Viscosity at 100°C	12,0	mm²/s	DIN 51659-2:2017-02	
Visosity Index	172		DIN ISO 2909:2004-08	
Pourpoint	-33	°C	ASTM D 7346:2015	
Total Base Number (TBN)	7,5	mgKoH/g	ASTM D 2896:2015	

### **5. PACKAGING**

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	808806	20 Liter	808830
205 Liter	808810	4 x 5 Liter	808850
60 Liter	808820	12 x 1 Liter	808875



EMKA Schmiertechnik GmbH Schmalbachstrasse 19 74626 Bretzfeld, Germany 
 Telefon
 +49 7946 94 470-0

 Telefax
 +49 7946 94 470-70

 E-Mail
 info@emka-oil.de

www.emka-oil.de