

DESCRIPTION

emka[®]

Quality engineered in Germany

Superpower C-4 5W30

Premium HC-Synthese Engine oil



1. APPLICATION

This high-performance, low-friction engine oil is suitable for diesel and petrol engines in modern cars/vans with and without extended maintenance intervals. HC synthetic base oils and modern additive technology with low sulphate ash, low phosphorus and sulfur content (LowSAPS) and friction-reducing properties result in maximum fuel savings and a reduction in pollutant emissions. The exhaust gas turbocharger is kept clean over the long term, which means that the boost pressure remains at an optimal level over the long term. Superpower C-4 5W30 has been specially developed for Renault diesel engines. It increases the effectiveness and service life of the built-in exhaust aftertreatment systems and the high level of economy through optimization of fuel consumption is maintained even when the extended oil change intervals are used.

2. YOUR BENEFIT

- Low exhaust back pressure.
- Reduction in fuel consumption.
- Extended service life of particle filters.
- Very good aging stability over the entire oil change interval.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA C4, C3;
- Fiat 9.55535-S4;
- Mercedes Benz 226.51/229.51/229.31;
- Nissan; Renault RN 0720; Suzuki;



DESCRIPTION



Quality engineered in Germany

Superpower 4-3 5W30

Premium HC-Synthese Engine oil



4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	845	Kg/m ³	D 4052
Kin. Viscosity at 40°C	70,4	mm ² /s	D 445
Kin. Viscosity at 100°C	12,1	mm ² /s	D 445
Viscosity Index	170		D 2270
Pourpoint	-36	°C	D 97
Flashpoint	>236	°C	D 92

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0809000	20 Liter	0809030
205 Liter	0809010	4 x 5 Liter	0809050
60 Liter	0809020	12 x 1 Liter	0809075

