

DESCRIPTION

emka[®]

Quality engineered in Germany

Supersint Light C-3 5W30

HC-Synthetic High Performance Engine oil



1. APPLICATION

Supersint Light C-3 SAE 5W30 is a specially developed low-friction motor oil based on HC-Synthetic base oils for petrol and diesel engines, which meets the current manufacturer specifications of the German automotive industry. It is based on a high-quality base oil with additives with a low ash content (Mid-SAPS), which are designed for use in modern passenger car petrol and diesel engines. It has an Outstanding shear stability and ensures compliance with the viscosity class over the entire change interval.

2. YOUR BENEFIT

- Excellent protection against corrosion.
- Excellent cold start properties and very quick oiling.
- Very low evaporation loss minimizes oil consumption.
- Excellent engine cleanliness because of a modern combination of additives.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA C3, C2;
- API SP, API CF;
- BMW Longlife-04;
- Mercedes Benz 229.51;
- VW 504 00/507 00;



DESCRIPTION



Quality engineered in Germany

Supersint Light C-3 5W30

HC-Synthetic High Performance Engine oil



4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	849	Kg/cm ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	73,3	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	12,2	mm ² /s	ASTM D7279
Viscosity Index	164		ASTM D2270
Flashpoint	242	°C	DIN ISO 2592
Pourpoint	-39	°C	ASTM D7346
Total Base Number (TBN)	6,6	mg KOH/g	ASTM D2896

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0809900	20 Liter	0809930
205 Liter	0809910	4 x 5 Liter	0809950
60 Liter	0809920	12 x 1 Liter	0809975

