

DESCRIPTION



Superpower C-2 0W20

Mid-SAPS low running Engine oil



1. APPLICATION

Superpower C-2 0W20 is a fuel-economy, high-performance car engine oil for petrol and diesel engines. It is characterized by excellent cold start properties and is especially recommended for car engines from General Motors and Opel according to GM dexos 1™ Gen. 2. Above all, it prevents premature fuel ignition (LSPI), which can lead to engine damage. It also enables extended oil change intervals according to manufacturer specifications.

2. YOUR BENEFIT

- Very high viscosity stability and aging resistance.
- Fuel economy and excellent cold start properties.
- Very good shear stability and high oxidation stability.
- Excellent protection against wear, corrosion and foaming.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- API SN Plus, API SN (RC)
- ILSAC GF-5
- Chrysler MS-6395
- GM dexos 1™ Gen. 2 / GM 6094M
- Fiat 9.55535-GSX/CR1
- Ford WWS-M2C947-A



DESCRIPTION



Quality engineered in Germany

Superpower C-2 0W20

Mid-SAPS low running Engine oil



4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	850	Kg/cm ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	45	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	8,5	mm ² /s	ASTM D7279
Viscosity Index	>165		ASTM D2270
Flashpoint	>220	°C	DIN ISO 2592
Pourpoint	-36	°C	ASTM D7346
Total Base Number (TBN)	8,4	mg KOH/g	ASTM D2896

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0851000	20 Liter	0851030
205 Liter	0851010	4 x 5 Liter	0851050
60 Liter	0851020	12 x 1 Liter	0851075

