

DESCRIPTION

emka[®]

Quality engineered in Germany

Multi-Light 10W30

High-Performance low running engine oil



1. APPLICATION

Multi-Light 10W40 is a modern, high-performance, low-friction engine oil for OTTO and diesel engines with/without turbocharging. It is characterized by excellent cold start properties and minimization of friction and wear. With Multi-Light, extended oil change intervals are also possible according to the manufacturer's instructions and it ensures safe operation under all operating conditions.

2. YOUR BENEFIT

- Excellent cold start properties.
- Very stable and excellent viscosity behavior and high shear stability.
- The low evaporation loss minimizes oil consumption.
- Very good detergent and dispersing properties.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- API SN, API CF; ILSAC GF-5;
- Chrysler MS-6395; Daewoo; Daihatsu;
- Fiat 9.55535-CR-1; GM 6094M; Honda; Hyundai;
- Isuzu; Kia; Mazda; Mitsubishi; Nissan;
- SsangYong; Subaru; Suzuki; Toyota;



DESCRIPTION



Quality engineered in Germany

Multi-Light 10W30

High-Performance low running engine oil



4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	863	Kg/m ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	81,0	mm ² /s	ASTM 7279
Kin. Viscosity at 100°C	12,2	mm ² /s	ASTM 7279
Viscosity Index	146		ASTM 2270
Pourpoint	-39	°C	ASTM 7346
TBN	10,0	mgKOH/g	ASTM D 2896:2015

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0263000	20 Liter	0263030
205 Liter	0263010	4 x 5 Liter	0263050
60 Liter	0263020	12 x 1 Liter	0263070

