

DESCRIPTION



Turbo Super SHPD 15W40

Super High-Performance Diesel engine oil



1. APPLICATION

Super High Performance Motoroil for use in Cars, Trucks and Working Mashines under severe conditions. Exceeds the performance requirements of modern Petrol- and Euro V-Diesel engines with and without turbocharging.

It has excellent cold starting properties, reduces wear and tear and fuel consumption.

Turbo Super SHPD 15W40 allows extended oil change intervals as specified by the manufacturer's instructions.

2. YOUR BENEFIT

- Designed for difficult operation conditions.
- Very good and fast oil circulation during cold start.
- Excellent aging resistance.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA A3/B4, E7;
- API CI-4, API SL;
- DAF; Daimler Truck DTFR 15B110(MB 228.3)/MB 229.1;
- Detroit Diesel DDC 93K215; MAN M3275-1; MACK EO-N;
- Iveco 18-1804 T2 E7; Renault VI RLD-2; Volvo VDS-3;
- Allison C-4/TES 439; Global DHD-1; Jaso DH-1;
- CATERPILLAR ECF-2/TO-2; Cummins CES 20078/77/76;
- Deutz DQC III-10; John Deere JDQ 78A; MTU Typ 2;



DESCRIPTION



Quality engineered in Germany

Turbo Super SHPD 15W40

Super High-Performance Diesel engine oil



4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	885	Kg/m ³	DIN EN ISO 12185
Viscosity at 40°C	118,0	mm ² /s	DIN 51562
Viscosity at 100°C	15,3	mm ² /s	DIN 51562
Viscosity index	136		DIN ISO 2909
Pourpoint	-36	°C	DIN ISO 3016
TBN (Total Base Number)	10,7	mgKOH/g	DIN ISO 3771

5. PACKAGING

INHALT	ART.NR.	INHALT	ART.NR.
Tankware	0320000	20 Liter	9621047
1000 Liter IBC	9621050	4 x 5 Liter	9621046
205 Liter	9621049	12 x 1 Liter	9621045
60 Liter	9621048		

