

DESCRIPTION



Turbo Super SHPD 20W50

Super High-Performance Diesel Motor oil



1. APPLICATION

Turbo Super SHPD 20W50 is a super high performance diesel engine oil for use in mixed Vehicle fleet, even under difficult operating conditions in trucks and work machines. It exceeds the performance requirements of modern Otto and Euro V diesel engines with and without turbocharging. It has excellent cold start properties, reduces wear and ensures a stable Lubricating film even at high temperatures.

2. YOUR BENEFIT

- Excellent resistance to aging.
- Very good cold start properties.
- Good shear stability and high oxidation resistance.
- Very stable and excellent viscosity-temperature behavior.
- High safety reserves, even under boundary lubrication conditions.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA A3/B4, E7;
- API CI-4, API SL, API CF;
- DAF; Daimler Truck DTFR 15B110 (MB 228.3)/MB 229.1
- Detroit Diesel DDC 93K215; MAN M3271-1; MACK EO-N
- Iveco 18-1804 T2 E7; Renault VI RLD-2; Volvo VDS-3
- Allison C-4/TES 439; Global DHD-1; Jaso DH-1
- CATERPILLAR ECF-2/TO-2; Cummins CES 20078/77/76
- Deutz DQC III-10; John Deere JDQ 78A; MTU Typ 2



DESCRIPTION



Quality engineered in Germany



Turbo Super SHPD 20W50

Super High-Performance Diesel Motor oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Color	Yellowbrown		Visually
Density at 15°C	885	Kg/m ³	DIN EN ISO 12185:1997-11
Kin. Viscosity at 40°C	168,2	mm ² /s	DIN 51659-2:2017-02
Kin. Viscosity at 100°C	18,5	mm ² /s	DIN 51659-2:2017-02
Viscosity index	124		DIN ISO 2909:2004-08
Pourpoint	-30	°C	ASTM D 7346:2015

5. PACKAGING

CONTENTS	ART.NO.	CONTENTS	ART.NO.
Tankware	0326000	20 Liter	9621057
1000 Liter IBC	9621060	4 x 5 Liter	9621056
205 Liter	9621059	12 x 1 Liter	9621055
60 Liter	9621058		

