

DESCRIPTION

emka[®]

Quality engineered in Germany



Supersint LL-12 FE 0W30

HC-Synthese Leichtlauf-Motorenöl für BMW-Fahrzeuge

1. APPLICATION

Supersint LL-12 FE 0W30 is an extremely fuel-efficient Mid SAPS low-friction engine oil based on HC-Synthesis technology for modern petrol and diesel engines, including turbocharged ones, and especially BMW engines, for year-round use. Its special formulation protects the turbocharger from deposits and thus enables maximum performance to be achieved over the long term.

This oil is suitable for maintenance interval extensions in accordance with the manufacturer's specifications.

2. YOUR BENEFIT

- Very good cold start properties.
- Fuel savings under all operating conditions.
- Excellent cleaning and dispersing properties.
- Excellent protection against wear, corrosion and foaming.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA C2, A5/B5;
- API SP (RC);
- ILSAC GF-6A;
- BMW Longlife-12 FE;
- Daimler Truck DTFR 15D100;
- Ford WSS-M2C950-A;
- Mercedes Benz 229.61/227.61;
- VW VWC 53035;



DESCRIPTION



Quality engineered in Germany

Supersint LL-12 FE 0W30

HC-Synthese Leichtlauf-Motorenöl für BMW-Fahrzeuge



4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	841	Kg/m ³	DIN EN ISO 12185:1997-11
Kin. Viscosity at 40°C	54,6	mm ² /s	DIN 51659-2:2017-02
Kin. Viscosity at 100°C	10,4	mm ² /s	DIN 51659-2:2017-02
Viscosity Index	194		DIN ISO 2909:2004-08
Pourpoint	-48	°C	ASTM D 7346:2015
Flashpoint	222	°C	DIN EN ISO 2592:2018-01

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0231000	20 Liter	0231030
205 Liter	0231010	4 x 5 Liter	0231050
60 Liter	0231020	12 x 1 Liter	0231075

