

DESCRIPTION



Supersint SL PCX 0W30

HC-Synthetic low-viscosity engine oil



1. APPLICATION

Supersint SL PCX 0W30 is an HC synthetic-based, extremely fuel-efficient, smooth-running engine oil and can be used in passenger cars with/without turbocharging and especially for VW engines with pump unit injectors.

This oil is suitable for extended oil drain intervals according to manufacturer specifications.

2. YOUR BENEFIT

- Longest maintenance interval extensions possible.
- Excellent cold start properties even at low temperatures.
- Excellent protection against wear, corrosion, deposits and foaming.
- Fuel economy and low exhaust emissions under all operating conditions.
- Very good shear stability, very high viscosity stability and aging resistance.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- ACEA A5/B5
- API SL/CF
- VW 503 00/506 00/506 01



DESCRIPTION



Quality engineered in Germany



Supersint SL PCX 0W30

HC-Synthetic low-viscosity engine oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 15°C	845	Kg/cm ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	52,0	mm ² /s	ASTM D7279
Kin. Viscosity at 100°C	9,9	mm ² /s	ASTM D7279
Viscosity Index	179		ASTM D2270
Flashpoint	221	°C	DIN ISO 2592
Pourpoint	-48	°C	ASTM D7346
Total Base Number (TBN)	9,4	mg KOH/g	ASTM D2896

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
Tankware	0118000	20 Liter	0118030
205 Liter	0118010	4 x 5 Liter	0118050
60 Liter	0118020	12 x 1 Liter	0118070

