DESCRIPTION





Emka RACE Power 20W60

Fully synthetic (PAO/ester) Engine Oil for use in Motorsport

1. APPLICATION

Emka RACE Power 20W60 is an extremely shear-stable, fully synthetic smooth-running engine oil and was specially developed for modern petrol engines for use in motorsports in long-distance and mountain races under the heaviest loads. Due to the pure PAO/ester formulation plus a special additive package and the extreme shear stability, this engine oil shows no loss of viscosity over the entire change interval and is therefore ideally suited for extremely sporty and extremely stressful racing use. It can also (but only) be used in overhauled engines of historic vehicles used in racing.

2. YOUR BENEFIT

- Special additives for racing use.
- Excellent and very stable viscosity behavior.
- Excellent protection against wear, corrosion, foaming.
- Very high HTHS value, resulting in extreme shear stability of the oil film.
- Reliable lubrication during cold starts and at very high operating temperatures.

3. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Color	brown		Visually
Density at 20°C	859	Kg/m³	EN ISO 12185
Kin. Viskosity at 40°C	176,7	mm²/s	DIN 51562-1
Kin. Viskosity at 100°C	24,4	mm²/s	DIN 51562-1
CCS Viskosity at -15°C	5302	mPa*s	ASTM D5293
Viskosity Index	169		DIN ISO 2909
HTHS at 150°C	>5,0	mPa*s	ASTM D5481
Flashpoint	248	°C	DIN EN ISO 2592
Pourpoint	-51	°C	DIN ISO 3016

4. PACKAGING

CONTENTS	ART.NO.	CONTENTS	ART.NO.
205 Liter 60 Liter 20 Liter	0327010 0327020 0327030	4 x 5 Liter 12 x 1 Liter	0327050 0327070



EMKA Schmiertechnik GmbH Schmalbachstrasse 19 74626 Bretzfeld, Germany
 Telefon
 +49 7946 94 470-0

 Telefax
 +49 7946 94 470-70

 E-Mail
 info@emka-oil.de

www.emka-oil.de