

DESCRIPTION

emka[®]

Quality engineered in Germany

Syntogear MP SAE 75W

Fully synthetic manual Transmission oil



1. APPLICATION

This fully synthetic manual transmission oil with the latest additive technology was developed for manual transmissions, especially for BMW and PSA vehicles. It offers outstanding wear protection and sliding properties for smooth and precise gear changes even at very low ambient temperatures and the highest loads. It allows the longest change intervals according to manufacturer specifications.

2. YOUR BENEFIT

- Ensures smooth and precise gear changes.
- Outstanding shear stability and best possible protection against wear.
- Very good viscosity-temperature behavior, excellent thermal stability.
- High-pressure stable lubricating film, even at high temperatures and under the highest loads.

3. TECHNICAL SPECIFICATIONS

Can be used with:

- AC Delco 10-4037; PSA B71 2310/PSA 9730A8
- BMW MTF LT-3 23 00 7 533 818/83 22 0 396 706/83 22 7 533 818
- BOT 350 M3/BOT 303; Fiat 9.55550-MZ6; Ford WSS-M2C200-D3/D2
- GM 19259104/1940004; Mercedes Benz 235.10/A 001 989 840 309
- JWS2271; Opel B0402167; Suzuki 99000-22B27-36
- Toyota 08885-81001/08885-81081; Volvo 1161838/1161839
- VW G 009 317 A2/G 052 171 A2/G 052 512/G 052 527(A2)
- VW G 055 512 A2/G 055 532 A2/G 060 726 A2/G 070 726 A2



DESCRIPTION



Quality engineered in Germany



Syntogear MP SAE 75W

Fully synthetic manual Transmission oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Density at 20°C	840	Kg/m ³	DIN EN ISO 12185
Kin. Viscosity at 40°C	35,1	mm ² /s	DIN 51562-1
Kin. Viscosity at 100°C	7,4	mm ² /s	DIN 51562-1
Viscosity Index	184		DIN ISO 2909
Pourpoint	-48	°C	DIN ISO 3016

5. PACKAGING

CONTENTS	ART.NO.
20 Liter	1123030
4 x 5 Liter	1123050
12 x 1 Liter	1123070

