

DESCRIPTION

emka®

Quality engineered in Germany



Transmatic Multi ATF VI

Synthetic Dexron ATF VI - Automatic Transmission oil

1. APPLICATION

Transmatic Multi ATF VI is a low-viscosity synthetic automatic transmission oil for the latest generation of modern passenger car automatic transmissions. It impresses with its unique shear and oil film strength, as well as the optimized friction properties and wear protection. It meets the requirements of Manufacturers like GM Dexron VI, ZF (Lifeguard 5/6/8), Volvo 97342, Aisin Warner (JWS 3324) and is backwards compatible with all previous Dexron applications.

It also enables extended oil change intervals of up to 240,000 km (the operating regulations of the motor vehicle and gearbox manufacturers must be observed).

2. YOUR BENEFIT

- Optimized friction properties across the entire temperature range.
- Outstanding cooling capacity and high thermal and oxidative stability.
- High level of protection against wear, corrosion and foaming.
- Stable viscosity index and very low pour point, resulting in very good lubricity.

3. TECHNICAL SPECIFICATIONS

Can be used with:

Acura ATF-Z1;Aisin Warner JWS 3324/3309/AW-1;Allison C4/C3;American Motors ATF +3 (MS7176-E) ATF RED 1/1K;BMW/Mini 7045E/83220026922/83220397114/83220403249/ETL8072B/LT71141 (ZF 5HP18FL/19FL/24A)/JWS 3309(T-IV)/LA 2634;Bentley PY112995PA;Bosch TE-ML 09;Caterpillar TO-2 Chrysler AS 68 RC(T-IV)/ATF++/2/+3/+4/JWS 3309/NAG-1/PN05127382AA/6868043742AA/68157995AA/AB 68171866AA/68218925AA;Daewoo LT71141;Daihatsu Ammix ATF D-II/D-III SP;Esso LT71141;Fiat JWS 3309 Ford FNR5/JWS 3309/M2C 138-CJ/166-H/924A/922-A/Mercon/XT-2-QDX(M)/QSM(S)/XT-8-QAW/XT-9- QMM5; Fuso ATF-A4/ ATF-II/SP-III;GM Dexron VI/IIH/IIIG/IIIF/III/IIIE/IIID/II/AW1/ATF Type A(Suffix A)/1940700/ 767/21005966/22717466/88863400/88863401/88900925/93160393/9986195(Aisin AW/JWS 3309); Hino Blue Ribon ATF;Honda ATF Ultra II/DW-1/Type 3.0/3.1/Z-1(except in CVT 's);Hyundai/Kia SPH-VI/ SP-IV RR/SP-IV M/SP-IV/ SP-III(except in CVT 's)/NWS-9638/NUMM040 CH20 Red-1/JWS 3314/ Dex-II/ 040000C90SG;Isemitu K17 3100 PL085;Isuzu Besco 08200-9001/ATF SP/ATF-II/ATF-III/SCS Fluid; JASO M315 Type 2A/1A/LV;Jaguar Land Rover 02JDE26444/ATF 3403 M115/ATF LT71141(ZF5HP24)/ Fluid 8432/JLM 20292/20238/K17/LR0022460/023288/M2C 922-A1/TYK500050;JEEP ATF +3;Lexus JWS 3309; MAN 339 Typ A;MB 236.12/.14/.15/.17/.41;Mazda ATF 3317/ATF D-II/F-1/FZ/M-III/M-V/N-1/S-1;Mitsubishi Diaqueen SP-IV/SK/J3/J2/AW/PA;Nissan Matic C/D/J/K/S/PSA 9730.AE(AL4 autom. gearbox)/ Z000169756/ZF4HP20;Porsche ATF 3403-M115/LT71141(ZFHP19FL/5HP20)/00004320509/00004320528/ 99991754700/T-IV(JWS 3309)/Z000169756;Renault DPO/AL4/Matic D2/Samsung SATF-D;Saab PN93160393/ 93165147/T-IV(JWS 3309);Saturn T-IV;Shell 3403/12108/LA 2634/M115;Ssang Yong DSIH 5M-66; Subaru ATF-5AT/-AW/-HP-D-II/K0710Y0700;Suzuki AT OIL 5D06/ATF 2326/2384K/3309/3314/3317/AW-1; Texaco 7045E/8072B/N402;Toyota D-II/D-III/Hybrid/T-III/T-IV/WS;VW/Audi G052025/055/162/990/ G053025/G055025/162/540/G060162;GUS000162/TL 521 62/LT71141(ZF5HP18FL/19FL/24A); Voith H55.6335.xx/Svc Bltn#13/#118;Volvo 97342(AT102)/97340/97335/97325/1161540/1621/1640/ 31256675/774;ZF 3HP/4HP/5HP/6HP/8HP/9HP/Lifeguard Fluid 5/6/8/TE-ML 05L/09/11A/11B/21L



DESCRIPTION



Quality engineered in Germany



Transmatic Multi ATF VI

Synthetic Dexron ATF VI - Automatic Transmission oil

4. TECHNICAL CHARACTERISTICS

Properties	Data	Units	Test
Color	Red		Visually
Density at 15°C	847	Kg/m ³	D 4052
Kin. Viscosity at 40°C	29,8	mm ² /s	D 445
Kin. Viscosity at 100°C	6,0	mm ² /s	D 445
Viscosity Index	151		D 2270
Pourpoint	-54	°C	D 97
Flashpoint	>200	°C	D 92

5. PACKAGING

CONTENT	ART.NO.	CONTENT	ART.NO.
205 Liter	1432010	4 x 5 Liter	1432050
60 Liter	1432020	12 x 1 Liter	1432070
20 Liter	1432030		

